# GOVERNMENT OF THE PUNJAS

#### FINANCE DEPARTMENT



#### TABLE OF CONTENTS

Ch.No.	Chapter	Pa	ige N	los
01.	Carriage	3	to	23
02.	Loading, Unloading & Stacking	24	to	26
03.	Earthwork (Excavation & Embankment)	27	to	33
04.	Dismantling (Demolition)	34	to	38
05.	Mortar.	39	to	40
06.	Concrete	41	to	50
07.	Brickwork	51	to	56
08.	Stone Masonry	57	to	59
09.	Roofing	60	to	65
10.	Flooring.	66	to	70
11.	Surface Rendering	71	to	74
12.	Wood Work	75	to	84
13.	Painting & Varnishing.	85	to	90
14.	Lining of Canals	91	to	92
15.	Sheet Piling	93	to	94
16.	Protection & Diversion Work	95	to	104
17.	Outlets	105	to	106
18.	Road & Road Structure	107	to	111
19.	Plumbing, Sanitary Installation & Gas Fittings	112	to	118
20.	Surface Drainage.	119	to	120
21.	Sewerage	121	to	125
22.	Sinking of Wells	126	to	128
23.	Tubewell & Water Supply	129	to	141
24.	Electric Installation	142	to	154
25.	Iron Work	155	to	160
26.	Miscellaneous	161	to	164

#### 1. CARRIAGE

Note: 1 The rates are applicable to carriage of material on pacca roads only.

For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.

Note: 2 For hilly areas 80% above the rates in the plain areas shall be allowed for total mileage (Km) covered.

Note: 3 In case of articles longer than 15 ft. (4.6 m) carried in trucks, the following rates shall be allowed:-

- i) Above 15 ft. to 25 ft. (4.6 to 7.6 m): Total rates to be paid for 15 ft. to 25 ft. (4.6 to 7.6 m) length will be 1.5 times of the rate given in the Composite Schedule of Rates.
- ii) Above 25 ft. (7.6 m): The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.

The length measured shall not be the actual length, but the length of the form of consignment as actually received.

- Note: 4 The term 'mile' (Km) whenever used is to mean statute mile (Km).
- Note: 5 The rates include loading and unloading of material from the conveyance and stacking as directed.

Note: 6 The rates for carriage by boat or steamer shall be the same as by any other mechanical means on land.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr. No.	Description	-			R Unit of M/ment			Spec. No.	Remarks			
1	Carriage of 100 Cft. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cft. (4.25 cu.m) of timber, by truck or by any other means owned by the contractor.	Fi	iance (	Departi	nent		·	16.1	Add 20% extra for the item "Recouping of Reserve Stock of stone for Flood Protection Work in Irrigation Department".			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30M 30M 30M 300 M	182.05 33.35 20.85 204.25						
	1st Km 2nd Km 3rd Km 4th Km				Km Km Km Km	190.90 89.20 67.50 46.35						
	5th Km 6th Km 7th Km 8th Km				Km Km Km Km	42.85 42.05 38.85 38.35						
	9th Km 10th Km 11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms				Km Km Km Km Km	35.75 33.10 25.25 3.25 2.00						

	MRS, 1st BI-ANNUAL	-2019 (1s	t JANUARY	2019 to 30th	JUNE-20	019) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
2	Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastenings, points and crossing, Bridge Girders, pipes, sheets, Rail, M.S. bars, etc. etc. by truck or any other means owned by the contractor.							16.1	Cement carried in containers other than bags will be paid according to this item. The word "pipes" covers G.I,C.I,R.C.C. and P.C.C.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km		Xt.		30M 30M 30M 300M Km Km Km	182.05 33.35 20.85 204.25 190.90 89.20 67.50 46.35			
	5th Km	,	70	/ \	Km	42.85			
	6th Km	146	The state of the s		Km	42.05			
	7th Km	13			Km	38.85			
	8th Km 9th Km	\$35	-	-7	Km Km	38.35 35.75			
	10th Km	6.177			Km	33.10			
3	11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms Carriage of 100 maunds of fuel wood by truck	Ti	iance (	SS <sup>28</sup> Departs	Km Km Km	25.25 3.25 2.00		16.1	
	or any other means owned by the contractor:  1st chain (1st 30 m)  2nd chain (2nd 30 m)  3rd to 10th chain (60 to 300 m)  1000 to 3000 ft. (300 to 900 m)  1st Km  2nd Km  3rd Km  4th Km				30 M 30 M 30 M 300 M Km Km Km	182.05 33.35 20.85 204.25 190.90 89.20 67.50 46.35			
	5th Km				Km	42.85			
	6th Km				Km	42.05			
	7th Km				Km	38.85			
	8th Km				Km	38.35			
	9th Km				Km	35.75			

	MRS, 1st BI-ANNUAL	2019 (1s	t JANUARY	2019 to 30th	JUNE-20	019) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	10th Km				Km	33.10			
4	11th & subsequent Kms Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm) or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or any other means owned by the contractor :-				Km	25.25		ditto	Reduce the rate by 33% in case of carriage of 1000 Nos. tiles size 12"x6"x11/4" (300 x 150 x 30 mm).
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	182.05 33.35 20.85 204.25 190.90			
	2nd Km		and the second second	and the same of th	Km	89.20			
	3rd Km 4th Km		/ ×		Km Km	67.50 46.35			
	5th Km	/		\	Km	42.85			
	6th Km		76		Km	42.05			
	7th Km	100		= 7	Km	38.85			
	8th Km	- F			Km	38.35			
	9th Km			9 Feb. 100	Km	35.75			
	10th Km	Fi	iance (	Departi	Km	33.10			
5	11th & subsequent Kms Carriage of 100 cft. (2.83 cu.m) of all material like stone, aggregate, spawl, kankar lime(unslaked), surkhi, etc. or 150 cft. (4.25 cu.m) of timber, by means of material trolly.				Km	25.25		16.1	Material trolly to be supplied by the Government and maintained and run by the contractor.
	1st chain (1st 30 m) 2nd chain to 10th chain (2nd 30 m to 300 m)				30 M 30 M	182.05 33.35			
	1000 to 3000 ft. (300 to 900 m)				300 M	204.25			
	1st Km 2nd Km				Km Km	156.55 118.30			
	3rd Km				Km	62.00			
	4th Km				Km	48.00			
	5th Km				Km	42.05			
	6th Km				Km	40.35			
	7th Km 8th Km				Km Km	33.90 33.45			
	9th Km				Km	33.45			
	10th Km				Km	28.85			
	11th Kms to 200Kms				Km	23.70			
	201 Kms to 250 Kms				Km	3.25			
	251 Kms & susequent Kms				Km	2.00			

	MRS, 1st BI-ANNUAL	-2019 (1s	t JANUARY	2019 to 30th	JUNE-20	019) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
<b>No.</b>	Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastening, points and crossing, Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by means of material trolly.  1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km 8th Km 9th Km 10th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms Carriage of 100 maunds of fuel wood, by means of material trolly.  1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 5th Km	- 300 M	i ance	Departs	Unit of			No.	Material trolly to be supplied by the Government and maintained and run by the contractor.  Material trolly to be supplied by the Government and maintained and run by the contractor.
	7th Km				Km	33.90			
	8th Km				Km	33.45			
	9th Km				Km	31.20			
	10th Km				Km	28.85			
8	11th & subsequent Kms Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm), by means of material trolly. 1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	23.70 182.05 33.35 204.25 156.55		ditto	Material trolly to be supplied by the Government and maintained and run by the contractor.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks		
No.					Unit of M/ment	Labour	Composite	No.			
	2nd Km 3rd Km 4th Km				Km Km Km	118.30 62.00 48.00		16.1			
	5th Km				Km	42.05					
	6th Km				Km	40.35					
	7th Km				Km	33.90					
	8th.				Km	33.45					
	9th Km		×.		Km	31.20					
	10th Km	/	/ ·		Km	28.85					
9	11th & subsequent Kms Carriage of 1000 No. bricks, 9"x4½"x3" (225x113x75 mm) or 8"x4"x4" (200x100x100 mm) (nominal)  1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km		rance (	Departs	30 M 30 M 30 M 30 M 300 M Km Km Km	23.70 149.16 31.90 17.11 167.22 156.50 72.95 55.30 38.25		ditto			
	5th Km				Km	36.15					
	6th Km				Km	35.30					
	7th Km				Km	31.80					
	8th Km				Km	31.40					
	9th Km				Km	29.30					
	10th Km				Km	27.10					
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½" (225x113x38 mm).				Km	20.60		16.1			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	90.02 16.47 10.23 101.02 94.45		16.1			

	MRS, 1st BI-ANNUAL	-2019 (1st	t JANUARY	-2019 to 30th	JUNE-20	)19) DIST	RICT ATTOC	K	
Sr.	Description				R	ate (M <i>e</i> tric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	2nd Km 3rd Km 4th Km				Km Km Km	44.15 33.40 22.90			
	5th Km				Km	21.05			
	6th Km				Km	20.70			
	7th Km				Km	19.20			
	8th Km				Km	19.00			
	9th Km		-		Km	17.70			
	10th Km		/ ×	) \	Km	16.45			
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.	/	4	\	Km	12.45		ditto	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	188	- DE		30 M 30 M 30 M	3.43 0.41 0.20		artto	
	1000 to 3000 ft. (300 to 900 m)	- 6			300 M	2.01			
	1st Km		***	2	Km	2.35			
	2nd Km	Fir	iance (	Departi	Km	1.60			
	3rd Km				Km	0.70			
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including bundling.				Km	0.40		16.1	
	1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft.				300 M 300 M	50.11 6.24			
	1st Km				Km	5.75			
	2nd Km				Km	5.50			
	3rd Km				Km	2.55			
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash or brushwood, by boat or road:-				Km	2.20		ditto	Previous lead of collection not to be deducted from the next lead of carriage.
	1st chain (1st 30 m)				30 M	74.48			

	MRS, 1st BI-ANNUAL	2019 (1s	t JANUARY	-2019 to 30th	JUNE-20	)19) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	33.35 10.23			
	1000 to 3000 ft. (300 to 900 m)				300 M	83.91			
	1st Km				Km	88.45			
	2nd Km				Km	44.15			
	3rd Km				Km	33.40			
	4th Km		-		Km	22.90			
	5th Km		/ ×	) \	Km	21.05			
	6th Km	1		\	Km	20.70			
	7th Km	8 8			Km	19.20			
	8th Km	100			Km	19.00			
	9th Km 10th Km	617	126	ر الراق المستدار المراق المستدار المراق المستدار المراق المستدار المراق المستدار المراق المستدار المراق المستد	Km Km	17.70 16.45			
	11th Km & subsequent	-85		<b>5</b> 4 2 8	Km	12.45			
	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre)	CX - Y -		50	Tonne 300 M	607.11		ditto	
	Exceeding 1000 to 5000 ft (300 to 1500metre)	7.11	iance (	Departi	300 IVI	147.10			
	1st Km				Km	187.80			
	2nd Km				Km	87.15			
	3rd Km				Km	58.65			
	4th Km				Km	37.55			
	5th Km				Km	35.45			
	6th Km				Km	34.00			
	7th Km				Km	29.30			
	8th Km				Km	28.90			
	9th Km 10th Km				Km Km	28.25 22.25			
	11th Km & susequent				Km	18.70			

	MRS, 1st BI-ANNUAL	-2019 (1st	JANUARY-	2019 to 30th	JUNE-20	)19) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
15	Carriage of small consignments weighing upto 5 maunds (job rates):							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%; and for consignments weighing 10
	Upto 1000 ft. (300 metre)				Consign- ment/	49.30			to 20 maunds, rate be increased by 100%.
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				300 M	33.81			
	1st Km				Consign- ment/ Km				
	2nd Km		-	and the same of th	"	18.25			
16	3rd Km & subsequent Carriage of consignments job.	/	/ ×		"	6.00			
	i) Cooly load for distance:-				Each				
	a) Upto 5 Km b) Above 5 to 13 Km		NOV.		Consignmer	59.60 134.85			
	ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ½ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km		iance (	Departs	Each Consignmer "" ""	10.85 16.45 20.80 26.00 45.95 82.25			
	iii) Cart load for a distance:-				Each Consig- nment				
	a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to10 Miles(16 Km)				"	89.85 163.55			
	iv) Camel load for a distance:-								
	a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km)				"	66.45 100.75			
17	Hire charges of:-								1. This item will be allowed with
	i) truck (10 Ton Capacity)				Per	3000.00			prior concurrence of Superintending Engineer.
	ii) tractor with trolly				day "	1000.00			2. The rate includes pay of driver and cleaner only. The repairs shall be the removed hills of the current
	iii) tractor without trolly				11	800.00			be the responsibility of the owner and the cost of lubrication, fuel,

	MRS, 1st BI-ANNUAL	-2019 (1s	t JANUARY	-2019 to 30th	JUNE-20	019) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
									loading and unloading shall be paid by the borrower.
18	Carriage of bitumen, tar or other lubricants, in drums:  0 Kilometer to 100 Kilometers  0 Kilometer to 200 Kilometers  0 Kilometer to 250 Kilometers  251 to susequent Kilometers				P.Ton P.Ton P.Ton P.Ton	1256.30 1651.45 1921.45 8.55		16.1	
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-		/ ×	)					
	i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	100 K			30 M 30 M 30 M 300 M Km Km Km	7.20 1.30 0.80 8.05 7.50 3.50 2.65			
	4th Km			0 5	Km	1.80			
	5th Km	Fi	tance (	Departi	Km	1.65			
	6th Km				Km	1.60			
	7th Km				Km	1.50			
	8th Km				Km	1.45			
	9th Km				Km	1.40			
	10th Km				Km	1.30			
	11th Km & Susequent				Km	1.25			
	ii) 4" (100 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	9.40 1.70 1.10			
	1000 to 9000 ft. (300 to 900 m)				300 M	10.55			

	MRS, 1st BI-ANNUAL	-2019 (1s	t JANUARY	-2019 to 30th	JUNE-20	)19) DIST	RICT ATTOC	K	
Sr.	Description					ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st Km				Km	9.90			
	2nd Km				Km	4.60			
	3rd Km				Km	3.45			
	4th Km				Km	2.35			
	5th Km				Km	2.20			
	6th Km				Km	2.10			
	7th Km		并		Km	2.00			
	8th Km 9th Km 10th Km 11th Km & subsequent Km	1			Km Km Km Km	1.90 1.80 1.70 1.65			
	iii) 6" (150 mm) i/d pipes:-	18			83				
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 9000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Fin	iance (	Departs	30 M 30 M 30 M 300 M Km Km Km	14.10 2.60 1.60 15.85 14.80 6.90 5.20			
	4th Km				Km	3.60			
	5th Km				Km	3.30			
	6th Km				Km	3.25			
	7th Km				Km	3.00			
	8th Km				Km	2.85			
	9th Km				Km	2.75			
	10th Km 11th Km & subsequent Km iv) 8" (200 mm) i/d pipes:				Km Km	2.55 2.20			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	23.90 4.40 2.75 26.80 25.05			

	MRS, 1st BI-ANNU	\L-2019 (1s	t JANUARY	-2019 to 30th	JUNE-20	019) DIST	RICT ATTOC	K	
Sr.	Description				R	ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	2nd Km 3rd Km				Km Km	12.05 9.00			
	4th Km				Km	6.15			
	5th Km				Km	5.65			
	6th Km				Km	5.55			
	7th Km				Km	5.15			
	8th Km				Km	4.95			
	9th Km		N.		Km	4.45			
	10th Km 11th Km & subsequent Km		-	/_ \	Km Km	2.50 1.80			
	v) 10" (250 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	32.1 5.90 3.65 36.05 33.70 15.65 11.80			
	4th Km	Fii	rance (	Departi	Km	8.05			
	5th Km				Km	7.45			
	6th Km				Km	7.30			
	7th Km				Km	7.00			
	8th Km				Km	6.90			
	9th Km				Km	6.45			
	10th Km 11th Km & subsequent Kms				Km Km	5.95 4.50			
	vi) 12" (300 mm) i/d pipes: 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	41.75 7.65 4.80 46.85 43.80 21.30 15.75			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks		
No.	·				Unit of M/ment		Composite	No.			
	4th Km				Km	10.50					
	5th Km				Km	9.70					
	6th Km				Km	9.50					
	7th Km				Km	8.75					
	8th Km				Km	8.65					
	9th Km				Km	8.05					
	10th Km		¥-	1	Km	7.45					
	11th Km & subsequent Kms	/	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		Km	5.75					
	vii) 16" (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	8			30 M 30 M 30 M 300 M Km Km Km	68.45 12.55 7.85 76.80 71.75 33.80 25.35					
	4th Km	(Kin	iancs (	Downsta	Km	17.40					
	5th Km	2. 27	rankus 1	oppus es	Km	16.10					
	6th Km				Km	15.80					
	7th Km				Km	14.55					
	8th Km				Km	14.40					
	9th Km				Km	13.40					
	10th Km 11th Km & subsequent Kms viii) <b>18" (450 mm) i/d pipes:-</b>				Km Km	12.40 9.50					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	87.95 16.10 10.05 98.70 92.20 43.10 32.60					

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description					ate (Metric	System)	Spec.	Remarks		
No.					Unit of M/ment	Labour	Composite	No.			
	4th Km				Km	22.40					
	5th Km				Km	20.70					
	6th Km				Km	20.30					
	7th Km				Km	18.75					
	8th Km				Km	18.55					
	9th Km				Km	17.30					
	10th Km 11th Km & subsequent Kms ix) 20" (500 mm) i/d pipes:-	/	/ ¥		Km Km	16.00 12.10					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	W. C.			30 M 30 M 30 M 300 M Km Km Km	93.35 17.10 10.70 104.75 97.90 45.75 34.60					
	4th Km	7775.		FR	Km	23.75					
	5th Km		iance (	Departi	Km	21.95					
	6th Km				Km	21.55					
	7th Km				Km	19.90					
	8th Km				Km	19.65					
	9th Km				Km	18.30					
	10th Km 11th Km & subsequent Kms x) <b>24" (600 mm) i/d pipes:-</b>				Km Km	16.95 13.05					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 5000 ft. (300 to 1500 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	103.40 18.95 11.85 116.05 108.45 50.65 38.30					

	MRS, 1st BI-ANNUAL	-2019 (1s	-2019 to 30th	th JUNE-2019) DISTRICT ATTOCK					
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	5th Km				Km	24.30			
	6th Km				Km	23.85			
	7th Km				Km	22.00			
	8th Km				Km	21.75			
	9th Km				Km	20.25			
20	10th Km 11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading, unloading and stacking (Rate per 1000 ft.) (300 metre):-	,	*		Km Km	18.75 14.25			
	i) 3" (75 mm) i/d pipes:-  1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	W. C.			30 M 30 M 30 M 300 M Km Km Km	14.10 2.60 1.60 15.80 14.80 6.90 5.20			
	4th Km	Ti	iance (	Departs	Km	3.55			
	5th Km				Km	3.30			
	6th Km				Km.	3.25			
	7th Km				Km	3.00			
	8th Km				Km	2.95			
	9th Km				Km	2.75			
	10th Km 11th Km & subsequent Kms ii) <b>4" (100 mm) i/d pipes:</b> -				Km Km	2.50 2.10			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	21.70 4.00 2.50 24.35 22.75 10.80			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description					ate (Metric	System)	Spec.	Remarks			
No.					Unit of M/ment	Labour	Composite	No.				
	3rd Km				Km	8.05						
	4th Km				Km	5.45						
	5th Km				Km	5.00						
	6th Km				Km	4.90						
	7th Km				Km	4.55						
	8th Km				Km	4.50						
	9th Km		1		Km	4.20						
	10th Km 11th Km & subsequent Kms iii) 5" (125 mm) i/d pipes:-	. /	\(\frac{\times}{2}\)		Km Km	3.85 3.40						
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M " 300 M Km "	29.60 5.45 3.40 33.25 31.05 14.65 11.10						
	4th Km	Ti	iance (	Departi	nent	7.65						
	5th Km				Km.	6.90						
	6th Km				11	6.75						
	7th Km				11	6.25						
	8th Km					6.15						
	9th Km					5.75						
	10th Km 11th Km & subsequent Kms					5.30 4.10						
	iv) 6" (150 mm) i/d pipes:											
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 300 m) 1st Km. 2nd Km				30 M 30 M 30 M 300 M Km. Km.	40.80 7.50 4.65 45.80 42.80 20.00						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description					ate (Metric	System)	Spec.	Remarks		
No.					Unit of M/ment	Labour	Composite	No.			
	3rd Km				Km.	15.15					
	4th Km				Km.	10.40					
	5th Km				Km.	9.60					
	6th Km				Km.	9.45					
	7th Km				Km.	8.70					
	8th Km				Km.	8.60					
	9th Km		production is		Km.	8.05					
	10th Km	<i>j</i>	#-		Km.	7.45					
	11th Km & subsequent Kms v) 8" (200 mm) i/d pipes:-	11/			Km.	5.65					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	71.60 13.10 8.20 80.35 75.05 35.10 26.55					
	4th Km	777	iance (	Departi	Km	18.25					
	5th Km				Km	16.85					
	6th Km				Km	16.55					
	7th Km				Km	15.25					
	8th Km				Km	15.10					
	9th Km				Km	14.10					
	10th Km 11th Km & subsequent Kms vi) <b>10" (250 mm) i/d pipes:</b> -				Km Km	13.00 9.90					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	111.00 20.35 12.70 124.55 116.40 54.40					

	MRS, 1st BI-ANNU	L-2019 (1st JANU	ARY-2019 to 30t	h JUNE-20	019) DIST	RICT ATTOC	K	_
Sr.	Description			R	ate (Metric	System)	Spec.	Remarks
No.				Unit of M/ment	Labour	Composite	No.	
	3rd Km			Km	41.15			
	4th Km			Km	28.25			
	5th Km			Km	26.10			
	6th Km			Km	25.60			
	7th Km			Km	23.65			
	8th Km			Km	23.40			
	9th Km		H. T.	Km	21.80			
	10th Km 11th Km & subsequent Kms		7	Km Km	20.20 15.45			
	vii) 12" (300 mm) i/d pipes:-	164		J.W				
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km			30 M 30 M 30 M 300 M Km Km Km	156.25 28.65 17.90 175.35 163.85 76.55 57.90			
	4th Km	Tinano	z svepari	Km	39.75			
	5th Km			Km	36.75			
	6th Km			Km	36.05			
	7th Km			Km	33.30			
	8th Km			Km	32.90			
	9th Km			Km	30.70			
	10th Km 11th Km & subsequent Kms			Km Km	28.40 21.70			
	viii) 14" (350 mm) i/d pipes:-							
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km			30 M 30 M 30 M 300 M Km Km	203.40 37.25 23.25 228.25 213.30 99.65			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description				R	ate (Metric	Svstem)	Spec.	Remarks			
No.					Unit of	•		No.				
	3rd Km				M/ment Km	<b>Labour</b> 75.40	Composite					
					NIII	75.40						
	4th Km				Km	51.80						
	5th Km				Km	47.85						
	6th Km				Km	46.95						
	7th Km				Km	43.35						
	8th Km				Km	42.85						
	9th Km		ist-		Km	39.95						
	10th Km 11th Km & subsequent Kms	1	/ ·		Km Km	37.00 28.30						
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-	183			14	_0.00						
	i) 2" (50 mm) i/d pipes:-  1st chain (1st 30 m)  2nd chain (2nd 30 m)  3rd to 10th chain (60 to 300 m)  1000 to 3000 ft. (300 to 900 m)  1st Km  2nd Km  3rd Km	18	rance (	Departs	30 M 30 M 30 M 300 M Km Km Km	10.30 1.90 1.20 11.55 10.80 5.05 3.85						
	4th Km				Km	2.65						
	5th Km				Km	2.45						
	6th Km				Km	2.40						
	7th Km				Km	2.20						
	8th Km				Km	2.15						
	9th Km				Km	2.00						
	10Km 11th Km & subsequent Kms				Km Km	1.85 1.45						
	ii) 2½" (63 mm) i/d pipes:-											
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30 M 30 M 30 M 300 M	16.00 2.95 1.85 18.00						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks			
No.					Unit of M/ment	Labour	Composite	No.				
	1st Km 2nd Km 3rd Km				Km Km Km	16.80 7.90 6.00	·					
	4th Km				Km	4.10						
	5th Km				Km	3.80						
	6th Km				Km	3.75						
	7th Km				Km	3.45						
	8th Km				Km	3.20						
	9th Km		, S.		Km	3.10						
	10Km 11th Km & subsequent Kms iii) 3" (75 mm) i/d pipes- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	3000			Km Km 30 M 30 M 30 M	2.85 2.25 22.20 4.05 2.55						
	1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km	Fi	iance (	Separts	300 M Km Km Km Km	24.90 23.25 10.90 8.25 5.65						
	5th Km				Km	5.25						
	6th Km				Km	5.15						
	7th Km				Km	4.75						
	8th Km				Km	4.70						
	9th Km				Km	4.25						
	10th Km 11th Km & subsequent Kms				Km Km	3.95 3.10						
	iv) 4" (100 mm) i/d pipes- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	36.75 6.75 4.20 41.25 38.55 18.00						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description					ate (Metric	System)	Spec.	Remarks		
No.					Unit of M/ment	Labour	Composite	No.			
	3rd Km				Km	13.60					
	4th Km				Km	9.35					
	5th Km				Km	8.65					
	6th Km				Km	8.50					
	7th Km				Km	7.90					
	8th Km				Km	7.70					
	9th Km		33.		Km	7.20					
	10th Km 11th Km & subsequent Kms	. /	-	_ \	Km Km	6.60 5.20					
v)	5" (125 mm) i/d pipes-	8			122						
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		ance (	Departs	30 M 30 M 30 M 300 M Km Km Km	54.95 10.05 6.30 61.65 57.60 26.90 20.35					
	4th Km			8	Km	14.00					
	5th Km				Km	12.90					
	6th Km				Km	12.65					
	7th Km				Km	11.70					
	8th Km				Km	11.55					
	9th Km				Km	10.80					
	10th Km 11th Km & subsequent Kms				Km Km	9.90 7.70					
V	•										
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	79.15 14.50 9.05 88.80 83.00					
	2nd Km				Km	38.80	_				

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description					ate (Metric	System)	Spec.	Remarks			
No.					Unit of M/ment	Labour	Composite	No.				
	3rd Km				Km	29.30						
	4th Km				Km	20.15						
	5th Km				Km	18.60						
	6th Km				Km	18.25						
	7th Km				Km	16.90						
	8th Km				Km	16.65						
	9th Km				Km	15.55						
	10th Km				Km	14.35						
22	11th Km & subsequent Kms				Km	11.10						
	Hand shunting loaded Railway wagons or trucks:-		-									
	a) upto ¼ mile / ¼ Km		14	) \	Each	175.40						
	b) upto ½ mile / ½ Km	/	Te		No	317.55						
	c) upto ¾ mile / ¾ Km	1. 1.	and the second second		"	428.70						
	d) upto 1 (1.6 Km) mile	184 F		and the same of th	" Each	510.15						
	e) 2nd mile and subsequent miles/ 2nd and subsequent kilometres				No/Km	308.55						
23	Hand shunting empty Railway wagons or trucks.	18	15-6			000.00						
	a) upto ¼ mile / ¼ Km	-63		100	Each	101.75						
	b) upto ½ mile/ ½ Km				No.	168.60						
	c) upto 3/4 mile / 3/4 Km				"	222.30 266.85						
	d) upto 1 mile / 1 Km e) 2nd mile and subsequent miles/	Fi	iance (	Devarti	Each	∠00.85						
	2nd and subsequent kilometres				No/Km	151.45						

# 2. LOADING, UNLOADING & STACKING

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	Ra	te (British Sys	stem)	Rat	te (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Loading or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	609.30		cu.m	215.20						
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-		/ ×									
	a) Bricks 10" (250 mm) size.	1000 Nos.	761.65	1	1000 Nos.	761.65						
	b) Bricks 9" (225 mm) or smaller size.	ditto	609.30		ditto	609.30						
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	761.65		100 Bags	761.65						
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	73.10		100 Nos.	73.10						
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	457.00	Depari	100 Kg	12.25						
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	365.60		Per Tonne	359.80						
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	45.70		Each	45.70						
8	Loading or unloading packages of all sorts, upto one Cwt (50 Kg). Loading or unloading sleepers other than wooden, including stacking lead within one chain:-	Each	22.85		Each	22.85			Except cement in jute or paper bags.			
	a) Broad gauge sleepers	100 Nos.	1523.30		100 Nos.	1523.30						
	b) Metre gauge and narrow gauge sleepers.	ditto	761.65		ditto	761.65						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	Ra	nte (British Sys	stem)	Rat	te (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
							•						
10	Loading or unloading timber logs or timber for shuttering, into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Per Ton	190.4		Per Tonne	187.4							
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	1827.95		100 Kg	49							
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	304.65		Per Tonne	299.85							
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	225.45		cu.m	79.65							
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	292.45	)	cu.m	103.30							
15	Unloading oil, bitumen tar, etc.	8											
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	761.65		100 litres	16.75							
	b) Crude oil (drained by gravity).	1000 Gallon	761.65	<b>4</b> 2	100 litres	16.75							
	c) Crude oil materials from railway wagons.	100 Cft.	97.50	Depari	cu.m	34.45							
	d) Fuel oil from tank into empty drums, including stacking within one chain (30 m).	Per Ton	270.80	100	Per Tonne	266.55							
	e) Petrol (2 gallon tin)	100 Nos.	383.85		100 Nos.	383.85			The rate includes checking and weighing the tins.				
16	f) Kerosene oil (4 gallon tin) Removing and stacking within one chain (30 m) lead:	100 Nos.	761.65		100 Nos.	761.65			and weighing the tins.				
	a) Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc.	100 Cft.	304.65		cu.m	107.60							
	b) Bricks.	1000 Nos.	812.40		1000 Nos.	812.40							
	c) Broad gauge wooden sleepers.	100 Nos.	487.45		100 Nos.	487.45							
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	290.15		100 Nos.	290.15							
	e) Rails girders, pipes, cement etc.	Per Ton	135.40		Per Tonne	133.25							

Page 25

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	Ra	te (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	f) Bridge and crossing timbers, etc.	100 No.	1624.85		100 No.	1624.85					
17	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	304.65		Per Tonne	299.85					
18	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	174.10		Per Tonne	171.35					
19	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	1218.60		100 Nos.	1218.60					
20	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	580.30	)	100 Nos.	580.30					
21	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	609.30		100 Nos.	609.30					
22	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	320.70		100 Nos.	320.70					
23	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	2437.25		100 Nos.	2437.25					
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	1218.60	vepari	100 Nos.	1218.60					
25	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	182.80		Per Tonne	179.90					

### 3. EARTHWORK (EXCAVATION & EMBANKMENT)

- 1 Special allowances for the hardness, wetness and slush:-
  - The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.
- 2 Deduction for shrinkage from bank measurements:-
  - The following allowances should be provided for material which is not rammed, or equally consolidated:-
  - a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour.......... 10%
  - b) Deduction for settlement from the bank measurement when the earthwork is done by machines................................. 3 to 6%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors.

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description	F	Rate (British Sy	stem)	Rate (Metric System)			Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
1	Earthwork excavation undressed lead upto a single throw of Kassi, phaorah or shovel:-	100			) W.			171 to 17.5	
	a) In ashes, sand, soft soil or silt clearance. b) In ordinary soil.	1000 Cft. 1000 Cft.	2,284.90 2,741.90		cu.m cu.m	80.70 96.85			
2	Earthwork excavation in ashes, sand and soft soil or silt clearance, undressed lead upto 50 ft (15 metre).	1000 Cft.	3,351.20		cu.m	118.35		ditto	
3	Bed clearance and dressing slopes of drains to required sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead.  a) Excavated material undressed.  b) Excavated material dressed in the specified manner.	1000 Cft. 1000 Cft.	4,265.20 4,613.65	Depari <del>-</del>	cu.m cu.m	150.65 162.95	 	ditto	The rate is applicable where the earth of the bed to be removed is of the type of ordinary soil. When it is silt or 1 or 2 above, whichever is applicable. the drains of each category.
4	Borrowpit excavation undressed lead upto 100 ft (30 metre).  a) Ordinary soil  b) Hard soil	1000 Cft. 1000 Cft.	4,265.20 5,240.10	 	cu.m cu.m	150.65 185.10	 		
5	Earthowrk in ordinary soil for embankments lead upto 100 ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete in all							* 411-1 to 411-13 and 301-1 & 202-3	The rate includes hire charges of machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also includes clearing and grubbing where necessary.
6	respects:- i) 95% to 100% maximum modified AASHO dry density. ii) 90% maximum modified AASHO dry density. iii) 85% maximum modified AASHO dry density. Regular excavation dressed.	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	4,655.10 4,655.10 4,655.10 3,141.70	5,420.85 5,300.55 5,180.25	cu.m cu.m cu.m cu.m	164.40 164.40 164.40 110.95	191.45 187.20 182.95 	*411-2	
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from							17.1 to 17.5	

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	,	Rate (British Sy	etem)	R	ate (Metric	Svetem)	Spec.	Remarks		
No.	Desarption	Unit of			Unit of			No.	Kanarka		
		M/ment	Labour	Composite	M/ment	Labour	Composite				
	trenches, back filling and surplus excavated material										
	disposed of and dressed within 50 ft. (15 m) lead:-										
	i) ordinary	1000 Cft.	5,341.80	5,419.05	cu.m	188.65	191.40				
	ii) hard	1000 Cft.	6,316.70	6,393.95	cu.m	223.10	225.85				
	iii) very hard iv) gravel & shingle	1000 Cft. 1000 Cft.	7,352.50 12,373.15	7,429.80 12,450.45	cu.m cu.m	259.70 437.00	262.40 439.75				
	graver & simgle	1000 Cit.	12,373.13	12,430.43	Cu.III	437.00	439.73				
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to							ditto			
	10.0 ft. (3.0 mm) depth for storm water channels, drains,										
	sullage drains in open areas, roads, streets, lanes, including										
	under pinning of walls and shoring to protect existing works,			and the same of th							
	shuttering and timbering the trenches, dressed to designed			6 1 3							
	level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material		/ 1	' ) \							
	disposed of and dressed within 100 ft. (30 m) lead:-		/	10000	\						
	i) ordinary	1000 Cft.	5,812.75	5,966.45	cu.m	205.30	210.75				
	ii) hard	1000 Cft.	6,787.65	6,941.35	cu.m	239.75	245.15				
	iii) very hard	1000 Cft.	7,823.50	7,977.20	cu.m	276.35	281.75				
	iv) gravel & shingle	1000 Cft.	13,453.45	13,607.15	cu.m	475.20	480.60				
		464/	1776		459			4-4.4			
9	Excavation in shingle or gravel formation and rock, not	5.00	the latest the same of the sam		1774			17.1 to 17.5			
	requiring blasting, undressed lead upto 100 ft (30 m). i) Dry	1000 Cft.	11,576.95		cu.m	408.90					
	ii) Wet	1000 Cft.	13,404.85		cu.m	473.45					
	iii) In flowing water	1000 Cft.	17,060.75	Butter	cu.m	602.60					
		72.13	HUHLE	wepun	3326321						
10	Earthwork excavation in irrigation channels, drains, etc. to							_			
	designed section, grades and profiles, excavated material							ditto			
	disposed off and dressed within 50 ft. (15 m) lead:-										
	i) ordinary	1000 Cft.	4,898.80		cu.m	173.05					
	ii) hard	1000 Cft.	5,873.70		cu.m	207.45					
	iii) very hard	1000 Cft.	6,909.50		cu.m	244.05					
	iv) gravel & shingle	1000 Cft.	12,234.80		cu.m	432.15					
11	Excavation in rock dressed to designed section, grades and										
	profiles, excavated material disposed off within 100 ft. (30 m)							17.1 to 17.5	Tools and plants shall be the liability		
	and lift upto 5'-0" (1.5 m).	1000 Cft.	11,698.35		011.00	442.20			of the contractor.		
	Soft rock, slate, shale, schist laterite work, with pick and crow bar.	1000 Cit.	11,096.33		cu.m	413.20					
	b) Medium hard rock, requiring occasional blasting.	1000 Cft.	18,508.15	19,098.55	cu.m	653.70	674.55				
			,	, <b>-</b>							
12											
1	of excavated material (blasted material) upto 50 ft. (15							17.1 to 17.5	1) Tools and plants required shall be		
1	m) lead, (including dressing and leveling to designed								the liability of the Contractor		
	section,e tc. complete).								2) Reduce the rate by 8% if the		
	i) Grade I	1000 Cft.	11,288.10	11,878.50	cu.m	398.70	419.55		excavated section is not dressed or		
1	ii) Grade II	1000 Cft.	12,097.55	13,081.55	cu.m	427.30	462.05		levelled to designed section.		
	iii) Grade III	1000 Cft.	14,466.15	15,646.95	cu.m	510.95	552.65				
	iv) Grade IV	1000 Cft.	16,067.05	17,444.65	cu.m	567.50	616.15				

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	l .	Rate (British Sy	retem)	P	ate (Metric	System)	Spec.	Remarks			
No.	Description	Unit of	tate (Di itisii Oy	adiij	Unit of	ate (Weti ic	oys.cm,	No.	Nana Ka			
		M/ment	Labour	Composite	M/ment	Labour	Composite					
	v) Grade V	1000 Cft.	17,785.15	19,359.55	cu.m	628.15	683.80					
	vi) Grade VI	1000 Cft.	19,081.40	20,852.60	cu.m	673.95	736.50					
	b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50							17.1 to 17.5	1) Tools and plants required shall be			
	ft. (15 m) lead (including dressing and levelling to								the liability of the contractor.			
	designed section, etc. complete):-								2) Reduce the rate by 8% if the			
	i) Grade I	1000 Cft.	22,576.20	23,757.00	cu.m	797.40	839.10		excavated section is not dressed or			
	ii) Grade II	1000 Cft.	24,195.05	26,163.05	cu.m	854.55	924.10		levelled to designed section.			
	iii) Grade III	1000 Cft.	28,932.30	31,293.90	cu.m	1021.90	1105.30					
	iv) Grade IV v) Grade V	1000 Cft. 1000 Cft.	32,134.10 35,570.30	34,889.30 38,719.10	cu.m cu.m	1135.00 1256.35	1232.30 1367.55					
	vi) Grade VI	1000 Cft.	38,162.80	41,705.20	cu.m	1347.90	1473.05					
			/	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1							
13	Rehandling of earthwork:		The control of the co		를 냈다.							
	a) Lead upto a single throw of Kassi, phaorah or shovel	1000 Cft.	1,523.30		cu.m	53.80		ditto				
	b) Upto a lead of 50 ft. (15 m).	1000 Cft.	2,132.60	The same of the sa	cu.m	75.30		ditto				
		188	1 7 7 6	L , \$0 /	1/5							
14	Rehandling of gravel work or excavated rock,	1000 Cft.	6,093.10		cu.m	215.20		17.1 to 17.5				
	lead upto 50 ft.( 15 m)			)	Sp.							
15	Filling, watering and ramming earth under floors:-							ditto				
	i) with somely a contletion of a well-time at a	1000 04	3,083.00	Denart	man	400.00						
	<ul><li>i) with surplus earth from foundation, etc.</li><li>ii) with new earth excavated from outside,</li></ul>	1000 Cft. 1000 Cft.	6,203.10		cu.m cu.m	108.90 219.10						
	lead upto one chain (30 m).	1000 0111	0,200.10		Canti	210110						
16	Extra for every 50 ft. (15 m) additional lead or part thereof:-								This rate shall be applicable upto			
	i) for earhtwork soft, ordinary, hard and very hard.	1000 Cft.	59.05		cu.m	2.10			1000 ft. total distance, including the lead covered in the item of earthwork			
	ii) for gravel, shingle or rock.	1000 Cft.	69.85		cu.m	2.10			lead covered in the item of earthwork			
17	Transportation of earth all types when the total distance,								This rate will be paid inaddition to the			
	including the lead covered in the item of work, is more than 1000 ft. (300 m)								rate of earthwork, without deducting the lead covered in the item of			
	a) upto ¼ mile (400 m).	1000 Cft.	2,818.50		cu.m	99.55			earthwork			
	b) for every 330 ft. (100 m) additional lead or part thereof,											
	beyond ½ mile (400 m) upto one mile. (1.6 Km.)	1000 Cft.	21.15		cu.m	0.75						
		1000 Cft	184 75		cu m	6.55						
	d) for every ½ mile (800 m) additional lead					0.00						
	or part thereof, beyond 5 miles (8 Km).	1000 Cft.	166.70		cu.m	5.90						
18	Dressing and levelling of earhtwork to designed section, etc.							17.10 to 17.5				
'	complete:-							.7.10 10 17.0				
	a) Ashes, sand, silt or soft soil.	1000 Cft.	199.85		cu.m	7.05						
	1 '				cu.m							
	c) Graver work or sort rock not requiring blasting.	1000 Cft.	938.25		cu.m	33.15						
18	<ul> <li>c) for every ¼ mile (400 m) additional lead or part thereof, beyond one mile (1.6 Km.) upto 5 mile (8 Km).</li> <li>d) for every ½ mile (800 m) additional lead or part thereof, beyond 5 miles (8 Km).</li> <li>Dressing and levelling of earhtwork to designed section, etc. complete:- <ul> <li>a) A shes, sand, silt or soft soil.</li> <li>b) Ordinary or hard soil.</li> <li>c) Gravel work or soft rock not requiring</li> </ul> </li> </ul>	1000 Cft. 1000 Cft.	184.75 166.70	   	cu.m cu.m	6.55 5.90		17.10 to 17.5				

	MRS, 1st BI-ANNUA	AL-2019 (1	st JANUAR	Y-2019 to 30t	h JUNE-	2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks
No.	·	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
		WITHCH	Labour	Odriposite	WITHCHE	Labour	Composite		
19	Dowel dressing.	Per Chain	182.80		Metre	6.00		ditto	This rate is in addition to payment for dressed earhtwork.
20	a) Dressing slopes of banks or ground surface.	100Sft.	81.65		sq.m	8.80		ditto	To be paid only when exclusively dressing is done and no earthwork is carried out in embankment or cutting.
	b) Dressing of earthwork (done by machinery or otherwise and left undressed) to designed section.	100 <b>S</b> ft.	144.70		sq.m	15.55			i) The surface area dressed is to be taken for measurement.
				5					ii) The item is applicable where the dressing is done by the contractor other than the one who executed the work.
21	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead upto one chain (30 m) and lift upto 5 ft. (1.5 m)	1000 00	5,500.40		7	404 55		17.1 to 17.5	
	<ul><li>a) in sand, ashes or loose soil</li><li>b) in ordinary soil.</li><li>c) in hard soil or soft murum.</li></ul>	1000 Cft. 1000 Cft. 1000 Cft.	5,508.10 6,434.20 7,201.90		cu.m cu.m cu.m	194.55 227.25 254.35	  		
22	Cutting hard rock such as granite, ballast, hard lime stone or sand stone, etc. with chisels and hammers, for small	1000 Cft.	46,214.80	50,469.55	cu.m	1632.30	1782.60	17.1 to 17.5	Tools and plants required shall be the liability of the contractor.
	foundations.	27	mance	Depart	meni				
23 24	Extra for excavation requiring shoring.  Compaction of earthwork (soft, ordinary or hard soil):-	1000 Cft.	782.25	1,040.95	cu.m	27.65	36.75	17.1 to 17.5 ditto	Composite rate includes materials, i.e. plank, etc.
	a) Mixing, moistening earth to optimum moisture content in layers for compaction, etc. complete.	1000 Cft.	738.40		cu.m	26.10			
	b) Compaction by rolling with animal driven roller/hand rammed:								
	i) soft or sandy soil	1000 Cft.	913.95		cu.m	32.30			The rate does not include hire
	ii) ordinary soil	1000 Cft.	1,066.30		cu.m	37.65			charges of the roller.  2) Roller to be 'supplied by
	iii) hard soil	1000 Cft.	1,218.60		cu.m	43.05			Government
	iv) admixture of shingle	1000 Cft.	1,370.95		cu.m	48.40			
	c) Ramming earthwork (all types of soil).	1000 Cft.	913.95		cu.m	32.30			
	d) Ramming earhtwork behind retaining walls.	1000 Cft.	1,218.60		cu.m	43.05			
25	Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture							17.1 (a) * 411-5 and	The rate also includes hire charges of

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	ı	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.	·	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
	content in layers, etc. complete:	W/Mork	Lusoui	Odinpodite	W/IIGIL	Labour	Odinpodite	202-3	machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.		
	i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.		765.75	cu.m	-	27.05				
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		645.45	cu.m	-	22.80				
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.		525.15	cu.m	-	18.55				
26	Extra for wet earthwork.	1000 Cft.	2,132.60		cu.m	75.30	-	17.1 to 17.5	That will support a man's weight.		
27	Extra for slush or Daldal including dewatering.	1000 Cft.	4,874.50		cu.m	172.15	-	17.1 to 17.5	That will not support a man's weight.		
28	Extra for puddling.	1000 Cft.	3,844.65	f) = \	cu.m	135.80	-	ditto			
29	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	578.85	<u>-</u>	Metre	19.00	-	ditto			
30	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.(15 m).	1000 Cft.	5,483.80		cu.m	193.70		17.1 to 17.5			
31	Dag bailing 3" (75 mm) deep.	Per mile	2,341.80	<b>*</b> ***	Per Km	1455.45			Dag bailing for layout of borrow pit, to be done by contractors at their own cost.		
32	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	1,015.50	Depari	sq.m	109.25		ditto			
33	Berm cutting:-							17.1 to 17.5			
	a) lead upto a single throw of Kassi, phaora or shovel (without dressing).	1000 Cft.	2,741.90		cu.m	96.85					
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	4,898.80		cu.m	173.05					
34	Berm trimming both sides of channels:-							17.1 to 17.5			
	a) upto 3½ ft. (1.06 m) depth. b) exceeding 3½ ft. to 5 ft. (1.06 to 1.5 m) depth. c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth	Per Mile Per Mile Per Mile	7,149.10 9,989.30 15,594.90	  	Per Km. Per Km. Per Km.	4468.20 6243.30 9746.80	  				
35	Ploughing and levelling borrowpits.							ditto	A rea ploughed to be measured.		
	i) upto 3 ft. (0.9 m) depth. ii) above 3 ft. (0.9 m) depth.	Per Acre Per Acre	1,523.30 3,046.55		Per Hect. Per Hect.	3764.10 7528.20					
36	Making boundary or service roads, including dag-belling, leveling and dressing:							ditto			
	i) in unploughed land:										

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	771.75 1,035.75	 	Metre Metre	25.30 33.95	 				
	ii) in ploughed land:										
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	794.15 1,058.15		Metre Metre	26.05 34.70					
37	Earthwork by boats, including hire of boats:-							17.1 to 17.5	For ordinary soil.		
	<ul> <li>i) Digging and loading into boats, upto 50 ft. (15 m) lead.</li> <li>ii) Carriage by boats upto 10 chains (300 m).</li> <li>iii) Extra for every additional one chain (30 m) or part thereof beyond 10 chains (300 m).</li> </ul>	1000 Cft. 1000 Cft. 1000 Cft.	4,569.85 1,153.25 121.85		cu.m cu.m cu.m	161.40 40.75 4.30	  				
	iv) Unloading earth from boats.	1000 Cft.	2,132.60		cu.m	75.30					
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	1,827.95		cu.m	64.55		17.1 to 17.5			
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	4,265.20		cu.m	150.65		17.1 to 17.5			
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	3,427.40		cu.m	121.05		ditto			
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	607.60	630.60	cu.m	214.60	222.75		The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.		
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface water, in all types of soil except shingle, gravel and rock:-								The rate does not include back filling after laying of sewer, which is payable separately.		
	i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth iii) above 15.0 ft. (4.5 m) depth	1000 Cft. 1000 Cft. 1000 Cft.	4,969.95 8,427.85 10,865.10	5,353.10 8,996.35 11,433.60	cu.m cu.m cu.m	175.55 297.65 383.75	189.05 317.75 403.85		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.		
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:								The rate does not include back filling after laying of sewer, which is payable separately.		
	<ul> <li>i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL.</li> <li>ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL.</li> <li>iii) Exceeding 8 ft. (2.4 m) depth below SSWL.</li> </ul>	1000 Cft. 1000 Cft. 1000 Cft.	6,846.60 8,559.35 12,839.05	9,483.95 11,935.60 16,476.05	cu.m cu.m cu.m	241.80 302.30 453.50	334.95 421.55 581.95				

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description		Rate (British Sy	stem)		ate (Metric	System)	Spec.	Remarks	
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.		
44	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, leveling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	4,582.00	-	cu.m	161.85		17.1 to 17.5 **8.1	The rate does not include back filling after laying of pipe line, which is payable separately.	
45	Cutting and removing trees within a distance of 100 ft. (30 m)									
	a) upto 2½ ft. (760 mm) girth. b) above 2½ ft. to 6 ft. (760 to 1800 mm) girth.	Each Each	891.35 1,739.45		Each Each	891.35 1739.45				
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	1,142.45	() <del>-</del> \	Each	1142.45				
47	Jungle clearance and removing within 100 ft. (30 m).	d			400					
	a) light b) thick	1000 Sft. 1000 Sft.	152.35 304.65		sq.m sq.m	1.65 3.30	 			
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	73.10		sq.m	7.85				
49	Ploughing 3 times.	Per Acre	618.85		Per Hect.	1529.15				
50	Leveling, dressing and making lawns.	100Sft.	304.65	Depart	sq.m	32.80				
51	Turfing lawns (excluding cost of turf).	100Sft.	264.00		sq.m	28.40				
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry, wet slush, daldal and under water) including its disposal and preparation of working pad for operation of machinery.  (Rates includes 100 ft lead)	1000 Cft.		2107.00	cu.m		74.40			

 <sup>\*</sup> Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 \*\* Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

## 4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	F	Rate (British Sy	rstem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	Stone Work										
1	Dismantling dry stone masonry.	100Cft.	517.90		cu.m	182.90		18.1			
2	Dismantling stone masonry in mud mortar.	100Cft.	761.65	-	cu.m	269.00		ditto			
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	1,827.95		cu.m	645.65		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.		
4	a) Dismantling dry stone or spawl pitching.	100Cft.	913.95		cu.m	322.80		ditto			
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	1,157.70	27	cu.m	408.90		ditto			
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	1,523.30		cu.m	538.05		ditto			
6	Dismantling stone pitching, cement or lime grouted.	100Cft.	2,437.25	Dame mark	cu.m	860.85		ditto			
7	Dismantling stone in crates:	777	nance	Depart	ment						
	a) wooden crates	100Cft.	1,218.60		cu.m	430.40					
	b) wire crates	ditto	1,523.30		ditto	538.05					
8	Dismantling stone ware drain including base concrete.	100Cft.	853.05		cu.m	301.30		ditto			
	<u>Brick Work</u>										
9	Dismantling mud/pise walling.	100Cft.	304.65		cu.m	107.6		18.1			
10	Dismantling sun dried brick masonry.	100Cft.	761.65		cu.m	269		ditto			
11	Dismantling dry brick masonry.	100Cft.	517.9		cu.m	182.9		ditto			
12	Dismantling brick work in mud mortar.	100Cft.	1066.3		cu.m	376.6		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th		
13	Dismantling brick work in lime or cement mortar.	100Cft.	2589.6		cu.m	914.65		ditto	and subsequent floors respectively against item No. 12, 13, 14 & 15.		
14	Dismantling cement block masonry.	100Cft.	2,284.90		cu.m	807.05		ditto			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
15	Dismantling Dhajji walling.	100Cft.	609.30		cu.m	215.20		ditto			
	<u>Concrete</u>										
16	Dismantling mud concrete.	100Cft.	1,218.60		cu.m	430.40		ditto			
17	Dismantling lime concrete.	100Cft.	1,675.60		cu.m	591.80			Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th		
18	Dismantling lime or cement concrete, under water.	100Cft.	6,397.80		cu.m	2259.70			and subsequent floors respectively against item No. 17, 19 & 20.		
19	a) Dismantling cement concrete plain 1:4:8.	100Cft.	3,351.20		cu.m	1183.65		ditto			
	b) Dismantling cement concrete plain 1:3:6.	ditto	5,483.80		ditto	1936.90					
	c) Dismantling cement concrete 1:2:4 plain.	ditto	6,702.45		ditto	2367.30					
	d) Dismantling cement concrete with brick aggregate.	ditto	1,827.95		ditto	645.65					
	e) Dismantling D.P.C. of cement concrete  1½" thick (40 mm) and clearing the site.	ditto	913.95		ditto	322.80					
20	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100Cft.	10,967.60		cu.m	3873.75		ditto			
	Roofing	Fi	nance	Depart	ment	-					
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or bellies.	100Sft.	365.60		sq.m	39.35		18.1			
22	a) Dismantling 1st class tile roofing.	100Sft.	913.95		sq.m	98.35			Add extra 13%, 32 and 51% on labour rate only for 2nd, 3rd, 4th		
	b) Dismantling 2nd class tile roofing.	100 <b>S</b> ft.	761.65		sq.m	81.95		ditto	and subsequent floors respectively against items No. 22, 25, 26 and 28.		
23	Dismantling from any height, asbestos sheets and ridge coping.	100 <b>S</b> ft.	477.60		sq.m	51.40		18.1			
24	a) Dismantling roof of wooden planks and battens, from any height.	100 <b>S</b> ft.	382.05		sq.m	41.1		ditto			
	b) Dismantling wooden ceiling above 20' (6.0 m) height in difficult position, including lifting with care and special scaffolding along live electric wires and with machines underneath.	100 <b>S</b> ft.	1,511.75		sq.m	162.65		ditto			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	1,218.60		sq.m	131.10		ditto			
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	1,523.30		sq.m	163.90		ditto			
27	a) Stripping and stacking slate or tiles from the truss roofing.	100 <b>S</b> ft.	761.65		sq.m	81.95					
	b) Stripping and stacking C.I. sheet roof.	ditto	692.30		ditto	74.50					
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	844.00		ditto	90.80					
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	1,218.60		sq.m	131.10		18.1			
	<u>Flooring</u>				78						
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	517.90		sq.m	55.75		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively		
30	Dismantling plank or wooden block flooring, etc.	100Sft.	761.65		sq.m	81.95		ditto	against items No. 29 and 30.		
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-	94	nance	Depart	meni				i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.		
	a) 6" to 12" (150 to 300 mm) diameter	Per Lft	19.10		Metre	62.65			,		
	b) 13" to 24" (325 to 600 mm) diameter	Per Lft	31.30		Metre	102.65			ii) Bends, elbows, sluice valves,		
	c) 25" to 36" (625 to 900 mm) diameter d) Above 36" (Above 900 mm) diameter	ditto ditto	36.55 52.15		ditto ditto	119.90 171.05			etc. should not be paid for extraif fixed in the length of pipe line that is being dismantled.		
	WOOD WORK										
32	a) Removing door with chowkat.	Per No.	243.95		Per No.	243.95		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th		
	b) Removing windows and sky lights with chowkat.	ditto	188.55		ditto	188.55			and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.		
33	Removing ventilators and wooden sunshade, etc.	Per No.	98.60		Per No.	98.60		ditto			
34	a) Dismantling wooden beams upto 12' (3.65m) length.	Per No.	190.40		Per No.	190.40		ditto			

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	/-2019 to 30t	h JUNE-2	2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length.	ditto	304.65		ditto	304.65			
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	341.15		sq.m	36.70		ditto	
	b) Dismantling wooden trusses.	100Kg	1,070.45		%Kg	1070.45			
36	Dismantling wooden palisade fencing.	Per Lft.	27.10		Metre	88.90		ditto	
	<u>Iron work</u>								
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	1,033.25		%Kg	1033.25		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.
38	Dismantling rolled steel beams or iron rails, etc.	100Kg	500.00		%Kg	500.00		ditto	
39	Dismantling iron latrine.	Per Unit/ 2 Seats	1,107.50		Per Unit/ 2 Seats	1107.50		ditto	
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per inch bore	22.60		Each per cm bore	9.05		ditto	
41	a) Dismantling B.G. water column.	Each	7,390.00		Each	7390.00		ditto	
	b) Dismantling M.G. or N.G. water column.	Each	4,888.95		Each	4888.95		ditto	
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	517.90		Metre	17.00		18.1	
	<u>Miscellaneous</u>								
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	243.75		sq.m	26.25		18.1	
44	Dismantling cloth ceiling and supporting timber.	100Sft.	457.00		sq.m	49.15		ditto	
45	Dismantling and removing road metalling.	100Cft.	1,218.60		cu.m	430.40		ditto	
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead (30 metre).	100Cft.	1,626.85		cu.m	574.60		ditto	
47	Removing mud plaster from walls.	100Sft.	126.95		sq.m	13.65		ditto	Add extra 13%, 32% and 51% on
48	Removing cement or lime plaster.	100Sft.	253.90		sq.m	27.30		ditto	labour rates only for 2nd, 3rd, 4th and subsequent floors against item No. 47, 48, 49, & 50 respectively

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
49	Scraping:-							18.1			
	a) White wash or colour wash.	100Sft.	152.35		sq.m	16.40					
	b) Ordinary distemper, oil bound distemper, or paint of wall.	ditto	457.00		ditto	49.15					
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	1,301.00		sq.m	140.00		18.1			
51	Scraping boulders.	100Cft.	2,132.60		cu.m	753.25		18.1			
52	Cleaning lime or cement mortar of old stones to be used in masonry.  Electric Wiring	100Cft.	1,066.30	5	cu.m	376.60		18.1			
53	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).	Per point	41.50	42.00	Per point	41.50	42.00				
54	Dismantling plug point and making good damaged surface (building portion).	Per point	35.60	36.00	Per point	35.60	36.00				
55	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-	Fi	nance	Depart	meni						
	i) on surface ii) recessed in wall	Per foot Per foot	7.60 16.55	7.70 16.70	P.Mtr P.Mtr	24.95 54.30	25.25 54.80				

	5. MORTAR													
	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK													
		Dry 100 C	Material Required St. Wet (Ready) N	d for	Dry Material Required for One Cum Wet (Ready) Mortar									
S. No.	Ratio of Mortar	Cement	Lime	Tortai	Cement	Lime	Sand							
0.110.	ratio of World	(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.							
		` ʁag´´	Crt.	Cit.	` ʁag. ´	Cum								
1	2	3	4	5	6	7	8							
1	Cement : Sand													
	1:2	33.48		82	11.83		0.82							
	1:3	23.11		85	8.16		0.85							
	1:4	18.37		90	6.49		0.90							
	1:5	14.70		90	5.19		0.90							
	1:6	13.61		100	4.81		1.00							
	1:7	11.68		100	4.12		1.00							
	1:8	10.21		100	3.61		1.00							
2	Cement: Lime: Sand													
	1:1:6	12.25	15.0	90	4.33	0.15	0.90							
	1:1:6	10.70	13.1	90	4.33 3.78	0.13	0.90							
	1:1:7	9.39	11.5	92	3.76 3.32	0.13	0.92							
	1:1:9	8.52	10.44	94	3.00	0.12	0.94							
	1:1:10	7.67	9.4	94	2.71	0.09	0.94							
	1:2:8	9.19	22.5	90	3.25	0.03	0.90							
	1:2:9	8.16	20.0	90	2.88	0.20	0.90							
	1:2:10	7.67	18.8	94	2.71	0.19	0.94							
	1 : 2 : 12	6.39	15.66	94	2.26	0.16	0.94							
	1:3:12	6.26	23.0	92	2.21	0.23	0.92							
	1:3:14	5.47	20.1	94	1.93	0.20	0.94							
	1:3:16	4.82	17.7	94	1.70	0.18	0.94							
	1:1/4:3	23.11	7.0	85	8.16	0.07	0.85							
		and the second second												
3	Lime: Sand	Timana	$ce \ \Omega em$	86	-									
	1:2		43			0.43	0.86							
	1:3		31	93		0.31	0.93							

		<u>5</u>	. MO9	<u>RTAR</u>	, J				
MRS, 1st BI-AN	NUAL-2019	(1st JAN	IUARY-20	019 to 30t	h JUNE-	2019) DIS	TRICT A	TTOCK	
		Dry Material Wet	Required fo (Ready) Mor					aterial Requi Wet (Ready)	
Ratio of Mortar	Clay	Lime (Putty)	Sand	Surkhi	Cinder	Clay	Lime (Putty)	Sand	Surkhi
	Ctt.	Ctt.	Ctt.	Ctt.	Ctt.	IVI	` IVI Ğ	IVI	IVI ~
2	3	4	5	6	7	3	4	5	6

73.5

81.5

91.0

40.5

57.0

	57.0	~ecc57
	1 1	And in concession in which the Party of the
Wet material	to the same of the	1000
macanny (incli	iding woodog	o).

49.00

40.75

30.30

40.50

40.5

凘

135

S.

No.

4

5

6

7

Mud

Lime: Surkhi

Lime: Sand: Surkhi

Lime: Cinder

2:3

1:2

1:3

1:1:1

1:1

Wet material required for 1M<sup>3</sup> (35.32 Cft)

0.49

0.41

0.30

0.41

0.57

0.41

1.35

0.74

0.82

0.91

0.41

Cinder

IVI~

0.57

		Wet material required for 100 Cft. masonry (including wastage):	Wet material required for 1M³ (35.32 masonry (including wastage):
1	Brick Masonry:  a) Mud Mortar  b) Cement, Sand  c) Cement, Lime (Putty) Sand  d) Lime (Putty) Sand	35.00 Cft 25.00 Cft 25.00 Cft 25.00 Cft	0.35 M <sup>3</sup> 0.25 M <sup>3</sup> 0.25 M <sup>3</sup> 0.25 M <sup>3</sup>
2	Stone M asonry:  a) Random rubble, uncoursed i) Foundation and Plinth ii) Superstructure iii) Coursed	45.00 Cft 40.00 Cft 35.00 Cft	0.45 M <sup>3</sup> 0.40 M <sup>3</sup> 0.35 M <sup>3</sup>
	<ul><li>b) Ashlar Block in course or Sc</li><li>c) Ashlar fine masonry</li></ul>	abled masonry 30.00 Cft 20.00 Cft	0.30 M <sup>3</sup> 0.20 M <sup>3</sup>
Notes:	<ul><li>(1) Cement</li><li>(2) Unslaked lime</li><li>(3) Slaked lime</li><li>(4) Quick lime</li></ul>	1 Cft. = 40.8233 Kg 1.7 Cft. = 37.3242 Kg 2.5 Cft. = 37.3242 Kg 40 Kg Will yield 2.6 Cft. lime putty.	

#### 6. CONCRETE

- 1. Rates for all finished works include the removal of surplus debris, unused material and by products.
- 2. If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.
- 3. Subsequent carriage of crushed stone aggregate and bajri will be paid according to the following:
  - a) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and / or rail, as the case may be.
  - b) It shall be payable from the nearest approved quarry to site of work.

MRS, 1st BI-ANNUAL-2019 (	(1st JANUARY-2019 to 30th JUNE-2019)	DISTRICT ATTOCK
---------------------------	--------------------------------------	-----------------

Sr.	Description	R	ate (British Sys	tem)	R	Rate (Metric System)		Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud concrete in foundation including watering and ramming,	100Cft	3356.95	5135.95	cu.m	1185.70	1814.00		The stone ballast, crushed bajri,
	using brick or stone ballast 11/2" (40 mm) gauge.		. market reserve	and the later of t					round shingle from nallah, or brick
			/ x						ballast may be used according to
2	Dry rammed brick or stone ballast, 11/2" to 2" (40 mm to 50	100Cft	2284.90	4000.90	cu.m	807.05	1413.10		their comparative cheaper rates in
	mm) gauge.				1				various areas of the Province.
3	Cement concrete brick or stone ballast 1½ " to 2" (40 mm to	3000			7			20.1	-do-
	50 mm) gauge, in foundation and plinth:-	~~			30-7				
	β-1, β-1β-1, 1β-1, 1								
	(a) Ratio 1: 3: 6	100Cft	4420.35	15198.75	cu.m	1561.25	5368.20		
	(b) Ratio 1: 4: 8	ditto	4420.35	13002.75	"	1561.25	4592.55		
	(c) Ratio 1:5:10	ditto	4420.35	11837.55	"	1561.25	4181.00		
	(d) Ratio 1: 6:12	ditto	4420.35	10963.95	"	1561.25	3872.45		
	(e) Ratio 1: 6: 18	ditto	4420.35	10015.95	"	1561.25	3537.65		
	(f) Ratio 1: 7:20	ditto	4420.35	9601.35	"	1561.25	3391.20		
	Extra on item No. 3 above, for sedimentation tank or filter								
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri,
	(a) in bed	100Cft	1359.60	-	cu.m	480.20	-		round shingle from nallah, or brick ballast may be used according to their comparative cheaper rates in
	(b) on slope	ditto	2010.10	-	11	709.95	-		various areas of the Province.
5	Cement concrete plain including placing,							20.1	
	compacting, finishing and curing								
	complete (including screening and								
	washing of stone aggregate):								

	MRS, 1st BI-ANNUAI	2019 (1s	st JANUARY	-2019 to 30t	h JUNE	-2019) DI	STRICT ATTO	CK	
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(a) Ratio 1: 1:2 (b) Ratio 1: 1½: 1½ (c) Ratio 1: 1½: 3 (d) Ratio 1: 2: 3 (e) Ratio 1: 3: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 6	100Cft ditto ditto ditto ditto 100Cft ditto	5909.65 5909.65 5909.65 5909.65 5909.65 5909.65	30868.45 30279.25 25112.05 23984.05 21380.05 22013.65 19848.85	cu.m " " " cu.m	2087.30 2087.30 2087.30 2087.30 2087.30 2087.30	10902.75 10694.65 8869.60 8471.15 7551.45 7775.20 7010.60		
	(h) Ratio 1: 3: 6 (i) Ratio 1: 4: 8	ditto ditto	5909.65 5909.65	19116.85 17026.45		2087.30 2087.30	6752.05 6013.75		
6	Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):-  (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-	3000	nance '	Depart	) wen			20.4	1) The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring.  2) Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid extra.  3) This item shall not be applicable to factory made units.
	(1) Type A (nominal mix 1:1:2) (2) Type B (nominal mix 1: 1½: 3) (3) (c) Type C (nominal mix 1: 2: 4) (a)(ii) Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 5(a) (i) above not requiring form work (i.e. horizental shuttering) complete in all respects:- (1) Type A (nominal mix 1: 1: 2) (2) Type B (nominal mix 1: 1½: 3) (3) Type C (nominal mix 1: 2: 4)	Per Cft ditto ditto  Per Cft ditto ditto	137.50 137.50 137.50 79.55 79.55	436.00 378.70 347.9 345.80 283.60 252.70	cu.m	4856.50 4856.50 4856.5 2809.70 2809.70 2809.70	15399.50 13375.70 12287.85 12213.65 10016.75 8925.35		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.

	MRS, 1st BI-ANNUAL	L-2019 (1s	st JANUARY	-2019 to 30	h JUNE-	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	tate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(b) Precast reinforced cement concrete and prestressed reinforced cement concrete in columns, beams, lintels, stair cases, shelves, etc.  (1) Type A (nominal mix 1: 1: 2)  (2) Type B (nominal mix 1:1½: 3)  (3) Type C (nominal mix 1: 2: 4)  (c) Erecting and fixing in position, precast cement concrete or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m)	Per Cft ditto ditto	103.45 103.45 103.45 46.75	389.60 331.85 301.50 59.05	cu.m "	3653.85 3653.85 3653.85	13760.65 11720.95 10649.00 2085.65		
	including all charges.	Per Cit	40.73	39.03	Cu.m	1031.20	2000.00		
	(d) Add extra labour for R.C. concrete in 2nd and subsequent storeys.	Per Cft	22.85		cu.m	807.05	-		
7	Providing and casting in situ bored reinforced concrete piles with type C concrete (nominal mix 1: 2: 4), using 10% extra cement in dry mix, and course sand, including all labour and material (except the cost of steel reinforcement and its labour for bending and laying in position, etc. which will be				7 133 133			*851-1 to 851-10	Composite rate shall be reduced by Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.
	paid separately, including, screening & washing of shingle and curing:-	Fi	nance (	Depari	men	Ė			
	i) 18 " (450 mm) dia pile ii) 20" (500 mm) dia pile iii) 22" (550 mm) dia pile iv) 24" (600 mm) dia pile	Per Rft Per Rft Per Rft Per Rft	793.20 932.00 1141.4 1421.40	1118.10 1332.85 1610.1 1998.85	Metre Metre	2601.70 3056.95 3743.8 4662.20	4371.75		
8	Fabrication of mild steel reinforcement bar cage for R.C.C. bored piles, including cutting, bending, laying in position, welding and fastening, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from the bars):-							*851-5	The rate includes wastage, overlaps, etc. but does not apply to the laps and spiral reinforcement which are specifically shown in the structural / working drawings of piles as per lapping requirements of design.
	(a) plain bars (b) deformed bars	Per Cwt. ditto	1574.75 1574.75		•	3099.90 3099.90			
9	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints							*851.5	The rate includes wastage, overlaps and chairs, etc.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	and fastenings, including cost of binding wire and labour										
	charges for binding of steel reinforcement (also includes										
	removal of rust from bars):-										
	(a) Plain bars	Per Cwt.	406.55	4731.05	•	800.30					
	(b) Deformed bars (Grade-40)	ditto	406.55	6678.05	ditto	800.30					
	('c) Deformed bars (Grade-60)	ditto	406.55	6942.05	ditto	800.30	13665.50				
10	Precast cement concrete solid or face blocks (1:2:4),	Per Cft	52.40	205.45	cu.m	1850.75	7256.50	20.2			
	including cost of templates.										
11	Precast cement concrete hollow blocks (1: 2: 4), including	Per Cft	116.05	216.50	cu.m	4098.90	7646.80	20.2			
	cost of templates and constructing walls thereof.				\						
	<b>3</b>	1018	And the second s		크椒.						
12	Providing and fixing ornamental cement jali 2" (50 mm) thick	Per Sft	32.55	58.45	sq.m	350.25	628.90	20.1 to			
	(1: 2: 4), without steel.	1223	(m)	AND THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.	1 3/1/2	000.00		20.4			
	( /,	.61.77	100	/ر <sup>96</sup> دست							
13	Extra labour for laying concrete plain or reinforced:	1			93						
	, , ,			2/2							
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	2437.25		cu.m	860.85	-				
	(b) for every additional 10'(3 m) height.	100Cft	1523.30	Depari	cu.m	538.05	-				
	·										
14	Extra labour for work of weirs, rail or road bridges, syphons, and	100Cft	609.30	-	cu.m	215.20	-				
	concreting in superstructure										
15	Making reinforced cement concrete spout, including fixing in	Each	406.55	573.10	Each	406.55	573.10	20.4			
	position (2½' x 6" x5") (760 mmx150 mm x 125 mm)										
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement	Per hole	975.75	-	Each	975.75	_	20.1			
	concrete or stone masonry walls and repairing.										
	, <del>,</del> <del>-</del>										
17	Extra labour for skipping concrete in wells.	100Cft	3622.95	_	cu.m	1279.65	-	20.1			
	11 0										
18	Nicking concrete surface:										
	(a) Cement concrete surface	100Sft	345.85	-	sq.m	37.20	-				
	(b) Lime concrete surface	ditto	114.15	-	"	12.30	-				

	MRS, 1st BI-ANNUAL	2019 (1s	t JANUARY	-2019 to 30t	h JUNE	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
19	Preparing, watering and ramming surface for laying concrete (for Headworks only):- (a) Horizontal floor (b) Glacis and crest (c) Inverted filters	100Sft ditto ditto	346.00 498.15 162.60		sq.m "	37.25 53.60 17.50			
20	Fabrication of high tensile steel prestressing cables for prestressed (post tensioned) concrete, including assembling by drawing the H.T. wire through metal spacer plate, inserting in helix core and taping or tying, sheathing in longitudinally welded metal corrugated sheath, positioning, anchorage with male and female set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule, maintaining stressing record and supply the same in the approved proforma to the Engineer-in-charge, making loop at blind end, including all materials required for it, grouting the cable ducts with cement, cutting projected ends and making good recesses, etc., complete in all respects.	100 Kg.	4963.30	39999.85	100 Kg.	4963.30	39999.85	to	The rate includes wastage in cutting and breakage in stressing, etc.
21	Fabrication of High Tensile steel reinforcement for prestressed (pretension) concrete work, including inserting wire in moulds, providing M.S. shear bars, spacers and lift hooks, male and female anchorage, tie down, struts, stressing cables, maintaining stress record and supply the same in approved proforma to the Engineer-in-charge, cutting wires and projecting ends and making good recesses, etc., complete in all respects.  Lifting, transporting and placing precast prestressed concrete	100kg	2955.50	37075.80	%kg	2955.50	37075.80		1) The rate includes wastage in cutting and breakage in stressing, etc.  2) Quantity of H. T. wire will form basis of payment.  3) This item shall not be applicable to factory made units.
	B eam, Girder and other members (excluding battens) etc. in Position on the bridge to correct alignment and level, etc. complete							to 811-11	
	<ul> <li>i) Beam upto 50 ft. (15 m) length</li> <li>ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length</li> <li>iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length</li> <li>iv) Beam above 100ft. (30m) upto 150ft.(45m) length</li> <li>v) Beam above 150ft. (45m) length</li> </ul>	100Cft 100Cft 100Cft 100Cft 100Cft		1826.05 2586.44 3500.35 4548.15 5629.05	cu.m cu.m cu.m		644.95 913.55 1236.30 1606.40 1988.20		

	MRS, 1st BI-ANNUAL	2019 (1s	st JANUARY	-2019 to 30	h JUNE-	STRICT ATTO	СК		
Sr.	Description	R	ate (British Sys	tem)	Ra	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Providing and laying foam concrete 3 inch (75 mm) thick, using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,	Per Sft.	32.00	71.55	sq.m.	344.30	769.90		
	Providing and fixing 6 in(150 mm). wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-								
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	15.80 16.15	92.70 91.40	Metre Metre	51.80 52.95	304.05 299.80		
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-	3002 46			7 (S) (S)				
	a) On interior surface (without mastic strip) b) On exterior surface (with mastic strip)	Per Rft. ditto	14.40 14.40	91.35 94.95	Metre "	47.25 47.25	299.65 311.45		
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on expansion joints complete in all respects.	Per Sft.	16.25	105.25	Sq.m	174.85	1132.50		
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG. stopper to expansion joint.	Per Rft.	5.35	74.90	Metre	17.55	245.65		
	Providing embeding 10" (250 mm) wide 1/4" (6 mm) thick rubber water stopper in expansion joints of R.C.C. roof slab complete in all respects.	Per Rft.	21.60	69.60	Metre	70.85	228.25		
29	Filling expansion joints with bitumen. sand & saw dust in ratio 1:2:2.	Per Rft per inch width	3.80	19.70	P.Metre/ Per 25 mm Width	12.45	64.60		
30	Filling expansion joints with bitumen.	Per Rft.	56.20	-	Metre	184.35	-		

	MRS, 1st BI-ANNUAL	CK							
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
31	Laying asphaltic mixture in expansion joints.	Per Rft.	53.30	-	Metre	174.80	-		Material to be paid on actuals.
	Providing and fixing theremopore (foamed polythene) sheet in horizontal and vertical expansion joints:								
	a) 1" (25 mm) thick thermopore sheet	Per Sft.	6.50	12.00	Sq.m	69.95	129.10		
	b) 1½" (40 mm) thick thermopore sheet	ditto	6.50	15.90	"	69.95	171.10		
	Providing and laying damp proof course of cement concrete  1:2: 4(using cement, sand and shingle), including bitumen coating:-	11	, and						
	(a) with one coat bitumen and one coat polythene sheet 500gauge	100 M	- Sign		78				
	i) 1½" thick (40 mm)	100Sft	1522.20	4731.70	sq.m	163.80	509.15		
	ii) 2" thick (50 mm)	100Sft	1522.20	5309.15	•	163.80	571.25		
	iii) 3" thick (75 mm)	100Sft	1579.80	6631.80	sq.m	170.00	713.60		
	(b) with 2 coats of bitumen:								
	i) 1½" thick (40 mm)	100Sft	1522.20	5120.45	sq.m	163.80	550.95		
	ii) 2" thick (50 mm)	100Sft	1522.20	5697.20	-	163.80			
	iii) 3" thick (75 mm)	100 <b>S</b> ft	1579.80	7019.90	sq.m	170.00	755.35		
	Providing and laying damp proof course with cement sand plaster and bitumen coating:-								
	(a) with one coat of bitumen and one coat of polythene sheet 500 gauge:-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	1435.70	3123.75	-	154.50	336.10		
	b) ¾" thick (20 mm)	100 <b>S</b> ft	1435.70	3424.00	sq.m	154.50	368.40		

	MRS, 1st BI-ANNUAL	2019 (1	st JANUARY	'-2019 to 30	h JUNE	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) Ratio 1:3								
	a) ½" thick (13 mm)	100Sft	1435.70		sq.m	154.50	346.65		
	b) 3/4" thick (20mm)	100Sft	1435.70	3539.65	sq.m	154.50	380.85		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	1435.70	3365.80	sq.m	154.50	362.15		
	b) 3/4 " thick (20 mm)	100Sft	1435.70	3816.05	sq.m	154.50	410.60		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4		/ ~		\				
	a) ½" thick (13 mm)	100Sft	1435.70	3361.00	sq.m	154.50	361.65		
	b) ¾" thick (20 mm)	100Sft	1435.70	3661.50	sq.m	154.50	394.00		
		183	·		7 83				
	ii) Ratio 1:3	\$35A	1	67					
	a) ½ " thick (13 mm)	100Sft	1435.70	3459.85	sq.m	154.50	372.30		
	b) 3/4 " thick (20 mm)	100Sft	1435.70	3778.00	sq.m	154.50	406.50		
	iii) Ratio 1:2	ari.	98 / 892 / 50 6	Dans		į.			
	a) ½ " thick (13 mm)	100Sft	1435.70	3703.20	sq.m	154.50	398.45		
	b) 3/4 " thick (20 mm)	100 <b>S</b> ft	1435.70	4179.85	sq.m	154.50	449.75		
35	Providing and laying vertical damp proof course with cement								
	sand plaster and bitumen coating:-								
	(a) with one coat of bitumen and one coat of polythene sheet								
	500 gauge:								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	1435.70	3024.15	sq.m	154.50	325.40		
	b) <sup>3</sup> / <sub>4</sub> " thick (20 mm)	100Sft	1435.70		•	154.50			
	ii) Ratio 1:3								
	a) ½ " thick (13 mm)	100 <b>S</b> ft	1435.70	3122.45	sq.m	154.50	336.00		
	b) 3/4 " thick (20 mm)	100Sft	1435.70			154.50			

	MRS, 1st BI-ANNUAL	2019 (1	t JANUARY	-2019 to 30	STRICT ATTO	OCK			
Sr.	Description	R	ate (British Sys	tem)	Ra	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				-					
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	1435.70	3365.80	·	154.50			
	b) 3/4" thick (20 mm)	100Sft	1435.70	3842.45	sq.m	154.50	413.45		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	1435.70	3360.90	sq.m	154.50	361.65		
	b) 3/4" thick (20 mm)	100Sft	1435.70	3661.50	sq.m	154.50	394.00		
			/ X	) \					
	ii) Ratio 1:3		/ ~	J.	\				
	a) ½ " thick (13 mm)	100Sft	1435.70	3459.05	sq.m	154.50	372.20		
	b) ¾" thick (20 mm)	100Sft	1435.70	3777.15	sq.m	154.50	406.40		
		139	-		7 88				
	iii) Ratio 1:2	1884	1	507					
	a) ½ " thick (13 mm)	100Sft	1435.70	3702.55	Gweler.	154.50			
	b) ¾ " thick (20 mm)	100Sft	1435.70	4179.00	sq.m	154.50	449.65		
	Grouting concrete between, the grooves of gates, including shuttering.	100Cft	6761.70	Depari	cu.m.	2388.25	-		
37	Chiesel dressing concrete surface on sides of grooves.	100 <b>S</b> ft	190.20	-	sq.m	20.45	-		
38	Laying and ramming dry ballast or kankar.	100Cft	2475.35	-	cu.m	874.30	-		
39	Hoisting and placing in position R.C.C. shelves.	per No.	74.60	-	per No.	74.60	-		
40	Breaking brick ballast, screening and stacking:-								
	(a) 2"(50 mm) ring	100Cft.	1904.10	-	cu.m	672.55	-		
	(b) 1½ "(40 mm) ring	ditto	2132.60	-	"	753.25	-		
	(c) 1" (25 mm) ring	ditto	2475.35	-	"	874.30	-		
	(d) Jhama ballast ¾" (20 mm) ring	ditto	2856.15	-	"	1008.80	-		
	Supplying and fixing broken glasses on court yard walls, including 1:3: 6 cement concrete coping.	Per Rft	58.85	105.60	metre	193.05	346.35		

	MRS, 1st BI-ANNUAL	2019 (1s	st JANUARY	-2019 to 30	th JUNE	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Crushing stone ballast by machine.	100Cft	1904.10		cu.m.	672.55	-		This does not include the charges for working of crushers, but includes manual labour for carriageof stone to crusher within three chains (90 m) and also stacking the product after crushing within three chains (90 m).
43	Breaking stone ballast screened and stacked:-								
	(a) 2" ring (50 mm) (b) 1½" ring (40 mm) (c) 1" ring (25 mm) d) ½" ring (13 mm) (e) 1/8" to ¼" ring (3 mm to 6 mm)  Screening and stacking stone ballast shingle or bajri, etc.  Washing ballast, bajri or shingle.	100Cft. ditto ditto ditto 100Cft.	2132.60 2475.35 2856.15 3808.20 6473.95 609.30		cu.m.	753.25 874.30 1008.80 1345.05 2286.60 215.20	- - - -		
46	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2½' (1.50 m x 0.76 m)	Each	330.20	Depari	Each	330.20	-		

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

### 7. BRICK WORK

- 1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.
- 2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4"x4" (200x100x100 mm) nominal.

	MRS, 1st BI-ANNUAL	-2019 (1s	t JANUARY	-2019 to 30th	JUNE-2	TRICT ATTO	CK		
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Pacca brick work in mud mortar in buildings:							21.1 to	Masonry of boundary wall to be considered as masonry other than
	<ul><li>i) in foundation and plinth</li><li>ii) in ground floor</li></ul>	100Cft. ditto	2955.85 3911.00	14773.15 15728.30	cu.m ditto	1044.00 1381.35	5217.90 5555.25	21.4	building.
2	Add extra labour on item No. 1 for brick work in:-		×	5					The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) first floor	100Cft.	782.25		cu.m	276.30	_		
	ii) second floor	ditto	1737.40	The state of the s	ditto	613.65	_		
	iii) third floor	ditto	2692.55		ditto	951.00	_		
	iv) fourth & subsequent floors	ditto	4298.20		ditto	1518.10	_		
	Toditir a subsequent risors	OLUG /	4250.20		4	1010.10			
3	Pacca brick work in mud mortar other than building:-	100			3			21.1 to 21.4	Same remarks as against item No. 1 above
	i) upto 20 ft. (6.1 m) height	100Cft.	4029.70	15847.00	cu.m	1423.30	5597.15		
	ii) extra labour for every 5 ft. (1.5 m)	ditto	782.25	Denart	ditto	276.30	-		
	additional height, or part thereof.	.35 107.1	8-866-8-62-82-		25 20 20 20 20 20 20 20				
4	Pacca brick work in foundation and plinth in:-							ditto	Same remarks as against item No. 1 above.
	i) Cement, sand mortar:-								
	Ratio 1:2	100Cft.	3887.55	21191.55	cu.m	1373.05	7484.85		
	Ratio 1:3	ditto	3887.55	19880.55	ditto	1373.05	7021.80		
	Ratio 1:4	ditto	3887.55	19093.95		1373.05	6744.00		
	Ratio 1:5	ditto	3887.55	18569.55		1373.05	6558.75		
	Ratio 1:6	ditto	3887.55	18175.60		1373.05	6419.60		
	Ratio 1:7 Ratio 1:8	ditto ditto	3887.55 3887.55	17917.35 17691.15		1373.05 1373.05	6328.40 6248.50		
	Ivalio 1.0	unto	3007.33	17091.13	uitto	1373.03	0240.30		
	ii) lime, cement sand mortar:-							21.1	The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	3887.55	18448.75	cu.m	1373.05	6516.10		
	Ratio 1:1:7	ditto	3887.55	18175.45	ditto	1373.05	6419.55		
	Ratio 1:1:8	ditto	3887.55	17953.85	ditto	1373.05	6341.30		
	Ratio 1:1:9	ditto	3887.55	17768.20		1373.05	6275.75		
	Ratio 1:1:10	ditto	3887.55	17629.15	ditto	1373.05	6226.60		
	iii) lime, sand mortar 1:2	100Cft.	3887.55	17114.5	cu.m	1373.05	6044.85	ditto	ditto

	MRS, 1st BI-ANNUAL	JUNE-2	2019) DIS	TRICT ATTO	CK				
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
=		Offic	Laboui	Composite	Offic	Laboui	Composite		
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to be reduced by 7% and 14%,
	i) cement, sand mortar:-								if 2nd or 3rd class bricks are used.
	Ratio 1:2	100Cft.	5147.40	22451.40		1818.05	7929.85		ii) Masonry of boundary wall
	Ratio 1:3	ditto	5147.40	21140.40	ditto	1818.05	7466.80		to be considered as masonry
	Ratio 1:4	ditto	5147.40	20353.80	ditto	1818.05	7188.95		other than building.
	Ratio 1:5	ditto	5147.40	19829.40	ditto	1818.05	7003.75		
	Ratio 1:6	ditto	5147.40	19435.40	ditto	1818.05	6864.60		
	Ratio 1:7	ditto	5147.40	19177.20	ditto	1818.05	6773.40		
	Ratio 1:8	ditto	5147.40	18949.60	ditto	1818.05	6693.00		
	ii) lime, cement, sand mortar:-		/ ×						The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	5147.40	19708.55	cu.m	1818.05	6961.05		
	Ratio 1:1:7	ditto	5147.40	19437.95	ditto	1818.05	6865.50		
	Ratio 1:1:8	ditto	5147.40	19213.65	ditto	1818.05	6786.25		
	Ratio 1:1:9	ditto	5147.40	19028.00	ditto	1818.05	6720.70		
	Ratio 1:1:10	ditto	5147.40	18889.35	ditto	1818.05	6671.70		
		1638	1 milion	& /	143				
	iii) lime, sand mortar 1:2	100Cft.	5147.40	18374.30	cu.m	1818.05	6489.80		The rate of lime mortar also includes grinding of mortar.
6	Add extra labour on item No. 5 for brickwork		~~~						
0	in:-	7870		73					
	111	Ti	nance $q$	Departi	nen1				
	i) first floor	100Cft.	782.25		cu.m	276.30	_		
	ii) second floor	ditto	1737.40		ditto	613.65	-		
	iii) third floor	ditto	2692.55		ditto	951.00	_		
	iv) fourth & subsequent floors	ditto	4298.20		ditto	1518.10	-		
	,	G 110			G 110	10.00.00			
7	Pacca brick work other than building upto 10ft. (3 m) height.							21.1 to 21.5	i) The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) cement, sand mortar:-								
	Datio 4:0	1000#	4400.05	04707.05	<b></b>	1500 50	7005.05		ii) Workshops, godowns,, bins,
	Ratio 1:2	100Cft.	4483.25	21787.25	cu.m	1583.50	7695.25		house type godowns, reservoirs,
	Ratio 1:3	ditto	4483.25	20476.25	ditto	1583.50	7232.20		filter beds, storage tanks, wells,
	Ratio 1:4	ditto	4483.25	19689.65	ditto	1583.50	6954.40		screening chambers, collecting
	Ratio 1:5	ditto	4483.25	19165.25	ditto	1583.50	6769.15		tanks, manholes etc. are to be
	Ratio 1:6 Ratio 1:7	ditto	4483.25	18771.30	ditto	1583.50	6630.00		treated as masonry other than
	Ratio 1:7	ditto ditto	4483.25 4483.25	18513.05 18286.80	ditto ditto	1583.50 1583.50	6538.80 6458.90		buildings.
	NORTO 1.0	artto	7-00.20	10200.00	artto	1000.00	0-30.30		
	ii) lime, cement, sand mortar:-								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	4483.25	19044.45	cu.m	1583.50	6726.50		
	Ratio 1:1:7	ditto	4483.25	18771.15	ditto	1583.50	6629.95		

	MRS, 1st BI-ANNUAL	2019 (1s	st JANUARY	-2019 to 30th	JUNE-2	2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British S)	rstem)	R	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Ratio 1:1:8	ditto	4483.25	18549.50	ditto	1583.50	6551.70		
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	4483.25 4483.25	18363.80 18224.80		1583.50 1583.50	6486.10 6437.00		
	IXCATO 1.1.10	artto	7705.25	10224.00	artto	1303.30	0437.00		
	iii) lime, sand mortar 1:2	100Cft.	4483.25	17710.15	cu.m	1583.50	6255.25		ditto
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	782.25		cu.m	276.30	-		
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	1342.20		cu.m	474.05	-	21.5	
10	Extra for pacca brick work in steining of wells or any other circular masonry.	100Cft.	864.60	1573.10	cu.m	305.40	555.60	21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
11	Extra labour for profile and flared walls.	100Cft.	297.40		cu.m	105.05	-		
12	Extra labour for pacca brick work in piers and abutment:-				783				
	i) from 10ft. to 20ft. (3 m to 6 m) height	100Cft.	387.65	6	cu.m	136.90			
	ii) above 20 ft. (6 m) height.	100Cft.	782.25		cu.m	276.30	_		
	, , , , , , , , , , , , , , , , , , , ,	40			53				
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.		3749.00	cu.m		1324.15		This item is to be executed only under the written permission of
		Fi	nance (	Departi	neni	1			Superintending Engineer.
14	Reinforced brick work in lintel of openings, laid in 1:3 cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	Per Cft.	127.95	296.05	cu.m	4518.85	10456.50		
15	Extra for dressing or chamfering bricks for:-								
	a) special architectural bricks	100 Nos.	2282.20	_	% Nos.	2282.20	_		
	b) all other purposes	ditto	1141.10	-	ditto	1141.10	-		
40	Derforated poops brief welling half heigh think in amount							04.4	The composite vets is to be
16	Perforated pacca brick walling half brick thick, in ground floors:-							21.1 to	The composite rate is to be reduced by 7% and 14%, if 2nd or
								21.4	3rd class bricks are used.
	i) mud mortar	100 Sft.	1952.45	4911.10	Sqm.	210.10	528.45		
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	2579.90	6910.20	sq.m.	277.60	743.55		
	Ratio 1:3	ditto	2579.90	6582.15	ditto	277.60	708.25		
	Ratio 1:4	ditto	2579.90	6385.80	ditto	277.60	687.10		

	MRS, 1st BI-ANNUAL	st JANUARY	-2019 to 30th	JUNE-	2019) DIS	TRICT ATTO	CK		
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				•					
	Ratio 1:5	ditto	2579.90	6254.70	ditto	277.60	673.00		
	Ratio 1:6	ditto	2579.90	6162.60	ditto	277.60	663.10		
	Ratio 1:7 Ratio 1:8	ditto ditto	2579.90 2579.90	6091.10 6038.50	ditto ditto	277.60 277.60	655.40 649.75		
	Treate 1.5	artto	2070.00	0000.00	artto	277.00	0-10.70		
	iii) lime, cement sand mortar								The rate of lime mortar also
	Defin 4.4.0	40004	0570.00	COO 4 FO		077.00	CCO 75		includes grinding of mortar.
	Ratio 1:1:6 Ratio 1:1:7	100Sft. 100Sft.	2579.90 2579.90	6224.50 6155.05	•	277.60 277.60	669.75 662.30		
	Ratio 1:1:8				sq.m				
		100Sft.	2579.90	6103.50		277.60	656.75		
	Ratio 1:1:9	100Sft.	2579.90	6053.70		277.60	651.40		
	Ratio 1:1:10	100Sft.	2579.90	6024.10	sq.m	277.60	648.20		
	iv) lime, sand mortar 1:2	100Sft.	2579.90	5888.30	sq.m	277.60	633.60		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	,	/	<i>*</i>	\				
		-1.1	Sangaga and Property of the Spinish Street, Sp	and the state of t					
	i) first floor	100Sft.	394.55	-	sq.m	42.45	-		
	ii) second floor	ditto	865.25	-	ditto	93.10	-		
	iii) third floor	ditto	1349.75		ditto	145.25	-		
	iv) fourth & subsequent floors	ditto	2066.40	L 56/	ditto	222.35	-		
18	Perforated pacca brick walling one brick thick, in ground	Y. 48						21.1	The composite rate is to be
	floor:							to 21.4	reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) mud mortar	100Sft.	2761.95	8670.60	sq.m	297.20	932.95	21. <del>4</del>	STO CLASS DITCKS are used.
	ii) cement, sand mortar:-	.2. 60	120025-000-7	ere free es					
	D. (	400.00	0074.50	40500 50		440.00	40.47.05		
	Ratio 1:2	100 Sft.	3874.50	12526.50	-	416.90	1347.85		
	Ratio 1:3	ditto	3874.50	11871.00	ditto	416.90	1277.30		
	Ratio 1:4	ditto	3874.50	11477.70	ditto	416.90	1235.00		
	Ratio 1:5	ditto	3874.50	11215.50		416.90	1206.80		
	Ratio 1:6	ditto	3874.50	11031.30		416.90	1186.95		
	Ratio 1:7	ditto	3874.50	10887.80		416.90	1171.55		
	Ratio 1:8	ditto	3874.50	10776.30	ditto	416.90	1159.55		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	3874.50	11155.05	sq.m	416.90	1200.30		includes grinding of mortar
	Ratio 1:1:7	ditto	3874.50	11015.05	ditto	416.90	1185.20		]
	Ratio 1:1:8	ditto	3874.50	10907.70	ditto	416.90	1173.65		
	Ratio 1:1:9	ditto	3874.50	10814.80	ditto	416.90	1163.65		
	Ratio 1:1:10	ditto	3874.50	10746.60	ditto	416.90	1156.35		
	iv) lime, sand mortar 1:2	100Sft.	3874.50	10486.70	sq.m	416.90	1128.35		ditto
40	Add sytus labour on Horo No. 40 feet software discuss by the								
19	Add extra labour on item No. 18 for perforated pacca brick work in:-								
	i) first floor	100Sft.	586.65		sq.m	207.20	_		
<u> </u>	-/- ···································	.000.	000.00		~q	_07.20			

	MRS, 1st BI-ANNUAL	TRICT ATTO	CK						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		<u> </u>		Composito	<u> </u>		Composito		
	ii) second floor iii) third floor	ditto ditto	1303.05 2019.40		ditto ditto	460.25 713.25	-		
	iv) fourth & subsequent floors	ditto	3223.65		ditto	1138.60	-		
	English and the Court of Court							04.4	
20	Fire brick masonry in fireclay mortar:-							21.1 to	
	i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	48.30	642.55	cu.m	1705.65	22695.05		
	ii) Extra for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	782.25		ditto	276.30	-		A&C No.I dated 2.9.1998
21	First class brick walling laid in 1:3 cement sand mortar,								
	reinforced with 1" (25 mm) wide 18 gauge hoop iron:-		76	1				21.19	
	i) 4½" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	100Sft.	2144.35	9318.15	sq.m	230.75	1002.65		
	ii) 4½" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	100Sft.	1910.70	8631.20	sq.m	205.60	928.70		
	iii) 3" (75 mm) thick walling with hoop iron, bonding 6"	ditto	1698.20	6923.80	ditto	182.75	745.00		
	(150 mm) apart. iv) 3" (75 mm) thick walling with hoop iron, bonding 12"	ditto	1358.55	6080.65	ditto	146.20	654.30		
	(300 mm) apart.	46177			7(1)		3555		
22	Ghilafi work (1½ brick thick wall)	100Cft.	3936.35	10427.90	cu.m	1390.30	3683.15	21.18	
23	Dry brick pitching	100Cft.	2387.90	14051.90	cu.m	843.40	4963.15	21.1	
24	Sun dried bricks in mud mortar	100Cft.	3328.50	4494.30	cu.m	1175.65	1587.40	21.16	
25	Pise wall (mud walling)	100Cft.	1922.45		cu.m	679.00	-	21.17	
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2	
	i) 3" (75 mm) thick drip course cornice	Rft.	24.35	59.95		79.85	196.65		correction vide A&C No.I
	ii) 4½" (113 mm) thick drip course cornice. iii) 4½" (113 mm) thick eave brick with back brick.	ditto ditto	27.60 19.10	113.75 129.40	ditto ditto	90.55 62.65	373.10 424.45		dated 2.9.98
	iii) 4/2 (113 iiiii) tiilck eave blick with back blick.	unto	19.10	129.40	unto	02.00	424.40		
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2	
	i) 1 brick	Rft.	27.60	44.35	Metre	90.55	145.45		
	ii) 2 bricks	ditto	40.60	91.70	ditto	133.15	300.80		
	iii) 3 bricks iv) 4 bricks	ditto ditto	54.20 68.20	139.20 190.40	ditto ditto	177.80 223.70	456.60 624.50		
20									
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	1066.30		1,000 Nos	1066.30	-		
29	Scraping bricks dismantled from pacca masonry	1,000	2010.75		1,000	2010.75	-		

	MRS, 1st BI-ANN	UAL-2019 (1s	t JANUARY	-2019 to 30th	JUNE-2	2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Nos			Nos				
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	253.90	1573.90	cu.m	89.70	555.90		
31	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart.	Rft.	101.65	161.00	Metre	333.40	528.10		
32	First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG hoop iron strips bonding placed at 2.0' (600 mm) apart horizontally, and at 1.0' (300 mm) interval vertically.		- X						This item is to be executed only under the written permission of the Superintending Engineer.
	i) 1:3 ii) 1:4	100Sft. ditto	1910.70 1910.70	9675.90 9361.25	sq.m ditto	205.60 205.60	1041.15 1007.25		
33	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	54.20		sq.m	583.20	-		
34	Replacing kallar eaten bricks	Each No.	41.50	48.80	Each	41.50	48.80		
35	Repairing corners of bridges and other hydraulic masonry works	Each No.	271.05	352.30	Each	271.05	352.30		
36	Extra labour for drains of bath rooms, etc.	Per Lft.	21.60	Deriort	Metre	70.85			
37	Maroo corners	Each Corner	138.35		Each Corner	138.35			Payable in addition to brick work

#### 8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Description	F	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
O	Unit	Labour	Composite	Unit	Labour	Composite	No.			
Random, rubble masonry (uncoursed), in foundation and	J.	The second section of the second section is a second section of the second section is a second section of the second second section is a second secon		-1ヵ			22.10,			
plinth:	- 185			ゴ ※			22.11			
a) dry masonry	100 Cft.	4014.10	4818.10	cu.m	1417.80	1701.75				
1.	100 Cft.	5025.25		cu.m	1774.90	2128.50				
'	100 Cft.	7662.60		cu.m	2706.45	3699.90				
c) in lime, sand mortar 1:2 d) in cement, sand mortar	100 CIT.	7002.00	10475.40	Cu.III	2700.43	3099.90				
i) ratio 1:3	100 Cft.	7662.60	14960.10	cu.m	2706.45	5283.90				
ii) ratio 1:4	100 Cft.	7662.60	13780.20	cu.m	2706.45	4867.15				
iii) ratio 1:6	100 Cft.	7662.60	12429.80	cu.m	2706.45	4390.20				
iv) ratio 1:8	100 Cft.	7662.60	11682.60	cu.m	2706.45	4126.30				
Coursed rubble masonry hammer dressed, in foundation and plinth:							22.8			
a) dry masonry	100 Cft.	4878.70	5682.70	cu.m	1723.15	2007.15				
b) in mud mortar	100 Cft.	6900.95	7902.05	cu.m	2437.40	2791.00				
c) in lime, sand mortar 1:2	100 Cft.	8509.05	11097.90	cu.m	3005.40	3919.80				
d) in cement, sand mortar:										
i) ratio 1:3	100 Cft.	8509.05	15373.05	cu.m	3005.40	5429.75				
ii) ratio 1:4	100 Cft.	8509.05	14324.25	cu.m	3005.40	5059.35				
iii) ratio 1:6	100 Cft.	8509.05	13123.55	cu.m	3005.40	4635.25				
iv) ratio 1:8	100 Cft.	8509.05	12463.30	cu.m	3005.40	4402.05				
Random rubble masonry (uncoursed) in							22.10			
ground floor or 20 ft.(6 m) height, building/other										
than building.										
a) dry masonry	100 Cft.	4446.40	5250.40	cu.m	1570.45	1854.45				
b) in mud mortar	100 Cft.	6036.35	7037.45	cu.m	2132.05	2485.65				

Sr. No.	Description				MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
No.	o.				R	Rate (Metric S	System)	Spec.	Remarks							
		Unit	Labour	Composite	Unit	Labour	Composite	No.								
C	c) in lime, sand mortar 1:2	100 Cft.	8292.90	11105.70	cu.m	2929.05	3922.55									
С	d) in cement, sand mortar:	400.00	2000 00	45500 40		0000.05	5500 55									
	i) ratio 1:3 ii) ratio 1:4	100 Cft. 100 Cft.	8292.90 8292.90	15590.40 14410.50	cu.m	2929.05 2929.05	5506.55 5089.80									
	iii) ratio 1:6	100 Crt. 100 Cft.	8292.90	13060.10	cu.m cu.m	2929.05	4612.85									
	iv) ratio 1:8	100 Cft.	8292.90	12312.90	cu.m	2929.05	4348.90									
	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8								
а	a) dry masonry	100 Cft.	5691.85	6495.85	cu.m	2010.35	2294.35									
	b) in mud mortar	100 Cft.	8527.20	9519.55	cu.m	3011.80	3362.30									
C		100 Cft.	9538.30	12127.15	cu.m	3368.95	4283.30									
	d) in cement, sand mortar: i) ratio 1:3	100 Cft.	9538.30	16402.30	cu.m	3368.95	5793.30									
	ii) ratio 1:4	100 Cft.	9538.30	15353.50	cu.m	3368.95	5422.85									
	iii) ratio 1:6	100 Cft.	9538.30	14152.80	cu.m	3368.95	4998.75									
	iv) ratio 1:8	100 Cft.	9538.30	13492.55	cu.m	3368.95	4765.55									
	Ashlar block in course or scabbled masonry (including dressing, etc.,) in ground floor or 20 ft. (6 m) height,	83	F	:	7 / 19	Ç		22.5 &								
b	building/other than building.	· · · · · ·			<b>6</b> 53			22.6								
	a) in lime, sand mortar 1:2	100 Cft.	24732.85	27241.70	cu.m	8735.65	9621.75									
	o) in cement, sand mortar: i) ratio 1:3	100 Cft.	24732.85	30231.75	cu.m	<b>∌</b> 8735.65	10677.85									
	ii) ratio 1:4	100 Cft.	24732.85	29445.15	cu.m	8735.65	10400.05									
	iii) ratio 1:6	100 Cft.	24732.85	28553.65	cu.m	8735.65	10085.15									
	Ashlar fine masonry (including dressing, etc.) in ground loor or 20 ft. 6 m) height, building/other than building.							22.3 (A) to								
а	a) in lime, sand mortar 1:2	100 Cft.	43908.50	46195.75	cu.m	15508.50	16316.35	(C) & 22.4								
b	o) in cement, sand mortar:															
	i) ratio 1:3	100 Cft.	43908.50	47690.75	cu.m	15508.50	16844.35									
	ii) ratio 1:4 iii) ratio 1:6	100 Cft. 100 Cft.	43908.50 43908.50	47297.00 46859.95	cu.m cu.m	15508.50 15508.50	16705.30 16550.95									
7 E	Extra labour on items 3, 4, 5 & 6 above for work in:-															
	) first floor	100 Cft.	1099.25	-	cu.m	388.25	-									
	i) second floor	100 Cft.	2414.25	-	cu.m	852.70	-									
	ii) third floor	100 Cft.	3759.70	-	cu.m	1327.95	-									
i	v) fourth floor	100 Cft.	5902.20	-	cu.m	2084.65	-									
	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m) additional height, other than building, or part thereof.	100 Cft.	955.15	-	cu.m	337.35	-									

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	2678.30	-	cu.m	946.00	-	22.12				
10	Extra labour for:-							22.7				
	a) coping and caps, etc. b) cornice & string course	100 Cft. 100 Rft.	12450.25 12450.25	- -	cu.m Rm.	4397.45 408.35	- -					
11	Dressing stones:-							22.2				
	a) hammer dressed b) rough tooled dressed c) chisel dressed d) fine dressed	100 Sft. 100 Sft. 100 Sft. 100 Sft.	4981.70 9354.05 11346.70 23105.30	Č.	sq.m sq.m sq.m	536.05 1006.50 1220.90 2486.15			<ul> <li>i) This rate of dressing shall be paid only when the supply of undressed stone is made.</li> <li>ii) In case of masonry, dressing is already included and this rate shall not be added thereto.</li> <li>iii) Only dressed surface of stone</li> </ul>			
12	Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft.	9883.65	15822.00	sq.m.	1063.50	1702.45	22.13	shall be measured.			
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	460.80	491.25	cu.m	16275.45	17350.95					
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	259.60	293.00	cu.m	9169.05	10348.75					

# 9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		Rate (British S	/stem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100 <b>S</b> ft.	6972.50	12691.95	sq.m	750.25	1365.65	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	5409.35	9529.05	sq.m	582.05	1025.35	23.2	ditto			
3	Covering mud roof with coal tar, and fine sand. Filling spaces in between:-	100 <b>S</b> ft.	294.15	1094.40	sq.m	31.65	117.75	23.1 to 23.2	ditto			
	a) Wooden battens over beams, filled with deodar wood pieces (spacers). b) RCC battens, filled with CC block 1:3:6. c) Spaces filled with bricks.	100Sft. roof area -ditto- -ditto-	542.10 1034.35 284.55	2539.60 1437.75 817.65	sq.m	58.35 111.30 30.60	273.25 154.70 88.00		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100 <b>S</b> ft.	1695.35	6507.20	sq.m	182.40	700.20	23.1	ditto			
6	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm) earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ½" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.  Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			

	MRS, 1st BI-ANNUAL	<sub>-</sub> -2019 (1	st JANUARY	7-2019 to 30th	า JUNE-	2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) cement concrete in haunches 1:6:12. b) cement concrete in haunches 1:3:6.	100Sft. ditto	7665.50 7665.50	19011.35 20370.10	•	824.80 824.80	2045.60 2191.80		
7	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ½" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster and gobri) soffit of arches cement plastered. The rate also includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.  Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
	a) cement concrete in haunches 1:6:12. b) cement concrete in haunches 1:3:6.	100Sft. ditto	6232.80 6232.80	18340.75 18735.70	sq.m ditto	670.65 670.65	1973.45 2015.95		
8	Extra for vaulted jack arch roofing.	100Sft.	1383.35		sq.m	148.85	-		ditto
9	Jack arch roofing of shingle and cement concrete 1:3:6, $4\frac{1}{2}$ " (113 mm) thick at crown, with $\frac{1}{2}$ " (13 mm) cement plaster including cost of supplying, erecting and dismantling centring.	100 <b>S</b> ft.	8943.65	17542.40	sq.m	962.35	1887.55	23.3 to 23.5	ditto
10	Earth filling over roof including watering, ramming with 1" (25 mm) mud plaster finished, with gobri leeping:	Fi	nance	Depart				23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 3" (75 mm) thick earth filling and 1" (25 mm) mud plaster	100Sft.	768.35	1020.75	sq.m	82.70	109.85		& sub-sequent floors, respectively.
	b) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster	100 <b>S</b> ft.	1007.95	1304.15	sq.m	108.45	140.35		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	100.85	113.85	sq.m	10.85	12.25	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or 1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)	100Sft.	609.30	2155.00	sq.m	65.55	231.90	23.1	
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively,
	a) 20 BWG b) 22 BWG c) 24 BWG	100Sft. 100Sft. 100Sft.	1084.15 1084.15 1084.15	16274.65 13932.15 11298.4	sq.m sq.m sq.m	116.65 116.65 116.65	1751.15 1499.1 1215.7		on items 13 to 18.
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300	Rft.	77.40	100.75	Metre	253.85	330.45	23.10	

	MRS, 1st BI-ANNUAL	2019 (1	st JANUARY	/-2019 to 30tl	h JUNE-	2019) DIS	TRICT ATTO	СК	
Sr.	Description		Rate (British S)	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	mm) outside width finished smooth with a floating coat of neat cement.								
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	291.90	486.05	Each	291.90	486.05	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4½" (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	291.90	870.30	Each	291.90	870.30	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.								
	a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe	Per Rft. Per Rft.	59.80 59.80	177.80 203.70		196.15 196.15	583.20 668.15		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	59.80	147.85	sq.m	643.45	1590.85	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	17.30	83.70	Sq.m	186.15	900.60		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-	7							Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 4" dia (100 mm) cast iron down pipe. b) 3" (75 mm) cast iron down pipe.	Per Rft. Per Rft.	54.20 54.20	217.15 193.15	Metre Metre	177.80 177.80	712.25 633.55		& sub-sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	224.20	532.70	Each	224.20	532.70		
22	Shoes, bends or offsets for cast iron rain water down pipe, including fixing and painting.	Each	81.30	323.60	Each	81.30	323.60		
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	249.10	384.40	Each	249.10	384.40	23.10	
24	Laying $1/2$ " (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100 <b>S</b> ft.	5743.30	21137.65	sq.m	618.00	2274.40	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	a) 22 BWG sheets roofing b) 24 BWG sheets roofing	100Sft. 100Sft.	3470.70 3470.70	17441.75 15704.90	•	373.45 373.45	1876.75 1689.85	23.60	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and	100 <b>S</b> ft.	2387.90	6294.50	sq.m	256.95	677.30	23.8	

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		Rate (British S)	vstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ridges, etc).											
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100 <b>S</b> ft.	288.45		sq.m	31.05	-	23.6				
28	Fixing asbestos cement sheet ridges and valleys 1/4" (6 mm) thick.	Per Rft.	28.20	77.65	Metre	92.50	254.70	23.8				
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-							23.6				
	a) 6" (150 mm) lap and 18" (450 mm)	Per Rft.	74.75	435.70	Per Metre	245.20	1429.10					
	overall, of 22 gauge G.I sheet ridging. b) 9" (225 mm) lap and 24" (600 mm)	Per Rft.	97.55	434.30	Per Metre	319.95	1424.50					
	overall, of 24 gauge G.I sheet ridging. c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging.	Per Rft.	97.55	509.15	Per Metre	319.95	1670.00					
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	48.80	179.10	Per Metre	160.05	587.45	23.11				
31	Making masonry ventilators in cement, sand mortar 1:4	Each	1084.15	1642.00	Each	1084.15	1642.00					
32	Fixing water spouts or parnalas.	Each	325.25	Depart	Each	325.25	-	23.10				
33	Making drip course $2"x\frac{1}{2}"$ (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	14.00	15.40	Metre	45.90	50.50					
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	40.90	354.80	sq.m	440.10	3817.65					
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:-											
	i) Thermopore sheet ½ " (13 mm) thick ii) Thermopore sheet ¾ " (20 mm) thick iii) Thermopore sheet 1" (25 mm) thick	100Sft. 100Sft. 100Sft.	2619.20 2619.20 2623.55	7566.25 7692.25 7822.60	sq.m	281.85 281.85 282.30	814.15 827.70 841.70					
36	Providing and fixing AC rain water down pipe 4" (100 mm)	Rft.	16.25	300.00	Metre	53.30	984.00					

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		Rate (British S)	rstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	dia, with shoe, T-bend, clamp, etc.											
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:-								Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.			
	i) for slabs upto 6" (150 mm) thick ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick.	Rft. Rft.	17.30 29.75	19.35 33.50	Metre Metre	56.75 97.60	63.45 109.90					
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-								Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times for reinforced cement concrete.			
	i) upto 1.0' (300 mm) height of girder or beam.	Each	72.05	78.90	Each	72.05	78.90		To Tamerood Samark Some			
	ii) for every 6" (150 mm) additional height or part thereof.	Each	34.60	37.85	Each	34.60	37.85					
39	Hoisting RS. Beams and wooden beams and placing in position.	Each	314.95		Each	314.95	-					
40	Hoisting and placing in position sahl ballies, over roof.	Each	46.45	- Je /	Each	46.45	-					
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.	1		<b>A</b> 43								
	a) 5' to 6' (1.50 to 1.83 m) long b) 6' to 7' (1.83 to 2.13 m) long c) 7' to 8' (2.13 to 2.44 m) long d) 8' to 9' (2.44 to 2.74 m) long e) above 9' (2.74 m) length	Each Each Each Each Each	45.00 63.00 78.75 105.00 126.00	Depart :	Each Each Each Each Each	45.00 63.00 78.75 105.00 126.00	- - - -					
42	Hoisting and placing in position R.C. trough:	Each	126.00		Foob	126.00			Applicable only to roof trough (inverted tees & trough) for height of			
	a) upto 10' (3 m) in length b) 10' to 11' (3 to 3.36 m) in length c) 11' to 12' (3.36 to 3.66 m) in length d) 12' to 13' (3.66 to 3.96 m) in length e) 13' to 14' (3.96 to 4.26 m) in length f) 14' to 15' (4.26 to 4.57 m) in length g) 15' to 16' (4.57 to 4.88 m) in length h) 16' to 17' (4.88 to 5.19 m) in length i) 17' to 18' (5.19 to 5.49 m) in length j) 18' to 19' (5.49 to 5.80 m) in length k) 19' to 20' (5.80 to 6.10 m) in length	ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto	126.00 157.50 209.95 242.25 262.45 286.30 314.95 349.95 449.95 484.55 524.90	- - - - - - -	Each ditto	126.00 157.50 209.95 242.25 262.45 286.30 314.95 349.95 449.95 484.55 524.90	- - - - - - - -		1st storey only.			
43	i) upto 10' (3.05 m) span ii) from 10' to 12' (3.05 to 3.66 m) span iii) from 12' to 13' (3.66 to 3.96 m) span	Each ditto ditto	97.80 217.30 260.75	- - -	Each ditto ditto	97.80 217.30 260.75	- - -					

	MRS, 1st BI-ANNUAL	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
44	iv) from 13' to 14' (3.96 to 4.26 m) span v) from 14' to 15' (4.26 to 4.57 m) span vi) from 15' to 16' (4.57 to 4.88 m) span vii) from 16' to 18' (4.88 to 5.49 m) span viii) from 18' to 20' (5.49 to 6.10 m) span Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	ditto ditto ditto ditto Each	325.95 355.55 391.10 488.90 782.25 433.65	- - - - 724.55	ditto ditto ditto ditto ditto	325.95 355.55 391.10 488.90 782.25 433.65	- - - - - 724.55						
45	Providing and Laying Insulation material of Extruded Polystyrene XPS in Rigid Insulation / Foam Board on roof or walls, Density 32-38Kg/M, compressive strength 250-400 kpa, R-value 5 per inch thickness and water obsorption (1% by volume, cell structure clored cell) i/c cutting and placing in position. complete in all respect.  a) 1" thick b) 1-1/2" thick c) 2" thick		396.00 396.00 396.00	5,688.00 8,334.00 10,854.00	P.Sqm P.Sqm P.Sqm	42.60 42.60 42.60	612.05 896.75 1,167.90						

Finance Department

chapter-9(Roofing) Page 65

# 10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description		Rate (British S	/stem)	Ra	ate (Metric Sy	rstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	3113.20	4382.60	sq.m	335.00	471.55						
2	Earth flooring, consisting of 6" (150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	1067.70	1286.70	sq.m	114.90	138.45	24.1					
3	Providing, laying, watering and ramming brick ballast 1½" to 2" (40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	2440.30	4330.30	cum.	861.90	1529.45						
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	1937.45	2299.70	sq.m	208.45	247.45	24.2					
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	986.85	4103.10	sq.m	106.20	441.50	24.12					
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by ½ "(13 mm) thick mud plaster.	100 Sft.	1785.10	6426.60	sq.m	192.10	691.50	24.12					
7	Grouting 4½" (113 mm) dry brick work with cement mortar ratio 1: 5	100 Sft.	967.30	1497.10	sq.m	104.10	161.10						
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	1749.55	5779.15	sq.m	188.25	621.85	24.4					
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar 1:6.	100 Sft.	2,227.10	8,097.25	sq.m	239.65	871.25	24.4					
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement	100 Sft.	2,186.90	4,442.90	sq.m	235.30	478.05	ditto					
11	mortar 1:6. Brick ties (9"x4½"x1½")(225 mm x 113 mm x 40 mm) laid flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.	100 Sft.	2,403.05	6,022.25	sq.m	258.55	648.00	24.4					
12	Cement tiles (8"x8"x¾")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement	100 Sft.	1,436.65	6,499.35	sq.m	154.60	699.35	24.7					

	MRS, 1st BI-ANN	UAL-2019	9 (1st JANU)	ARY-2019 to	30th JUNI	E-2019) DIS	STRICT ATTO	OCK	
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S)	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	mortar 1:2.								
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm) (b) 9"x9"x¾" (225 x 225 x 20 mm) (c) 6"x6"x¾" (150 x 150 x 20 mm)	100 Sft. ditto ditto	1,436.65 1,436.65 1,436.65	4,631.50 5,873.00 8,320.00	sq.m ditto ditto	154.60 154.60 154.60	498.35 631.95 895.25		
14	Coloured cement tiles $(8"x8"x3/")(200 \times 200 \times 20 \text{ mm})$ of approved dark shade laid flat in 1:2 cement mortar, over $3/4$ " (20 mm) bedding mortar of 1:2.	100 Sft.	1,436.65	6,528.85	sq.m	154.60	702.50	24.7	
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-			5)				24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick (b) 1½"(30 mm) thick (c) 1½"(40 mm) thick (d) 1¾"(45 mm) thick (e) 2"(50 mm) thick (f) 2½"(56 mm) thick (g) 2½"(62 mm) thick (h)2¾"(70 mm) thick (i) 3"(75 mm) thick	100 Sft. ditto	1,540.75 1,540.75 1,961.20 1,961.20 2,381.60 2,457.75 2,802.05 2,802.05 2,802.05	2,842.80 3,132.00 3,841.60 4,144.10 4,923.25 5,268.30 5,821.30 6,202.75 6,538.95	sq.m ditto ditto ditto ditto ditto ditto ditto	165.80 165.80 211.05 211.05 256.25 264.45 301.50 301.50	305.90 337.00 413.35 445.90 529.75 566.85 626.35 667.40 703.60		
16	Providing and laying conglomerate flooring (two coat work) with top layer of ½"(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone chips passing 3/16"(6 mm) sieve, over bottom layer of cement concrete 1:3:6, including surface finishing and dividing in panels:-		Financ	е Дера	rimen	- Control of the Cont		24.10	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1½"(40 mm) thick (b) 1¾"(45 mm) thick (c) 2"(50 mm) thick	100 Sft. ditto ditto	2,285.90 2,285.90 2,922.50	4,121.30 4,316.30 5,242.45	sq.m ditto ditto	245.95 245.95 314.45	443.45 464.45 564.10		
17	Add extrain cement concrete floor topping, if finished with pigment and polishing.	100 Sft.	542.10	1,073.70	sq.m	58.35	115.55		
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	457.00	-	sq.m	49.15	-		On items 19-25 & 29-34
19	Flag stone flooring in lime mortar 1:2, over 3/4" (20 mm) bedding mortar, in platforms and floors, etc.							24.5	
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	4,704.10 4,704.10	6,376.55 6,633.70	sq.m ditto	506.15 506.15	686.10 713.80		

	MRS, 1st BI-ANNU	JAL-2019	9 (1st JANU)	ARY-2019 to	30th JUNE	E-2019) DIS	STRICT ATT	OCK	
Sr.	Description		Rate (British S	/stem)	Ra	ate (Metric S <sub>)</sub>	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
20	Asphalt flooring, including preparation of proper base remelting, setting out, and finishing complete:-							24.10	
	(a) 1"(25 mm) thick topping (b) ½"(13 mm) thick topping (c) ¼"(6 mm) thick topping	100 Sft. ditto ditto	1,955.60 1,531.55 1,124.75	15,909.90 8,657.30 4,789.45	sq.m ditto ditto	210.40 164.80 121.00	1711.90 931.55 515.35		
21	1 <sup>3</sup> / <sub>8</sub> " (35 mm) thick mosaic flooring, consisting of 3/8" (10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1" (25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete:-								If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	6,965.40 6,965.40	9,722.65 10,106.25	sq.m ditto	749.50 749.50	1046.15 1087.45		
22	1½"(40 mm) thick mosaic flooring, consisting of ½ "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing:-	100				e 6			If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	6,965.40 6,965.40	9,928.95 10,706.05	sq.m ditto	749.50 749.50	1068.35 1151.95		
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over ¾"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	3,992.75	8,209.90	sq.m	429.60	883.40	24.8	
24	Laying floor of approved white glazed tile 1/4" (6 mm) thick in white cement 1:2 over 3/4" (20mm) thick cement mortar 1:2, complete.	100 Sft.	5,171.75	14,359.90	sq.m	556.50	1545.15	24.7	
25	Laying floor of approved coloured glazed tiles ¼ "(6 mm) thick, laid in white cement and pigment on a bed of ¾" (20 mm) thick cement mortar 1:2.	100 Sft.	5,171.75	15,916.20	sq.m	556.50	1712.60	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	1,459.40	1,593.10	sq.m	157.05	171.40		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	1,554.45	1,690.85	sq.m	167.25	181.95		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric Sy	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	207.45	253.00	sq.m	22.30	27.20	24.6					
29	Shi sham wood boarding or strip flooring 3/4" (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½ "x2" (40 x 50 mm), size placed at 12" (300 mm) centre to centre, including two coats of bitumen laid hot on the base.	100 Sft.	4,323.00	38,104.10	sq.m	465.15	4100.00	24.13					
30	Deodar wood boarding or strip flooring 3/4" (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½"x2"(40 x 50 mm) size, placed at 12"(300 mm) centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	4,878.70	46,632.70	sq.m	524.95	5017.70	ditto					
31	Teak wood boarding or strip flooring ½" (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens 1½" x2" (40 x 50 mm) size, placed at 12" (300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	4,151.40	51,191.35	sq.m	446.70	5508.20	ditto					
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	4,497.90	42,508.85	sq.m	483.95	4573.95	24.13					
33	Teak wood block 1" (25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	4,151.40	85,076.05	sq.m	446.70	9154.20	ditto					
34	Laying wooden paving of hard wood on edge in coal tar and asphalt:-  (a) Shisham wood  (b) Kikar wood	100 Sft. Per Inch thickness ditto	2,676.10 2,676.10	26,249.20 17,152.00	sq.m per cm thickness ditto	287.95 287.95	2824.40 1845.55	ditto					
35	Tile skirting laid in 1:2 cement mortar, over ¾" (20 mm) thick cement mortar, 1:2 including cement washing and filling joints complete:-												
	(a) cement tiles (b) mosaic tiles	100 Sft. ditto	2,348.10 3,831.30	7,862.00 11,292.05	sq.m ditto	252.65 412.25	845.95 1215.05						
36	Providing grey cement skirting or dado 3/8" (10 mm) thick including rounding of corner and straight ening of top edge and finishing to smooth surface afterplastering:												
	(a) 1:2 cement, sand mortar	100 Sft.	2,858.60	3,536.70	sq.m	307.60	380.55						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description		Rate (British S	ystem)	stem) Rate (Metric System)			Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	(b) 1:3 cement, sand mortar (c) Extra if skirting or dado is finished with pigment of any colour.	ditto ditto	2,858.60 190.40	3,335.75 458.05	ditto ditto	307.60 20.50	358.95 49.30			
37	White glazed tile (6"x6"x¼") (6 mm) thick dado jointed in white cement and laid over 1:2 cement sand mortar 3/4" (20mm) thick, including finishing.	100 Sft.	6,365.70	15,553.85	sq.m	684.95	1673.60	24.7		
38	Coloured glazed tile dado (6"x6"½") (6mm) thick in pigment over 1:2 cement, sand mortar 3/4"(20mm) thick, including finishing.	100 Sft.	6,365.70	17,092.75	sq.m	684.95	1839.20	ditto		
	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:			CX						
	(a) using grey cement: i) 3/8"(10 mm) thick ii) ½"(13 mm) thick  (b) using white cement:	100 Sft. ditto	8,367.50 8,367.50	9,802.15 10,712.05	sq.m ditto	900.35 900.35	1054.70 1152.60			
	'i) 3/8"(10 mm) thick ii) ½"(13 mm) thick	100 Sft. ditto	8,367.50 8,367.50	10,859.05 11,230.20	sq.m ditto	900.35 900.35	1168.45 1208.35			
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	20.05	82.95	sq.m	215.75	892.55	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.	
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	4.20	Metre	-	13.80		Labour for fixing already included in items No. 15, 16, 21 and 22 of this Chapter.	
42	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels									
	a) :Size 1½" x <sup>3</sup> / <sub>8</sub> " (40 x 10 mm) b) :Size 1½" x ¼" (40 x 6 mm)	Per Rft. ditto	- -	6.60 4.60	Metre ditto	-	21.65 15.10			
43	Providing and laying Tuff pavers, having 7000 PSI, crushing strength of approved manufacturer, over 2" to 3" sand cushion i/c grouting with sand in joints i/c finishing to require slope. complete in all respect.  (50% Grey / 50% Coloured)									
	a) 50-mm thick b) 60-mm thick c) 80-mm thick	P.Sft P.Sft P.Sft	13.95 13.95 13.95	82.75 97.45 123.25	Sq.m Sq.m Sq.m	150.00 150.00 150.00	890.15 1,048.80 1,326.20			

### 11. SURFACE RENDERING

- 1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.  MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description		Rate (British System)			Rate (Metric System)			Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7	
	a) ½" (13 mm) thick b) 1" (25 mm) thick	100 Sft. ditto	453.90 639.65	525.20 782.25	sq.m ditto	48.85 68.85	56.50 84.15		
2	Mud plaster on floor or roof (excluding Gobri leeping):-							ditto	Add extra 13%, 32% and 51% above the labour rates only or 6%, 15% &
	a) ½" (13 mm) thick	100 Sft.	409.60	480.90	sq.m	44.05	51.75		23% on the composite rates for 2nd, 3rd, 4th and subsequenct floors,
	b) 1" (25 mm) thick	ditto	409.60	552.20	ditto	44.05	59.40		respectively.
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.	88			78			25.1 to 25.6	
	a) 1/4" (6 mm) thick	100 Sft.	1286.45	1463.60	sq.m	138.40	157.50		
	b) ½" (13 mm) thick	ditto	1286.45	1640.55	ditto	138.40	176.50		
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-	H	nance	Depari		į.		ditto	
	a) ¼" (6 mm) thick b) ½" (13 mm) thick	100 Sft. ditto	1286.45 1286.45	1765.85 2053.10	sq.m ditto	138.40 138.40	190.00 220.90		
5	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand and shingle) upto 20' (6.00 m) height.	100 Sft.	3319.00	6254.10	sq.m	357.10	672.95	ditto	
6	Providing and laying machine sprayed plaster ½" (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto	
	i) ratio 1:1 ii) ratio 1:1½ iii) ratio 1:2	100 Sft. ditto ditto	1089.25 1089.25 1089.25	2864.05 2736.85 2663.65	sq.m ditto ditto	117.20 117.20 117.20	308.15 294.50 286.60		
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1 to	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) <sup>3</sup> ⁄ <sub>4</sub> " (20 mm) thick	100 Sft. ditto ditto	1286.45 1286.45 1611.70	1964.60 2166.05 2967.95	sq.m ditto ditto	138.40 138.40 173.40	211.40 233.05 319.35	25.6	

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK								
Sr.	Description	Rate (British System)		stem)	Rate (Metric System)			Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Offic	Labour	Composite	Onit	Labour	Composite		
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	1286.45 1286.45 1611.70	1763.65 1922.70 2566.10	ditto	138.40 138.40 173.40	189.75 206.90 276.10		
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	1286.45 1286.45 1611.70	1709.10 1824.55 2450.40	sq.m ditto ditto	138.40 138.40 173.40	183.90 196.30 263.65		
10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, upto 20' height.		( )	5	\			ditto	<ul> <li>i) This item shall be applicable to buildings meant for human habitation only, such as buildings like residences, offices,</li> </ul>
	a) 1:2 b) 1:3 c) 1:4	100 Sft. ditto ditto	1459.40 1459.40 1459.40	2272.55 2070.95 2016.45	sq.m ditto ditto	157.05 157.05 157.05	244.55 222.85 216.95		educational institutions and hospitals, etc. It shall not be admissible on godowns; bins; agriculture, poultry and animal sheds; cycle stands; garrages; etc.  ii) The thickness of the plaster will not be more than 3/8" (10 mm)
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-							25.1 to 25.6	thick.
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	1286.45 1286.45 1611.70	1662.05 1742.45 2362.90	sq.m ditto ditto	138.40 138.40 173.40	178.85 187.50 254.25		
12	Cement plaster 1:6 upto 20' (6.00 mm) height:-							ditto	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	1286.45 1286.45 1611.70	1594.85 1695.45 2228.50	ditto	138.40 138.40 173.40	171.60 182.45 239.80		
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	734.45	1003.25	sq.m	79.05	107.95	25.4 to 25.6	
14	Lime pointing flush upto 20' (6.00 m) height including raking joints, in lime, sand mortar 1:2.	100 Sft.	961.20	1081.75	sq.m	103.45	116.40	25.8	
15	Lime pointing struck joints on walls, upto 20' (6.00 m) height, including raking joints in lime sand mortar 1:2.	100 Sft.	1459.40	1579.90	sq.m	157.05	170.00	ditto	
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2 b) ratio 1:3	100 Sft. ditto	1286.45 1286.45	1794.05 1675.75	•	138.40 138.40	193.05 180.30		

	MRS, 1st BI-ANNUAI	2019 (1	st JANUAR	Y-2019 to 30t	h JUNE	-2019) DIS	STRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
17	Cement pointing 1:2 flush on floor.	100 Sft.	961.20	1468.80	sq.m	103.45	158.05	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-								
	a) ratio 1:2 b) ratio 1:3	100 Sft. ditto	1459.40 1459.40	1967.00 1848.65	•	157.05 157.05	211.65 198.90		
19	Pointing flush on stone work, upto 20' (6.00 m) height.							25.8	
	a) in lime mortar 1:2 (lime, sand) b) in cement mortar 1:3 c) on stone work raised:-	100 Sft. ditto	1154.75 1154.75	1315.50 1544.00	sq.m ditto	124.25 124.25	141.55 166.15		
	i) in lime mortar 1:2 ii) in cement mortar 1:3	100 Sft. ditto	2151.05 2151.05	2311.80 2540.35		231.45 231.45	248.75 273.35		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	691.70		sq.m	74.45	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	345.85		sq.m	37.20	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	130.10	151.95	sq.m	14.00	16.35	25.11	
23	Distempering:-							ditto	
	a) new surface:- i) one coat	100 Sft.	131.60	212.75	sq.m	14.15	22.90		
	ii) two coats	ditto	194.70	300.50	ditto	20.95	32.35		
	iii) three coats	ditto	257.80	388.20	ditto	27.75	41.75		
	b) old surface:- i) one coat	100 Sft.	120.90	177.45	sq.m	13.00	19.10		
	ii) two coats	ditto	194.70	251.30		20.95	27.05		
24	Colour washing:-							25.10	
	a) new surface:-								
	i) one coat ii) two coats	100 Sft. ditto	119.55 179.35	148.25 221.25	sq.m ditto	12.85 19.30	15.95 23.80		
		unto	179.33	221.23	unto	19.50	25.00		
	b) old surface:- i) one coat	100 Sft.	119.55	137.30	sq.m	12.85	14.75		
	ii) two coats	ditto	179.35	208.40		19.30	22.40		
25	White washing:-							25.9	
	a) new surface:-	400.00	440 ==	4 40 05		40.05			
	i) one coat ii) two coats	100 Sft. ditto	119.55 179.35	143.00 214.40		12.85 19.30	15.40 23.05		
	ii) two oodio	GILLO	170.00	ک ۱۳۰ <del>۹</del> ۵	artto	15.50	20.00		

	MRS, 1st BI-ANNUAI	2019 (1	st JANUAR	Y-2019 to 30t	h JUNE	-2019) DIS	STRICT ATTO	OCK	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) three coats	ditto	232.20	278.90	ditto	25.00	30.00		
	b) old surface:-								
	i) one coat ii) two coats	100 Sft. ditto	119.55 179.35	137.15 208.55	sq.m ditto	12.85 19.30	14.75 22.45		
	,	artto	179.55	200.55	unto	19.50	22.40		
26	Gobri leeping:-							25.7	
	a) on walls b) over roofs	100 Sft. ditto	141.75 121.00	145.45 124.70	sq.m ditto	15.25 13.00	15.65 13.40		
				124.70			10.40	0.7.0	
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	172.90		sq.m	18.60	-	25.8	Payable with fresh masonry, when the face of the work is not to be
28	Extra for lime, mud or cement plaster and pointing from	100 Sft.	235.35	). \	sq.m	25.30	-		plastered/pointed.
	20' (6.00 m) and above for each additional 10' (3.00 m) height or part thereof.	- 11			1				
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	650.50	1112.85	sq.m	70.00	119.75		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	650.50	673.40	sq.m	70.00	72.45		
31	Extra cost of labour and material for red oxide pigment in	100 Sft.	216.15	316.65	sq.m	23.25	34.05		
	cement pointing to match with the colour of bricks.								
32	Providing grooved cement sand plaster 1:3 over existing plastered and roughened surface upto 20' (6.00 m) height.	F	nance	Depari		t			
	i) 3/8" (10 mm) thick	100 Sft.	1459.40	1936.55		157.05	208.35		
	ii) ½" (13 mm) thick	ditto	1459.40	2095.65	ditto	157.05	225.50		
33	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	10.30	39.90	Metre	33.80	130.85		
34	Petty repairs to fire place.								
	i) Single	Each	227.65	283.75	Each	227.65	283.75		
	ii) Double	Each	455.35	567.50	Each	455.35	567.50		Area above 100 Sft (10.76 sq.m)
35	Petty repair to main rooms.	Each	475.10	624.70	Each	475.10	624.70		Area upto 100 Sft (10.76 sq.m)
36	Petty repair to small rooms.	Each	237.55	312.30	Each	237.55	312.30		3.1.5,1.1.2.3.1 (1.0.1.2.34.1.1)
37	Petty repair to verandah.	Each	475.10	594.70	Each	475.10	594.70		The height will be taken from the
38	Extra labour for white washing, colour washing, priming coat	100 Sft.	19.95	-	sq.m	2.15	-		floor, roof or ground uderneath as
	and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	Per coat			Per coat				the case may be on the side towards which the work is to be done.

# 12. WOOD WORK

- No extra rate is to be paid for sawing as the rates are inclusive of these.
   Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	F	Rate (British Sy	vstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	760.85 864.60			26873.20 30537.65	149778.00 114466.80		
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.	1.		5				26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	492.80 492.80	the control of the co	cu.m ditto	17405.70 17405.70	141769.20 103793.10		
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-					ğ.		26.1 to 26.3 & 26.7	
	i) 2" (50 mm) thick ii) 1 <sup>3</sup> / <sub>4</sub> " (45 mm) thick	Per Sft. ditto	131.35 131.35	1558.00 1455.35	ditto	1413.35 1413.35	16764.10 15659.55		
4	iii) 1½" (40 mm) thick  First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cm²) including brass fittings, sash bars, etc. complete:-  a) teak wood framing 1¾" (45 mm) thick with wire gauze	ditto	131.35	1355.10	ditto	1413.35	14580.90	26.8 to 26.10	i) This also includes the cost of wood required for extra thickness of chowkat.  ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and
	fixed in position:- i) without springs or spring hinges.	Per Sft.	24.00	632.10	sq.m	258.25	6801.40		Rs.50.60 per sq.m.
	ii) with springs or spring hinges.	ditto	24.00	635.80	ditto	258.25	6841.20		
	<ul> <li>b) teak wood framing 1½" (40 mm) thick, with wire gauze fixed in position:-</li> <li>i) without springs or spring hinges.</li> <li>ii) with springs or spring hinges.</li> </ul>	Per Sft. ditto	24.00 24.00		•	258.25 258.25	6275.25 6320.40		

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	1	Rate (British Sy	rstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
							•		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes per cm²) fixed to chowkat with ¾" (20 mm) teak wood strips and screws.	Per Sft.	43.25	198.85	sq.m	465.35	2139.65		
	d) G.I. wire gauze 22 SWG, 12x12 meshes per square inch (5x5 meshes per cm²) fixed with ½" (13 mm) strip on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc.	Per Sft.	40.55	610.40	sq.m	436.30	6567.90		
5	P/F expanded metal ½" to ¾" (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	54.05	315.60	sq.m	581.60	3395.85		
6	Providing and fixing expanded metal ½" (13 mm) to ¾" 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	54.05	461.90	sq.m	581.60	4970.05		
7	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-	3655 AF			78			26.1 to 26.3 & 26.7	
	a) 2" thick (50 mm) b) 1¾" thick (45 mm) c) 1½" thick (40 mm)	Per Sft. ditto ditto	128.10 128.10 128.10	1048.70	sq.m ditto ditto	1378.35 1378.35 1378.35	12044.75 11284.10 10755.70		
8	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	a) 2¼" (56 mm) thick, with 1¼" (30 mm) battens and 1" (25 mm) planks.	Per Sft.	144.10	773.05	sq.m	1550.50	8318.00		
	b) 13/4" (40 mm) thick with 1" (25 mm) battens and 3/4" (20 mm) planks.	ditto	133.00	669.45	ditto	1431.10	7203.30		
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	164.25	453.25	sq.m	1767.35	4876.95		
10	Deodar battened ledged and braced doors and windows 2½" (56 mm) thick (1½" (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	155.20	756.85	sq.m	1669.95	8143.70	26.1, 26.2 26.4 to 26.6	
11	a) Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the							& 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	ı	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				3 3334			3 3334 3333		
	<ul> <li>Engineer incharge:-</li> <li>i) G.I. sheet facing on one side.</li> <li>ii) G.I. sheet facing on both sides.</li> </ul>	Per Sft. ditto	67.55 74.30	580.65 611.75	•	726.85 799.45	6247.80 6582.45		Sq.m) for G.I. facing on one side and Rs.9.40 per Sft. (Rs.101.20 per Sq.m) for G.I. sheet facing on both sides.
	b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges and locking arrangements, as directed by the Engineer-in-charge:-								-ditto-
	<ul><li>i) G.I. sheet facing on one side.</li><li>ii) G.I. sheet facing on both sides.</li></ul>	Per Sft. ditto	67.55 74.30	259.05 290.20	sq.m ditto	726.85 799.45	2787.40 3122.55		
12	First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm²) including iron fittings etc. complete:-	Дe			1			26.8 to 26.10	This also includes the cost of wood required for extra thickness of chowkat.
	a) deodar wood framing 1¾" (45 mm) thick with wire gauze fixed in position:-	183 183 183			78				ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	<ul><li>i) without springs or spring hinges.</li><li>ii) with springs or spring hinges.</li></ul>	Per Sft. ditto	72.05 72.05	488.15 492.30	sq.m ditto	775.25 775.25	5252.50 5297.15		
	<ul> <li>b) deodar wood framing 1½" (40 mm) thick, with wire gauze fixed in position:-</li> <li>i) without springs or spring hinges</li> <li>ii) with springs or spring hinges</li> </ul>	Per Sft. ditto	72.05 72.05	455.25 457.80	sq.m ditto	775.25 775.25	4898.50 4925.95		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm²) fixed to chowkat, with ¾" ('20 mm) thick deodar wood strip and screws.	Per Sft.	54.05	170.40	sq.m	581.60	1833.50		
	d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm <sup>2</sup> ) fixed to chowkat, with ½" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm).	Per Sft.	81.05	425.75	sq.m	872.10	4581.05		
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	120.10	516.45	sq.m	1292.30	5557.00	26.1 26.2	
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-								
	a) M.S. angle iron 1½"x 1½"x ½" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	28.80	179.20	sq.m	309.90	1928.20		

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) M.S. tee iron 1½"x 1½"x ½" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	28.80	136.45	sq.m	309.90	1468.20		
15	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 11/4" x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:								
	a) single rebate b) double rebate	Per Sft. ditto	44.50 52.20	147.75 170.35		478.80 561.65	1589.80 1832.95		
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	4.10	32.20	sq.m door area	44.10	346.45	26.2	
17	Providing and fixing brass spring hinges to wire gauzed doors.	Each	86.45	238.85	Each	86.45	238.85		
18	Providing and fixing sliding bolt to doors:-	1		10 min	<b>3</b> 3				
	i) iron sliding bolt, 10" (250 mm) long ii) iron sliding bolt, 12" (300 mm) long iii) brass sliding bolt, 10" (250 mm) long iv) brass sliding bolt, 12" (300 mm) long	Each ditto ditto ditto	81.05 81.05 81.05 81.05	143.45 185.45 184.25 341.45	Each ditto ditto ditto	81.05 81.05 81.05 81.05	143.45 185.45 184.25 341.45		
19	Extra for brass fittings to doors and windows, except for hinges, which shall be of iron:-								
	i) deodar wood panelled or panelled and glazed or fully glazed.	Per Sft.	2.45	12.75	sq.m	26.35	137.20		
	ii) deodar wood wire gauzed shutters.	ditto	2.45	10.30	ditto	26.35	110.85		
20	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	259.40	470.60	Each	259.40	470.60		
21	Providing and fixing, approved quality mortice lock.	Each	360.25	551.05	Each	360.25	551.05		
22	Providing and fixing, expended metal $\frac{1}{2}$ " to $\frac{3}{4}$ " (13 mm to 20 mm) mesh 16 gauge.								
	a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc.	Per Sft.	54.05	252.20	sq.m	581.60	2713.65		
	b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm)	ditto	54.05	349.90	ditto	581.60	3764.90		

	MRS, 1st BI-ANNUAI	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	ı	Rate (British Sy	rstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
23	a) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. complete.	Per Sft.	172.90		sq.m	1860.60	17177.00		For hollow frame shutter with commercial ply on one side, the composite rate shall be reduced by Rs.54.00 per Sft;or Rs.580.00 per Sqm and for hollow frame shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per
	b) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm)depth with shelves, shutters, brass fittings, etc., without boxing and back, complete.	Per Sft.	129.70	588.10	sq.m	1395.45	6327.85		Sft. or Rs.245.00 per Sq. metre.
	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ¼" (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1½:3) shelves 1½" (40 mm) thick including 3 coats of painting.  Providing and fixing wooden box type wardrobe 22" (550 mm) deep including ¾" (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods,	Per Sft.	103.25	395.10	Sq.m	1111.00	4251.35		If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood
	etc. including three coats of enamel paint:- i) Partal wood boxing and deodar wood shelves and leaves, etc.	Per Sft.	199.50	8'	sq.m	2146.85	8364.35		bracing and deodar wood lipping is used, the composite rate will be reduced by Rs.13.00 per Sft. or Rs.140.00 per Sq. metre.
	ii) Deodar wood boxing, and deodar wood	ditto	193.00	989.10	ditto	2076.50	10642.50		
26	shelves and leaves, etc.  Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete.	Per Sft.	77.40	634.85	Sq.m	832.85	6831.15		
27	Providing and fixing chowkat for doors, windows and C. windows, including holdfast, etc.								
	a) Teak wood b) Deodar wood	Per Sft. ditto	38.45 24.00		•	413.45 258.40	5722.70 3934.50		

	MRS, 1st BI-ANNUA	L-2019 ( <i>1</i>	1st JANUAR	Y-2019 to 30t	h JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) Shisham wood	ditto	28.80	188.00	ditto	310.10	2023.05		
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	a) 1" (25 mm) thick b) <sup>3</sup> / <sub>4</sub> " (20 mm) thick c) <sup>1</sup> / <sub>2</sub> " (13 mm) thick	Sft. ditto ditto	43.25 43.25 43.25	328.55 257.15 186.05	sq.m ditto ditto	465.15 465.15 465.15	3535.10 2766.85 2001.80		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	i) 1" (25 mm) thick ii) 1½" (40 mm) thick iii) 2" (50 mm) thick	Sft. ditto ditto	43.25 43.25 43.25	328.55 471.05 613.55	sq.m ditto ditto	465.15 465.15 465.15	3535.10 5068.40 6601.70		
30	a) Making and fixing cleats for doors and windows, including hinges and screws.	Each	51.90	136.10	Each	51.90	136.10	26.1 and 26.2	
	<ul> <li>b) Making and fixing cleats with brass hooks for roof ventilators.</li> </ul>	Each	69.15	111.95	Each	69.15	111.95		
	c) Providing and fixing door stops of 1½" (40 mm) dia rubber block.	Each	7.20	60.30	Each	7.20	60.30		
	d) Providing and fixing G.I. hook with clamps for doors.	Each	2.30	(Dep 11.20	Each	2.30	11.20		
	Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.							ditto	
	a) Shisham wood b) Teak wood	Per Rft. ditto	195.55 145.75	353.70 745.90	Metre ditto	641.40 478.05	1160.15 2446.65		
32	Deodar wood dado or picture rail 3"x1½" (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete.	Per Rft.	72.85	256.65	Metre	239.00	841.90	26.1 26.2	
33	Sawing wood by hand:-								
	<ul><li>a) Soft wood (deodar, kail or chir).</li><li>b) Hard wood (shisham, kikar, teak or sahl).</li></ul>	100Sft. ditto	864.60 1152.80	-	sq.m ditto	93.05 124.05	-		
34	Sawing wood by machine:								
	a) Soft wood b) Hard wood	100Sft. ditto	510.11 766.60	- -	sq.m ditto	54.90 82.50	-		

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	h JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	1	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	60.50	401.90	sq.m	651.20	4324.40	26.1	
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	72.05	205.15	sq.m	775.25	2207.40	ditto	
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	259.40	7812.20	Each	259.40	7812.20	ditto	
38	Dismantling and refixing eave boards.	Per Rft.	18.55		Metre	60.80			
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1½" (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	285.80	2499.75	Metre	937.35	8199.15	26.1	
40	Providing and fixing partition, including frame work:-	.1,			1				
	a) Sheets on one side of framework:-	8			78				
	i) Hard board ii) Ply wood ¼" (6 mm) thick	100Sft. ditto	1350.95 1350.95	13316.45 14828.45	sq.m ditto	145.35 145.35	1432.85 1595.55		
	iii) Masonite	ditto	1350.95	15080.45	ditto	145.35	1622.65		
	b) Sheets on both sides of frame work:-				1000				
	i) Hard board	100Sft.	1621.15	15002.80	sq.m	174.45	1614.30		
	ii) Ply wood ¼" (6 mm) thick iii) Masonite	ditto ditto	1621.15 1621.15	25344.20 18530.80	ditto ditto	174.45 174.45	2727.05 1993.90		
41	Providing and fixing ceiling, including frame work:-								
	i) Hard board	100Sft.	2648.25	10237.10	sq.m	284.95	1101.50		
	ii) Chip board iii) Ply wood ¼" (6 mm) thick	ditto ditto	2648.25 2648.25	12877.10 12757.10	ditto ditto	284.95 284.95	1385.60 1372.65		
	iv) Masonite	ditto	2648.25	12157.10	ditto	284.95	1308.10		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-								In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	i) ¾" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	2966.35 2966.35	10495.35 10570.20	sq.m ditto	319.20 319.20	1129.30 1137.35		
	b) Partal wood frame panelling:								

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	h JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	;\ 3/   /00\ 4h; al-	40004	2000 25	7007.05		240.20	700 05		
	i) ¾" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	2966.35 2966.35	7307.85 7433.85	sq.m ditto	319.20 319.20	786.35 799.90		
43	a) Fixing door, including chowkats.	Each	406.55	-	Each	406.55	-		
44	<ul><li>b) Fixing windows, including chowkats.</li><li>a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty.</li></ul>	ditto Per Sft.	203.30 30.90		ditto sq.m	203.30 332.25	- 699.30	26.12	
	b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty.	Per Sft.	38.90	98.55	sq.m	418.65	1060.55		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	57.90	116.30	sq.m	623.00	1251.40	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	21.60	22.75	sq.m	232.60	244.55		
	b) Cutting to required size and fixing glass panes with wooden fillets and putty.	Per Sft.	32.40	52.15	sq.m	348.85	561.10		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-	18	To a	- 19/					
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	49.70	116.60	sq.m	534.95	1254.75		
	b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sft (2.25 sq.m).	Per Sft.	49.70	116.80	sq.m	534.95	1256.85		
48	Providing and fixing 1½" (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with:-								
	i) M.S. angle iron 1½"x1½"x¼", welded i) (40 mmx 40 mmx 6mm) with M.S. flat 2"x¼" (50 mm x 6 mm)	Per Sft.	184.75	765.85	sq.m	1988.10	8240.55		
	ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm)	Per Sft.	184.75	710.85	sq.m	1988.10	7648.55		
49	Providing and fixing 1½" (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1½" (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1½"x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complete in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	i) M.S. angle iron 1½"x1½"x½", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x½" (50 mm x 6 mm)	Per Sft.	128.10	626.80	sq.m	1378.25	6744.30		

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUAR	Y-2019 to 30	th JUNE	-2019) DIS	TRICT ATTO	CK	
Sr.	Description	ı	Rate (British Sy	vstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm)	Per Sft.	128.10	584.05	sq.m	1378.25	6284.50		
50	Providing and fixing 1½" (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	70.60	363.10	sq.m	759.45	3907.05		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	120.75	413.60	sq.m	1299.35	4450.50		
52	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	25.95	39.70	Metre	85.10	130.25		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	10.80		Metre	35.45	437.35		
54	Providing and fixing M.S. flat ½"x1/8" (13mm x 3mm) grill including ¾" x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	61.60	217.95	sq.m	662.95	2345.05		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to steel window, complete with flat iron patti ½"x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	22.00	70.05	sq.m	236.80	753.60		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 P.SQM
56	Providing and fixing wooden moulding stopper 2½"x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	a) Teak wood moulding b) Deodar wood moulding	Per Sft. ditto	27.00 27.00		•	290.70 290.70	1297.15 770.75		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))

Sr.	Description	F	Rate (British System)			Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	braces with 1:3:6 PCC fixing ply of approved quality including holdfasts complete in all respects.								
	a) Teak wood ply b) With commercial ply	Per Sft. ditto	66.50 66.50	349.25 343.10	sq.m ditto	715.60 715.60	3758.15 3691.90		
58	Providing and fixing ornamental wooden architrave 3" x $(1\frac{1}{2}$ " tapered to $\frac{1}{2}$ ") all along the door frame complete in all respect.								
	a) Teak wood architrave b) Deodar wood architrave	Per Sft. ditto	12.15 12.15	74.75 41.60	sq.m ditto	130.60 130.60	804.15 447.35		
59	Providing and fixing Vin board cabinet 3/4" thick with drawers 3"deep in 'Kitchen including termite proofing and polishing with synthetic enamel as specified, with handles hinges, screws etc., complete in all respects.								
	<ul> <li>i) 1-1/2' deep, without back</li> <li>ii) 1-1/2' deep, with back</li> <li>iii) 2' deep, without back</li> <li>iv) 2' deep, with back</li> </ul>	Per Sft Per Sft Per Sft Per Sft	140.55 140.55 140.55 140.55	570.70 622.30 621.00 672.60	sq.m sq.m sq.m sq.m	1512.40 1512.40 1512.40 1512.40	6140.90 6696.10 6682.20 7237.45		

Finance Department

# 13. PAINTING AND VARNISHING

- 1 The rates include charges for scaffolding and other arrangements.
- 2 The rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		Rate (British Sy			e (Metric S		Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	a) Cleaning painted wood work with oil and water.	100 Sft.	152.35	186.70	m.pe	16.40	20.10					
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	101.55	149.45	sq.m	10.95	16.10	27.7				
	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	304.65		sq.m	32.80	-	27.3				
	Scraping, brushing and removing old paint from metal surface.	100 Sft.	1218.60	J	sq.m	131.10	-	27.9				
	Painting old surfaces:-  a) Painting corrugated surfaces, patent roofing, etc. with oil paint.	\$200 A			7			27.1 27.3 & 27.9				
	i) first coat ii) each subsequent coat	100 Sft. ditto	357.75 271.05	535.50 361.80	sq.m ditto	38.50 29.15	57.60 38.95					
	b) Painting sashes, fanlights, glazed or gauzed doors and windows:-	Fi	nance	Depar	ment							
	i) first coat ii) each subsequent coat	100 Sft. ditto	216.85 184.30	311.30 261.40	sq.m ditto	23.35 19.85	33.50 28.15					
	c) Painting doors and windows, any type:											
	i) first coat ii) each subsequent coat	100 Sft. ditto	357.75 271.05	539.25 409.05	sq.m ditto	38.50 29.15	58.05 44.00					
	d) Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:-											
	i) first coat ii) each subsequent coat e) Painting fillets, framings, skirtings, pipes, gutters and similar linear work not exceeding 6" in girth:-	100 Sft. ditto	216.85 184.30			23.35 19.85						
	i) first coat ii) each subsequent coat	100 Lft. ditto	184.30 130.10			6.05 4.25	9.15 6.80					
	f) Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:-											

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British Sys	tem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
		Offic	Luboui	Остроите	Oint	Labour	Остросто					
	i) first coat ii) each subsequent coat	100 Nos. ditto	527.50 479.35	705.25 573.85		527.50 479.35	705.25 573.85					
	g) Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:-											
	i) first coat ii) each subsequent coat	100 Nos ditto	1205.75 711.65	1735.20 976.40		1205.75 711.65	1735.20 976.40					
5	Painting new surface:-							27.1				
	a) Preparing surface and painting corrugated surface, patent roofing, etc.		/ ×		\			27.2 & 27.9				
	i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	523.70 184.70	754.40 405.95	sq.m ditto	56.35 19.90	81.15 43.70					
	b) Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):-	18	F-65		7							
	i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	221.65 156.10	381.40 281.65		23.85 16.80	41.05 30.30					
	c) Preparing surface and painting of doors and windows any type (including edges):-	Fi	nance	Depar	ment							
	i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	523.70 184.75	750.65 406.00		56.35 19.90	80.75 43.70					
	d) Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:-											
	i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	345.65 156.10	483.30 281.65		37.20 16.80	52.00 30.30					
	e) Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-											
	i) priming coat. ii) each subsequent coat of paint.	100 Lft. ditto	276.45 104.10	380.65 207.25	Metre ditto	9.05 3.40	12.50 6.80					
	f) Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-											
	i) priming coat. ii) each subsequent coat of paint.	100 Nos. ditto	813.1 398.10	1364.35 836.85		813.1 398.10	1364.35 836.85					

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British Sy	stem)	Rat	e (Metric Sy	/stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
		Oint	Laboui	Composite	Offic	Labour	Composite					
	g) Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-											
	<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Nos. ditto	2274.70 686.20	3175.00 1472.90		2274.70 686.20	3175.00 1472.90					
	h) Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	34.60	50.25	sq.m	3.70	5.40					
6	Applying Khanki Mixture hot to barrage gates:-		×					27.10				
	i) first coat ii) second coat	100 Sft. ditto	271.05 219.15	513.90 374.00	sq.m ditto	29.15 23.60	55.30 40.25					
7	French polishing complete:-	8			78			27.6				
	a) on new work b) on old work	100 Sft. ditto	2658.50 1423.35	2726.70 1459.85	sq.m ditto	286.05 153.15	293.40 157.10					
8	Varnishing wood work, including cleaning and preparing surface.	1			50							
	a) first coat b) second coat c) third coat	100 Sft. ditto ditto	216.85 81.30 81.30	350.30 182.45 161.50	sq.m ditto ditto	23.35 8.75 8.75	37.70 19.65 17.40					
9	Bitumen coating to plastered or cement concrete surface:-											
	<ul> <li>i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m)</li> <li>ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m)</li> <li>iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m)</li> </ul>	100 Sft. ditto ditto	253.90 243.75 201.05	1174.35 712.95 670.30		27.30 26.25 21.65	126.35 76.70 72.15					
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	10.85	11.50	Per No.	10.85	11.50	27.1				
11	Writing letters or figures at any surface with reflective paint of approved quality and colour per letter per inch height.	Per Letter per inch height	10.85	11.20	Per Letter per 25 mm height	10.85	11.20	27.1				
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	12.45	13.35	ditto	12.45	13.35	ditto				
13	Coaltar painting:							27.8 to				
	a) first coat, laid hot b) second coat, laid hot	100 Sft. ditto	228.25 138.35	950.30 595.80	•	24.55 14.90	102.25 64.10	27.11				

	MRS, 1st BI-ANNUAL	-2019 (1	st JANUARY	′-2019 to 30	th JUNE-2	2019) DIS	TRICT ATT	ОСК	
Sr.	Description	F	Rate (British Sy	stem)	Rat	e (Metric S	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Solignum painting:-							27.8	
	a) one coat, applied hot b) two coats, applied hot	100 Sft. ditto	190.20 288.20	217.40 331.65		20.45 31.00			
15	Creosote painting:-							ditto	
	a) one coat, applied hot b) two coats, applied hot	100 Sft. ditto	228.25 345.85	346.15 543.50	•	24.55 37.20	37.25 58.50		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	844.00	859.60	sq.m	90.80	92.50	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	304.65	312.40	sq.m	32.80	33.60	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	54.20	61.10	Each	54.20	61.10	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	108.40	121.75	per Metre	355.60	399.40	ditto	
20	Painting sounding rods and other gauges, reading to 10th of a foot (metre)	Per Lft.	54.20	58.35	per Metre	177.80	191.45	27.1	
21	Painting leveling staves.	Per Lft.	166.05	172.75	per Metre	544.65	566.55		
22	a) Painting and lettering mile/Km stones, on both sides:							ditto	
	i) one coat ii) two coats	Each ditto	116.15 203.30	164.00 280.15		116.15 203.30			
	b) Painting and lettering Furlong/½ Km stones, on both sides:-							27.1	
	i) one coat ii) two coats	Each ditto	15.50 27.10	21.15 37.00	Each ditto	15.50 27.10			
	c) Painting and lettering Sign posts:-								
	i) one coat ii) two coats	Each ditto	130.10 214.65	161.15 267.55		130.10 214.65	161.15 267.55		
23	Removing paint or varnish from wall.	100 Sft.	609.30	-	sq.m	65.55	-	27.12	
24	Scraping from hydraulic gates:-							27.1	
	a) Khanki paint b) Aluminium paint	100 Sft. ditto	1218.60 1218.60	-	sq.m ditto	131.10 131.10			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British Sy	stem)	Rat	e (Metric Sy	/stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
							,					
25	Painting letters with shade.	per letter per inch height	17.35	17.35	per letter per 25 mm height	17.35	17.35	27.1				
26	Scraping rust from old rail or girders.	100 Sft.	913.95	955.95	sq.m	98.35	102.85	27.9 27.10				
27	Chiselling old paint from brick work.	100 Sft.	1218.60	1251.00	sq.m	131.10	134.60	27.12				
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	1015.50	1033.50	sq.m	109.25	111.20					
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	304.65	344.00	sq.m	32.80	37.00	27.9				
30	Cleaning and painting punkha poles, including fixing hooks.	Each	216.15	224.25	Each	216.15	224.25	27.3				
31	Preparing surface and painting with emulsion paint:-	8			78			27.12				
	a) first coat b) 2nd and each subsequent coat	100 Sft. ditto	264.80 203.40	452.05 350.70	sq.m ditto	28.50 21.90	48.65 37.75					
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.	7000						27.12				
	a) new surface:	100	nance	Depar	meni							
	i) 1st coat ii) 2nd and subsequent coat	100 Sft. ditto	264.80 203.40	353.30 280.75		28.50 21.90	38.00 30.20					
	b) old surface:											
	i) 1st coat ii) 2nd and subsequent coat	100 Sft. ditto	264.80 203.40	301.85 239.75		28.50 21.90	32.50 25.80					
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:											
	a) new surface:											
	i) 1st coat ii) 2nd coat	%sft %sft	955.15 520.80	1430.15 727.85	sq.m sq.m	102.75 56.05	153.90 78.30					
	b) old surface:	%sft	520.80	727.85	sq.m	56.05	78.30					
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	1.65	2.55	Metre	5.35	8.30					

	MRS, 1st BI-ANN	UAL-2019 (1s	st JANUARY	'-2019 to 30t	h JUNE-	2019) DIS	TRICT ATT	ОСК	1
Sr.	Description	R	Rate (British System)			te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads complete in all respect.	Per Rft.	2.10	10.35	Metre	6.85	33.90	AASHTO M248-91 (2000)	Rates shall be reduced by <b>Rs0.50</b> P.Rft or <b>Rs.1.65</b> P.Mtr. If glass beads are not used.
35	Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	61.75	95.35	Job	61.75	95.35		9.000 20000 00 0000
36	Repainting of iron poles with cross arms, with bitumen or other approved paint.	Per Job	144.10	264.70	Job	144.10	264.70		
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:		/ ×		\				
	i) upto 40 mm (1½") dia	Per Rft.	1.30	4.30	Metre	4.30	8.15		
	ii) above 40 mm (1½") to 50 mm (2") dia	ditto	2.65	4.65	ditto	8.65	15.20		
	iii) above 50 mm (2") to 100 mm (4") dia	ditto	4.40	7.40	ditto	14.40	24.20		
38	Repainting main switches and branch distribution boards	Per Job	28.55	76.80	Job	28.55	76.80		
	of all sizes and types, with approved paint (complete set).	657			/436 633				
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	97.50	NG Depart	sq.m	10.50	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.

## 14. LINING OF CANALS

- Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates also include curing for specified period wherever necessary.
- 3 Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

MRS, 1st BI-ANNU	JAL-2019 (1st JANUARY-2019 to 3	30th JUNE-2019) DISTRICT ATT	ГОСК
Description	Rate (British System)	Rate (Metric System)	Spec.

Sr.	Description		Rate (British S	/stem)	F	Rate (Metric	: System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3	
	a) in bed b) on slope	100Sft. ditto	678.25 926.10	-	sq.m ditto	73.00 99.65	-		
	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	1576.60	2150.20	sq.m	169.65	231.35	ditto	
3	Cement plaster ½" (13 mm) thick ratio 1:10.				\			ditto	
	a) in bed b) on slope	100Sft. ditto	1154.35 1424.30	1438.30 1708.20	sq.m ditto	124.20 153.25	154.75 183.80		
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	É	11 1	4:00	Z/\$	2		ditto	
	a) in bed b) on slope	100 <b>S</b> ft. ditto	1154.35 1424.30	1657.75 1927.70	sq.m ditto	124.20 153.25	178.40 207.40		
5	Cement plaster 11/2" (40 mm) thick ratio 1:6.	6	Financ	e Depa	rtme	nt.		ditto	
	a) in bed b) on slope	100 <b>S</b> ft. ditto	1424.30 1749.55	2627.05 2952.30	sq.m ditto	153.25 188.25	282.65 317.65		
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:-								The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bed b) on slope	100Cft. ditto	6563.70 7541.50	17278.60 18256.40	cu.m ditto	2318.30 2663.65	6102.80 6448.15		payable separately.
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-								The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are
	a) in bed	100Cft.	6563.70	18956.70	cu.m	2318.30	6695.50		payable separately.
	b) on slope	ditto	7541.50	19934.50	ditto	2663.65	7040.85		
8	Brick lining 9"x4½"x3" (225x113x75 mm) in 1:6 cement, sand mortar:-								The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bed b) on slope	100Cft. ditto	6563.70 7541.50			2318.30 2663.65	7374.35 7719.70		payable separately.

Sr.	Description		Rate (British Sy	rstem)	Rate (Metric System)			Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	Brick lining 9"x4½"x3" (225x113x75 mm), in 1:3 cement, sand mortar:-  a) in bed b) on slope	100Cft. ditto	6563.70 7541.50	22556.70 23534.50	cu.m ditto	2318.30 2663.65	7967.05 8312.40	ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are payable separately.
	Cement concrete lining, using washed screened and graded stone aggregate:-							20.1, 28.1 & 28.3	
	a) in bed:- i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8 b) on slope:-	100Cft. ditto ditto	5909.65 5909.65 5909.65	22013.65 19116.85 17026.45	ditto	2087.30 2087.30 2087.30	7775.20 6752.05 6013.75		
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	6808.25 6808.25 6808.25	22912.25 20015.45 17925.05		2404.65 2404.65 2404.65	8092.60 7069.45 6331.10		

Finance Department

## 15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products.

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description		ate (British Sy			ate (Metric S		Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Cutting Ransome and Larson piles.	Per cut	172.90	-	Per cut	172.90	-	29.1- 29.3			
2	Cutting universal piles.	Per cut	255.90	-	Per cut	255.90	-	ditto			
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	4158.25	C	sq.m	447.45	-	ditto	The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre).		
		18 too							2) The rates are for the tackle gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government.		
				954	353				3) T-piles and adjustable junction piles will be counted as two piles.		
4	Driving steel piles,more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	3985.35	е Фери	sq.m	428.80	-	ditto	ditto		
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	2947.80	-	sq.m	317.20	-	ditto	ditto		
6	Dolleying piles.	Each	260.20	-	Each	260.20	-	ditto	Upto 5' (1.5 m) dolleying.		
7	Drilling holes in piles by hand.	Each	23.80	-	Each	23.80	-	ditto			
8	Raising and lowering machine.	Per Ft.	3897.50	-	Metre	12783.85	-	ditto			
9	Turning Machine, 90°	Per Job	5813.30	-	Per Job	5813.30	-	29.1 to 29.3			
10	Turning Machine, 135°.	Per Job	7196.65	-	Per Job	7196.65	-	ditto			
11	Turning Machine, 180°.	Per Job	9798.60	-	Per Job	9798.60	-	29.1 to 29.3			
12	Travelling machine (light).	Per Chain	11577.20	-	30 M.	11577.20	-	ditto			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	Rate (British System)			Ra	ate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
13	Loading and unloading piles.	Ton	225.45	-	Tonne	221.90	-	ditto	To be done by hand carts or ramps, including cost of ropes.			
14	Dismantling piling machine.	Each	23720.85	-	Each	23720.85	-	ditto				
15	Erecting piling machine.	Each	27370.20	-	Each	27370.20	-	ditto				
16	Carriage of piling machine under different conditions.	per chain	4705.80	-	30 M	4705.80	-	ditto				



Finance Department

#### 16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
  - i) the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
  - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
  - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the point of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, 1st BI-ANNU	AL-2019 (1	st JANUARY	-2019 to 30t	h JUNE-2	2019) DIS	TRICT ATT	OCK	
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	1157.70		cu.m	408.85			
2	Weaving matresses.	100Cft.	2193.50		cu.m	774.65			
3	a) Supplying and filling jute bags 1.25 (o.o35 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	34.25	49.15	Per Baq	34.25	49.15		The rate does not include supply of sand or earth for filling bags, which will be paid extra.
	<ul> <li>Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water.</li> </ul>	ditto	53.30	68.20	Per Baq	53.30	68.2		-ditto-
4	a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	82.00	135.45	Per Bag	82.00	135.45		The rate does not include supply of sand or earth for filling bags, which will be paid extra.
	b) Supply and filling new jute bags 4 to 5 cft (0.11 to 0.14 cu.m) capacity, with sand or earth, sewing and	ditto	117.20	170.60	ditto	117.20	170.60		-ditto-

	MRS, 1st BI-ANNUA	AL-2019 (1:	st JANUARY	'-2019 to 30t	th JUNE-2	2019) DIS	TRICT ATT	оск	
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	laying in position, under water.								
5	Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled with sand or earth:-								
	a) 1st chain (30 m)	100 Nos	304.65		% Nos	304.65			
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	109.70		Per 30 m Per 100 Nos/	109.70			
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	42.65		ditto	42.65			
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-	3633							
	a) 1st chain (Ist 30 metre)	100 Nos	1218.60		% Nos	1218.60			
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	426.50	Depari	Per 30 m per %Nos	426.50			
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	164.50		ditto	164.50			
7	Rolling matresses to river edge and floating, after unroling:-								
	a) area of matress upto 2,000 Sft. ( 186 sq.m)	100 <b>S</b> ft.	685.50		sq.m	73.75			
	b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m)	100Sft.	1142.45		sq.m	122.95			
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	1332.85		ditto	143.40			
8	Sewing empty cement bags in sheets.	100 Nos	1066.30	1102.10	% Nos	1066.30	1102.1		
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	1485.20	1588.40	cu.m	524.55	561		Measured in the shape of compact round bundles and of size specified for the work, before filling at site.
10	Launching the above and placing in position.	100Cft.	731.15		cu.m	258.20			

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	Ra	ate (British Syst	em)	Ra	te (Metric Sy	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
11	Supply within 5 chains (150 m):-									
	a) Boulders 9" (225 mm) and above	100Cft.	2205.70		cu.m	778.95				
	b) Over size shingle 3" to 9" (75 to 225 mm)	ditto	1474.55		ditto	520.75				
	c) Mixed graded shingle	ditto	1748.75		ditto	617.55				
12	Supplying Munj or Patha Trungers 6" (150 mm) mesh to hold 3 Cft. (0.085 cu.m)	Each	95.20	140.10	Each	95.20	140.1			
13	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to make crate):-  a) 6" (150 mm) mesh		×		\					
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	1138.35 1219.70 1219.70	1471.00 2299.70 2913.10	sq.m ditto ditto	122.50 131.25 131.25	158.30 247.45 313.45			
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	1463.60 1626.25 1626.25	1963.65 3243.00 4161.00	sq.m ditto ditto	157.50 175.00 175.00	211.3 348.95 447.70			
14	Providing and laying shingle on top of bund, including handling of materials within three chains.	100Cft.	761.65	1223.65	cu.m	268.95	432.15			
15	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)									
	a) stone or boulder b) shingle or spawl c) brick bats	100Cft. ditto ditto	1332.85 1332.85 1028.20	2652.85 1794.85 1952.20	ditto	470.70 470.70 363.15	633.85		The rate includes supply of brick bats to site of work.	
16	Supply and dumping by boat, including loading into boat within three chains (90 m) lead, and hire charges of boat and boatman.								The rate includes supply of brick bats to site of work.	
	a) stone or boulder b) shingle or spawl c) brick bats	100Cft. ditto ditto	2387.90 2387.90 2083.20	3707.90 2849.90 3007.20	cu.m ditto ditto	843.40 843.40 735.80	1006.60			
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	1854.75	2778.75	cu.m	655.10	981.45		The rate includes supply of brick bats to site of work.	
18	Supplying and filling bricks in crates and hand packing (excluding cost of crates).	100Cft.	2235.55	15195.55	cu.m	789.60	5367.05		The rate includes supply of bricks to site of work.	
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-									

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	/stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	i) stone or boulder ii) shingle or spawl	100Cft. ditto	2540.20 2540.20	3860.20 3002.20	cu.m ditto	897.20 897.20	1363.45 1060.40					
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	268.10	-	cu.m	94.70	-					
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	1340.50	-	cu.m	473.45	-					
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	761.65	1271.65	sq.m	81.95	136.85	30.1				
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	1904.10	1955.10	sq.m	204.90	210.35	ditto				
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1½ (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	4557.60	5667.15	sq.m	490.40	609.80		The cost of placing earth between rolls shall be paid separately, as earthwork.			
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	1496.55	1599.75	sq.m	161.05	172.15		Measurement to be made of the area of elevation on one face only.			
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	2560.80	2683.20	sq.m	275.55	288.7					
27	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	1626.25	2517.25	cu.m	574.40	889.1					
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	4230.25	5022.25	cu.m	1494.15	1773.85					
29	Providing and laying stone pitching, for top layer only:-											
	a) one slope b) on level	100Cft. ditto	3581.80 3201.00	4373.80 3993.00		1265.10 1130.60	1544.85 1410.35					
30	Providing and laying stone or spawl filling:-											
	a) on level	100Cft.	977.80	1397.80	cu.m	345.35	493.70					
	b) on slope	ditto	1176.65	1596.65	ditto	415.60	563.95					

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	/stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.												
	<ul> <li>i) top layer on slope</li> <li>ii) top layer on level</li> <li>iii) stone pitching/filling on slope or on level (other than top layer).</li> </ul>	100Cft. ditto ditto	4674.85 4294.05 2516.25	7629.75 7248.90 5570.15	cu.m ditto ditto	1651.15 1516.65 888.75	2694.80 2560.30 1967.35						
32	Grouting stone pitching or apron, etc. in:-												
	a) cement, sand mortar 1:3 b) cement, sand mortar 1:8	100 <b>S</b> ft. ditto	1650.90 1391.95	5977.25 3554.80	sq.m ditto	177.65 149.75	643.15 382.50						
33	Sand grouting in stone apron, with high pressure hose.	100 <b>S</b> ft.	553.75	1213.75	sq.m	59.60	130.60						
34	Grouting stone filling or pitching, with bajri.	100Cft.	952.05	2212.05	cu.m	336.25	781.3						
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	3383.35		cu.m	1195.00	-						
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cft.	1218.60	<b>*</b>	cu.m	430.40	-						
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	977.80	2237.80	cu.m	345.35	790.40						
38	Grouting jharies between blocks with bajri.	100Cft.	977.80	1817.80	cu.m	345.35	642.05						
39	Breaking stone into spawls and stacking	100Cft.	913.95	-	cu.m	322.80	-						
	Canal and Roads												
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-												
	a) upto 2.0' (600 mm) F.S. depth	Each	31.10	-	Each	31.10	-						
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	35.00	-	ditto	35.00	-						
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	46.65	-	ditto	46.65	-						
	d) above 4.0' (1200 mm) F.S. depth	ditto	116.65	-	ditto	116.65	-						
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-												

		MRS, 1st BI-ANNU	′-2019 to 30	th JUNE-2	2019) DIS	TRICT ATT	OCK			
Sr.		Description	Ra	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.			Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a)	i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead.	100 Nos	1523.30	1555.85	% Nos	1523.30	1555.85		
		ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	650.50	-	100 Nos	650.50	-		
		iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	968.35	-	100 Nos	968.35	-		
		iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	76.15	107.35	Per 30 Metre of one row	76.15	107.35		
		v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1050.70	1225.55	ditto	1050.70	1225.55		
	b)	<ul> <li>i) Cutting and supplying unsharpened pegs 4.0'</li> <li>(1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).</li> </ul>	100 Nos	86.85	123.85	100 Nos	86.85	123.85		
		ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	650.50	Depari	100 Nos	650.50	-		
		iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	1136.50	-	100 Nos	1136.50	-		
		iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	76.15		Per 30 M of one row	76.15			
		v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	2768.70		ditto	2768.70			
	c)	i) Cutting and supplying unsharpened pegs 5.0' (1.5 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	108.60	154.95	100 Nos	108.60	154.95		
		ii) Sharpening one end of 5' (1.5 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	685.10	-	100 Nos	685.10	-		

	MRS, 1st BI-ANNUA	ОСК							
Sr.	Description	R	ate (British Syst	em)	Rate	e (Metric Sy	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	1301.00	-	100 Nos	1301.00	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	76.15	107.35	Per 30 M of one row	76.15	107.35		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per chain of one row	1296.90	1541.50	Per 30 M of one row	1296.90	1541.50		
	d) i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	3046.55	3102.15	100 Nos	3046.55	3102.15		
	ii) Sharpening one end of 6' (1.8 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	815.20		100 Nos	815.20	-		
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	1561.20	KSF Depan	100 Nos	1561.20	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	76.15		Per Chain of one row	76.15	107.35		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	3149.50	3446.55	ditto	3149.50	3446.55		
	e) i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	2284.90	2400.25	100 Nos	2284.90	2400.25		
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	1040.80	-	100 Nos	1040.80	-		
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3" to 6" (75 to 150 mm) dia driven 2' (600 mm) below the available bed or ground (average).	100 Nos	1721.75	-	100 Nos	1721.75	-		

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per chain of one row	76.15	93.45	Per 30 M of one row	76.15	93.45				
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per Chain of one row	3581.80	3931.25	Per 30 M of one row	3581.80	3931.25				
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-		×								
	a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2½" to 5" (63 m to 125 mm) dia.	100 Nos	7200.00	<i>.</i>	100 Nos	7200.00	-				
	ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	910.70		100 Nos	910.70	-				
	iii) Driving Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long 2½" to 5" (63 to 125 mm) dia, driven 2.5' (750 mm) below the available bed or ground (average).	100 Nos	1886.45		100 Nos	1886.45	-				
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	114.25	163.20	Per 30 M of one Row	114.25	163.20				
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	4394.95	4848.80	ditto	4394.95	4848.80				
	b) i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	10800.00	100 Nos	-	10800				
	ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	1040.80	-	100 Nos	1040.80	-				
	iii) Driving Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long 2½" to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average).	100 Nos	2047.00	-	100 Nos	2047.00	-				
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	380.80	1253.20	Per 30 M of one Row	380.80	1253.20				

	MRS, 1st BI-ANNUA	TRICT ATT	ОСК						
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	5372.75	5949.35	ditto	5372.75	5949.35		
	c) i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	11400.00	100 Nos	-	11400.00		
	ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	1170.90	-	100 Nos	1170.90	-		
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long 2½" to 5" dia, driven 3.5' (1.07 mm) below the available bed or ground (average).	100 Nos	2341.80		100 Nos	2341.80	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	380.80	1253.20	Per 30 M of one row	380.80	1253.20		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	6350.50	7014.55	ditto	6350.50	7014.55		
	d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	nance	12600.00	100 Nos	-	12600.00		
	ii) Sharpening one end of 14'-1" to 16.0' (4.30 to 4.90 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	1301.00	-	100 Nos	1301.00	-		
	iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	2602.00	-	100 Nos	2602.00	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one Row	380.80	1253.20	Per 30 M of one Row	380.80	1253.20		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	7315.95	8084.75	ditto	7315.95	8084.75		
	e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	13200.00	100 Nos	-	13200.00		
	ii) Sharpening one end of 16'-1" to 20' (4.9 to 6.10 m) long Bamboos, $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia.	100 Nos	1561.20	-	100 Nos	1561.20	-		

٠	MRS, 1st BI-ANN					•			Remarks
Sr. No.	Description	Unit	ate (British Syst Labour	em) Composite	Unit	e (Metric S) Labour	vstem)  Composite	Spec. No.	
	iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	3122.40	-	100 Nos	3122.40			
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	380.80	1253.20	Per 30 M of one row	380.80	1253.20		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	9170.70	10149.05	ditto	9170.70	10149.05		
13	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	380.80	450.55	cu.m	134.50	159.15		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.
44	Filling brush wood only, thoroughly packed.	100Cft.	304.65		cu.m	107.60	-		Measured in compacted and packed shape before filling.
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	731.15		Per 30 M	731.15	-		
46	a) Gachi pitching 1' (300 mm) thick. b) Gachi pitching done with silt clearance and berm dressing.	100Sft. 100Sft.	3960.55 3351.20	Depan	Sq.m Sq.m	426.15 360.60			

## 17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.			
	a) channels, discharge upto 50 cusecs.	Job	1269.40	-	Job	1269.40	-	17.5				
	b) channels, discharge from 51 to 100 cusecs.	Job	1675.60	-	Job	1675.60	-					
	c) channels, discharge from 101 to 200 cusecs.	Job	2538.80	*)- `	Job	2538.80	-					
	d) channels, discharge from 201 to 350 cusecs.	Job	3427.40	-	Job	3427.40	-					
	e) channels, discharge over 350 cusecs.	Job	5077.60		Job	5077.60	-					
2	Dismantling outlets:-	835	1	. 6	7 %			18.1	These rates are for total dismantlement and removal			
	a) old types, such as K.G.O's orifices, etc.	Each	1269.40		Each	1269.40	-		of material. The rates do not include earth work for which			
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	1904.10		ditto	1904.10	-		rates are given in item 1, above.			
	c) A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm)	ditto	2538.80	Дера	ditto	2538.80	-		Casov C.			
	d) A.P.M. or O.F., "H" above 3.0'. (900 mm)	ditto	3173.50	-	ditto	3173.50	-					
	e) Tail cluster bifurcation	ditto	1904.10	-	ditto	1904.10	-					
	f) Tail cluster trifurcation	ditto	2538.80	-	ditto	2538.80	-					
	g) Tail cluster quardification	ditto	3173.50	-	ditto	3173.50	-					
3	Making temporary A.P.M. bricks block and fixing at site.	Each	536.65	890.65	Each	536.65	890.65	21.1 & 21.2				
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	1128.05	-	Job	1128.05	-	18.1, 21.1 & 21.2				
5	Dismantling walls and fitting iron block of O.F. outlet.	Each	1128.05	-	Each	1128.05	-	18.1, 21.1 & 21.2				
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to 17.2				

chapter-17(Outlet)

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	F	Rate (British Sy	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth	Each ditto	3046.55 4112.85	-	Each ditto	3046.55 4112.85	- -						
	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	611.40	1098.60	Each	611.40	1098.60	18.1, 21.1 & 21.2					
	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	1193.95	1988.35	Each	1193.95	1988.35	ditto					
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-								Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no O.F. iron block.				
	a) for channel depth of 5.0'. (1.5 m) b) for channel depth of 4.0'. (1.2 m) c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) e) for channel depth of less than 2.0'. (600 mm)	Each ditto ditto ditto ditto	1301.00 975.75 780.60 650.50 520.40	1448.60 1123.35 928.20 764.50 600.80	Each ditto ditto ditto ditto	1301.00 975.75 780.60 650.50 520.40	1448.60 1123.35 928.20 764.50 600.80						
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	536.65	759.85	Each	536.65	759.85						
11	Laying iron pipes for outlets.	Per Lft.	26.00		Metre	85.35	-	21.1, 21.2 & 17.1 to 17.5					
12	Water allowance for constructing outlets or culverts, when canal water is not flowing.	Each	619.45 to 1269.40	Depa	Each	619.45 to 1269.40			At the discretion of the Engineer-in-charge depending upon the distance and source of supply.				
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	445.30	-	Each	445.30	-						
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2					
	a) portion under bank. b) portion under road, beyond bank.	Rft. ditto	115.95 49.60	125.80 59.45		380.45 162.75	412.75 195.05						
15	Removing pipe outlet, refilling earth and puddling.							17.1 to					
	a) portion under bank. b) portion under road, beyond bank.	Rft. ditto	101.55 38.10	-	Metre ditto	333.20 124.95	-	17.5					
16	Changing pipe outlets by removing one pipe and replacing it at the same site with another pipe complete with earth and puddling.												
	a) portion under bank. b) portion under road, beyond bank.	Rft. ditto	138.45 69.25	148.30 79.05		454.30 227.15							

chapter-17(Outlet) Page 106

### 18. ROAD & ROAD STRUCTURE

- 1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 3 The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.
- 4 Subsequent carriage of crushed stone aggregate and bajri will be paid according to the following:
  - a) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and / or rail, as the case may be.
  - b) It shall be payable from the nearest approved quarry to site of work.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr. No.	Description	R	ate (British Sys	tem)	Rat	te (Metric S	ystem)	Spec. No.	Remarks			
NO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.				
	Sub-base & base construction											
	Providing and laying sub-base course of brick on edge 4½" (113 mm) thick, including compaction to required camber and grade.	100Cft.	3647.25	16033.65	cu.m	1288.20	5663.10	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.			
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	2876.70	5535.90	cu.m	1016.05	1955.30	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.			
3	a) Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and. aggregate.	Tine	mce D	epartn.	ent			ditto				
	i) Pit run or bed run gravel. ii) Crushed stone aggregate.	100Cft. 100Cft.	2876.70 2876.70			1016.05 1016.05						
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.			
									2) It shall be payable from the nearest approved quarry.  3) The quantity of pit run or bed run gravel and crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft.			

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	a) Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and. aggregate.	100Cft.	3309.00	6903.30	cu.m	1168.75	2438.25	501-1 to 501-6	
	b) Subsequent carriage of crushed stone aggregate.	100Cft. of console- dated base		eparin					1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.  2) It shall be payable from the nearest approved quarry.  3) The quantity of crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 122 Cft.
5	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	8.65	33.55	Metre	28.35	110.00	552-1 to 552-5	
	Bituminous Work & Resurfacing.								
6	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre.	100Sft.	152.35	1041.05	sq.m	16.40	112.00	601-1 to 601-6	
7	Providing and laying bituminous tack coat, using 10 lbs. of bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.)	100 <b>S</b> ft.	152.35	588.80	sq.m	16.40	63.35	611-1 to 611-5	
8	<ul> <li>a) Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.</li> <li>1) 1st coat:-</li> </ul>							612-1 to 612-6	

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	R	ate (British Sys	tem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre	100Sft.	133.20	2415.90	Sq.m	14.35	259.95				
	ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size 3/4" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre.	100Sft.	133.20	2101.20	Sq.m	14.35	226.10				
	2) 2nd coat:-										
	i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size $1/2$ " (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre.	100Sft.	102.45	1504.10	Sq.m	11.00	161.85				
	ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre.	100Sft.	102.45	1112.45	Sq.m	11.00	119.70				
	3) 3rd coat:-	88%		7							
	14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	70.10	853.20	sq.m	7.55	91.80				
	b) Subsequent carriage of crushed stone aggregate/bajri,	100Cft.	mce D	epartn.	cu.m				1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.		
9	a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work.							612-1 to 612-6	2) It shall be payable from the nearest approved quarry.		

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
				-			-						
	i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m.	100Sft.	88.80	1325.05	sq.m	9.55	142.60						
	ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre.	100Sft.	88.80	1201.30	sq.m	9.55	129.25						
	b) Subsequent carriage of crushed stone aggregate/bajri.	100Cft.			cu.m				Same remarks as against item 8(b) above.				
	a) Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density.  (i) 3% Bitumen  (ii) 3.5% Bitumen  (iii) 4% Bitumen  (iv) 4.5% Bitumen  (v) 5% Bitumen  (vi) 5.5% Bitumen  (vii) 6% Bitumen  b) Subsequent carriage of crushed stone aggregate/bajri.  Scarifying old road surface including removal of debris within 1 chain (30 m).	per inch thickness per 100Sft. -do- -do- -do- -do- -do- -do- 100Cft.	1055.05 1055.05 1055.05 1055.05 1055.05 1055.05	3166.55 3433.35 3700.10 3966.90 4233.55 4500.50 4767.30	The State of the S	113.55 113.55 113.55 113.55 113.55 113.55 27.30	369.55 398.30 427.00 455.70 484.45 513.15		Same remarks as against item 8(b) above.				
	Incidental Construction  Providing R.C.C. railing on bridges, as per standard drawing.	PerRft.	133.85	1071.95	Metre	439.15	3516.85	to	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of binding wire and removal of rust from the bars, etc.				
	Providing and fixing G.I. pipe railing, as per standard drawing.	Per Rft. of 3 rows of Pipes	104.90	921.00	Metre	344.20	3021.65	ditto					
	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end	-	2400.00	Each set of one end	-	2400.00	911-1 to 911-6					
	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch	-	18.00	cu.cm	-	1.10	ditto					
	Providing and laying expansion joint of neoprine strip 4"x1/4" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	86.45	213.00	Metre	283.65	698.85	921-1 to 921-4					

	MRS, 1st BI-ANNUAL	CT ATTOC	K						
Sr.	Description	R	ate (British Sys	tem)	Ra	te (Metric S	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
17	Providing and fixing rain water outlet of A.C. pipe.	Each	43.25	359.65	Each	43.25	359.65	931-1 to 933-4	
18	Providing and erection at site of work:-  i) R.C.C. mile/Km. stone  ii) R.C.C. furlong/½ Km. stone  iii) R.C.C. boundary pillar.  iv) Sign post of M.S. plate 1/8" thick (3 mm)	Each Each Each	2578.00 126.00 242.50	384.45	Each Each Each	2578.00 126.00 242.50	384.45	941-5	The rate is for complete item of work according to Standard design including cement concrete foundation block and painting letters etc.
	a) Mandatory. b) Warning/Direction/Informatory.	Each Each	818.65 792.60	5413.15 5073.40	Each Each	818.65 792.60			
19	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	3264.75	15651.15	cu.m	1153.10	5528.00		The nominal thickness of bricks (9" x 4-3/8"x 2-11/16") shall be taker for the purpose of measurement and payment.

Finance Department

## 19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- 1 Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, 1st BI-ANNUAL-201	9 (1st JA	NUARY-201	19 to 30th Jl	JNE-201	9) DISTR	ICT ATTOC	K	
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-								
	i) white ii) coloured	Each Each	432.30 432.30	2,174.95 2,360.95	Each Each	432.30 432.30	2,174.95 2,360.95		
2	Providing and fixing, double seat and cover only.								
	i) bakelite ii) plastic	Each Each	4.50 4.50	334.50 232.50	Each Each	4.50 4.50	334.50 232.50		
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.	100 P							
	i) white ii) coloured	Each Each	311.35 311.35	1,226.20 1,430.20	Each Each	311.35 311.35	1,226.20 1,430.20		
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	311.35	2,063.35	Each	311.35	2,063.35		
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	311.35	650.20	Each	311.35	650.20		
6	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.								
	i) white, with pedestal	Each	406.55	2,512.55	Each	406.55	2,512.55		
	iii) coloured, with pedestal iii) white, without pedestal	Each Each	406.55 358.95	2,698.55 1,762.95	Each Each	406.55 358.95	2,698.55 1,762.95		
	iv) coloured, without pedestal	Each	358.95	1,810.95	Each	358.95	1,810.95		
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	358.95	4,452.10	Each	358.95	4,452.10		

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description		Rate (British Sy	stem)	Ra	nte (Metric S	System)	Spec. Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18") with drain board of mosaic, including bracket set, waste pipe and waste coupling.	Each	358.95	1,152.90	Each	358.95	1,152.90						
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-												
	i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18")	Each Each	358.95 358.95	1,729.65 1,549.65	Each Each	358.95 358.95	1,729.65 1,549.65						
10	Providing and fixing glazed earthen ware flat back urinal.	Each	216.15	919.00	Each	216.15	919.00						
11	Providing and fitting glazed earthen ware low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.		3										
	i) white ii) coloured	Each Each	358.95 358.95	1,359.65 1,437.65	Each Each	358.95 358.95	1,359.65 1,437.65						
12	Providing and fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.		THE.										
	i) white	Each	358.95	1,197.65	Each	358.95	1,197.65	· · · · · · · · · · · · · · · · · · ·					
	ii) coloured	Each	358.95	1,197.65	Each	358.95	1,197.65	composite rate will be reduced by Rs. 12.50					
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	358.95	1,384.20	Each	358.95	1,384.20						
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.												
	i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity	Each Each	380.55 380.55	2,503.80 1,663.80	Each Each	380.55 380.55	2,503.80 1,663.80						
15	Providing and fixing, chromium plated soap dish.	Each	21.60	193.70	Each	21.60	193.70						
16	Providing and fitting, glazed earthen ware soap dish.												
	i) white ii) coloured	Each Each	21.60 21.60	481.70 229.70	Each Each	21.60 21.60	481.70 229.70						
17	Providing and fixing, chromium plated toilet paper holder.	Each	28.80	414.40	Each	28.80	414.40						

	MRS, 1st BI-ANNUAL-201	19 (1st JA	NUARY-201	9 to 30th JU	JNE-201	9) DISTR	ICT ATTOC	K	
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
10	Drawiding and fiving abramium plated touch rails								
18	Providing and fixing, chromium plated towel rail:-								
	i) 60 cm (24") long, and 2 cm (3/4") dia.	Each	28.80	358.90	Each	28.80	358.90		
	ii) 50 cm (20") long, and 1.5 cm (½") dia.	Each	28.80	298.90	Each	28.80	298.90		
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	54.05	386.15	Each	54.05	386.15		
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-								
	i) with chromium plated brackets and railing.	Each	67.55	390.70	Each	67.55	390.70		
	ii) glass shelf only, without chromium plated brackets	Each	43.25	88.85	Each	43.25	88.85		
	and railing.		¥ )						
		/	~	\					
21	Providing and fitting glazed earthen ware shelf 60x13 cm	. /							
	(24"x5"), with chromium plated bracket and railing:-			And the second	M.				
	i) White	Each	67.55	945.10	Each	67.55	945.10		
	ii) Coloured	Each	67.55	1,077.10	Each	67.55	1,077.10		
	, and the second	SW 1	Sugar / Jan	.67 1			,		
22	Providing and fitting:-	The State of the S							
		ACT OF THE PARTY		1000		04.00	404.45		
	i) plastic soap dish	Each	21.60 28.80	161.45 227.20	Each	21.60	161.45 227.20		
	ii) plastic toilet paper holder iii) plastic towel rail	Each Each	28.80	251.20	Each Each	28.80 28.80	251.20 251.20		
	iv) plastic shelf 60x13 cm (24"x5") with bracket and railing.	Each	28.80	432.65	Each	28.80	432.65		
	3								
23	Providing and fixing chromium plated pillar-cock, heavy:-								
	i) 2 cm (¾")	Each	28.80	700.80	Each	28.80	700.80		
	ii) 1.5 cm (½")	Each	28.80	544.80	Each	28.80	544.80		
24	Providing and fixing chromium plated stop cock, heavy:-								
	i) 2 cm (¾")	Each	28.80	280.80	Each	28.80	280.80		
	ii) 1.5 cm (½")	Each	28.80	184.80	Each	28.80	184.80		
25	Providing and fixing underground stop cock 13 mm (½"),	Each	42.35	497.30	Each	42.35	497.30		
_~	with chromium plated cover.		12.00	107.00	_3011	12.00	107.00		
26	Providing and fixing chromium plated bib cock:-					20.55	0=0.00		
	i) 2 cm (3/4")	Each	28.80	352.80	Each	28.80	352.80		
	ii) 1.5 cm (½")	Each	28.80	334.80	Each	28.80	334.80		

	MRS, 1st BI-ANNUAL-2	2019 (1st J <i>l</i>	NUARY-201	19 to 30th Jl	JNE-201	9) DISTR	ICT ATTOC	K	
Sr.	Description		Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
27	Drouiding and fiving abromium plated too stop code	Each	28.80	454.80	Each	28.80	454.80		
21	Providing and fixing chromium plated tee stop cock 15mm (1/2").	Each	26.60	454.60	Each	20.00	454.60		
28	Providing and fixing chromium plated shower rose:-								
	i) 1.5x10 cm (½"x4")	Each	28.80	334.80	Each	28.80	334.80		
	ii) 2x15 cm (¾"x6")	Each	28.80	412.80	Each	28.80	412.80		
29	Providing and fixing, chromium plated mixing valve, for wash	Each	36.05	1,560.05	Each	36.05	1,560.05		
	hand basin, sink or shower.								
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)
	i) 30 mm (1¼") dia	Each	43.25	445.25	Each	43.25	445.25		will be reduced by Rs. 66, 77, 95, 107
	ii) 40 mm(1½") dia	Each	43.25	595.25	Each	43.25	595.25		and 120 respectively.
	iii) 50 mm(2") dia	Each	43.25	823.25	Each	43.25	823.25		
	iv) 65 mm(2½") dia	Each	43.25	1,291.25	Each	43.25	1,291.25		
	v) 80 mm(3") dia	Each	43.25	1,903.25	Each	43.25	1,903.25		
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (½") dia.	18 F	- 16 m						
	i) single way	Each	28.80	376.80	Each	28.80	376.80		
	ii) two way	Each	43.25	643.25	Each	43.25	643.25		
	iii) three way	Each	57.65	783.65	Each	57.65	783.65		
		2000 P							
32	Providing and fixing, union brass cock.	Tina	MICE MA	partm	ent				
	i) 13 mm (½") dia	Each	28.80	148.80		28.80	148.80		
	ii) 20 mm (¾") dia	Each	28.80	232.80	Each	28.80	232.80		
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-								
	i) 10x5 cm (4"x2") ii) 10x7.5 cm (4"x3")	Each Each	86.45 86.45	409.25 409.25	Each Each	86.45 86.45	409.25 409.25		
34	Providing and fitting "P" trap:-								
	i) 10 cm (4") of cast iron. ii) 10 cm (4") glazed.	Each Each	72.05 72.05	470.75 140.75	Each Each	72.05 72.05	470.75 140.75		
35	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	108.10	694.90	Each	108.10	694.90		

	MRS, 1st BI-ANNUAL-20	19 (1st J/	NUARY-20°	19 to 30th J	UNE-201	9) DISTR	ICT ATTOC	K	
Sr.	Description	F	Rate (British Sy	estem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
36	Providing and fitting, cast iron soil pipe with:-								
	i) lead caulked, yarn joint:-								
		Destant	00.40	200 00	Mater	140.40	700.45		
	a) 10 cm (4") i/d b) 5 cm (2") i/d	Per foot Per foot	36.40 14.55	233.60 99.00	Metre Metre	119.40 47.75	766.15 324.65		
	ii) cement caulked joint:-								
	a) 10 cm (4") i/d	Per foot	8.05	149.15		26.40	489.15		
	b) 5 cm (2") i/d	Per foot	3.20	82.00	Metre	10.55	268.95		
37	Providing and fitting, A.C. soil pipe with cement caulked		X V						
	joint, including all specials:-			\					
	i) 60 (2½)" mm i/d	Per foot	6.45	31.15	Metre	21.10	102.25		
	ii) 80 (3") mm i/d	Per foot	7.15	72.15	Metre	23.45	236.55		
	iii) 100 (4") mm i/d iv) 150 (6") mm i/d	Per foot Per foot	8.05 10.70	107.10 133.35	Metre Metre	26.40 35.15	351.25 437.35		
	10) 130 (0 ) 111111/4	rei toot	10.70	133,80	weire	35.15	437.33		
38	Providing and fitting cast iron specials, such as tee bend,	7 16	Same 1 to	675	6.3				In case of plug type, the composite
	collar, cross, etc. plain type:-	Charles Service			27				rate shall be increased by Rs.2 per kg.
		1	V 385	150					
	i) lead caulked joint	Kg	29.65	157.90	Kg	29.65	157.90		
	ii) cement caulked joint	Kg	18.05	117.15	Kg	18.05	117.15		
39	Supply and fitting of cast iron manhole cover with frame, etc. complete.	Tina	nce Di	partm	ent				
	i) 30 cm (12") dia	Each	43.25	199.25	Each	43.25	199.25		
	ii) 45 cm (18") dia	Each	43.25	871.25		43.25	871.25		
	iii) 60 cm (24") dia	Each	70.35	1,474.35	Each	70.35	1,474.35		
40	Providing and fitting R.C.C. pipe 10 cm (4") dia, including laying and jointing in trenches.	Per foot	18.20	90.20	Metre	59.70	295.85		
41	Providing and fitting chromium plated or oxidised, gas cock 6'mm (1/4"):-								
	i) single way	Each	28.80	202.80	Each	28.80	202.80		
	ii) two way	Each	43.25	307.25		43.25	307.25		
	iii) three way	Each	57.65	501.65		57.65	501.65		
42	Providing and fitting nipple or bush, 6 mm to	Each	21.60	52.50	Each	21.60	52.50		
	10 mm (¼" to 3/8") i/d.								

	MRS, 1st BI-ANNUAL-20	19 (1st J	ANUARY-20°	19 to 30th JI	JNE-201	9) DISTR	ICT ATTOC	K
Sr.	Description		Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec. Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.
43	Providing and fixing, brass gas cock:-							
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	4.50 163.75	94.50 106.50	Each Each	4.50 163.75	94.50 106.50	
44	Providing and fixing brass stop cock/bib cock:-							
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	7.20 7.20	85.20 127.20	Each Each	7.20 7.20	85.20 127.20	
45	Hoisting and placing in position, precast R.C. latrine seats.	Each	432.30	-	Each	432.30	-	
1	Replacement  Providing and fixing, chromium plated waste coupling:-		3					
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	43.25 43.25	127.25 133.25	Each Each	43.25 43.25	127.25 133.25	
2	Providing and fixing rubber plug with chain:-	18 F		7				
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	1.75 1.75	48.55 55.75	Each Each	1.75 1.75	48.55 55.75	
3	Providing and fixing, waste pipe of PVC:-	programp in		-				
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	21.60 21.60	48.00 54.00	Each Each	21.60 21.60	48.00 54.00	
4	Providing and fixing, flushing bend of PVC.							
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	19.20 19.20	45.60 51.60	Each Each	19.20 19.20	45.60 51.60	
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-							
	i) 3 cm (1½") i/d ii) 4 cm (1½")	Each Each	43.25 43.25	559.25 679.25	Each Each	43.25 43.25	559.25 679.25	
6	Providing and fixing, angle iron brackets for:-							
	i) wash hand basin and cistern ii) sinks	Each Each	43.25 43.25	172.85 189.65	Each Each	43.25 43.25	172.85 189.65	

	MRS, 1st BI-ANNUAL-201	K							
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
7	Providing and fixing 1.5 cm (½") dia connection, including check nuts, etc.:-								
	i) plastic rubber connection ii) copper connection	Each Each	17.30 17.30	49.70 88.10	Each Each	17.30 17.30	49.70 88.10		
8	Providing and fixing brass ball float valve:-								
	i) 1.5 cm (½") dia ii) 2.0 cm (¾") dia iii) 2.5 cm (1") dia iv) 3 cm (1¼") dia v) 4.0 cm (1½") dia vi) 5 cm (2") dia	Each Each Each Each Each Each	36.05 36.05 36.05 36.05 36.05 36.05	240.05 306.05 366.05 396.05 552.05 930.05	Each Each Each Each Each Each	36.05 36.05 36.05 36.05 36.05 36.05	240.05 306.05 366.05 396.05 552.05 930.05		



Finance Department

## 20. SURFACE DRAINAGE

- 1. Specification No. correspond to Book of Specification (B & R Department ) Vol. 11, 1966 (public Health Works).
- 2. Rates for all finished works include the removal of surplus debris, unused material and by products.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-							17.1					
	a) 3" thick (75 mm)		/ x	( )	\								
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,231.15 1,231.15	4,164.90 3,960.40	Metre ditto	40.40 40.40	136.60 129.90						
	B) 4½" thick (113 mm)	8			78								
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,846.40 1,846.40	6,065.25 5,756.00	ditto ditto	60.55 60.55	198.95 188.80						
2	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled	60%	nance		992 Fana aras 1			17.1					
	and struck flush:-						607.05						
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,814.75 1,814.75 1,814.75	5,920.65 5,593.25 5,501.15	Sqm. ditto ditto	195.25 195.25 195.25	637.05 601.85 591.90						
3	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1					
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	2,572.95 2,572.95 2,572.95	8,767.40 8,242.35 8,111.65	Sqm. ditto ditto	276.85 276.85 276.85	943.35 886.90 872.80						
4	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2					
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,749.55 1749.55 1749.55		Sqm. ditto ditto	188.25 188.25 188.25	630.05 594.8 584.9						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK												
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
5	Pacca brick on edge, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as							17.2					
	per Engineer's drawing:-  a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	2,714.55 2,714.55 2,714.55	8,909.00 8,383.95 8,253.25	Sqm. ditto ditto	292.10 292.10 292.10	958.60 902.10 888.05						
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ½:5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ½" (6 mm) thick, as per Engineer's drawing (excluding excavation):-		X	5				17.1					
	a) Type I b) Type II c) Type III d) Type IV e) Type V f) Type VI g) Type VII h) Type VIII i) Type IX j) Type X k) Type XII	Per Rft ditto	41.75 83.50 110.25 131.45 173.85 200.05 221.75 247.65 332.55 365.20 407.95 434.90	104.50 192.60 251.25 299.50 407.65 467.20 514.65 577.25 816.70 895.20 995.75 1,056.55	Metre ditto	136.95 273.95 361.60 431.10 570.30 656.15 727.25 812.25 1,090.75 1,197.90 1,338.15 1,426.55	342.75 631.70 824.05 982.30 1,337.10 1,532.35 1,688.05 1,893.40 2,678.80 2,936.15 3,266.05 3,465.45						
7	Laying R.C.C hume pipes in position, including jointing:- a) 6" to 12" (150 mm to 300 mm) dia b) 12" to 24" (300 mm to 600 mm) dia c) 24" to 36" (600 mm to 900 mm) dia	Per Lft. ditto ditto	78.20 123.90 156.45	81.90 131.30 167.50	Metre ditto ditto	256.55 406.45 513.15	268.65 430.60 549.45						

## 21. SEWERAGE

- 1 Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works).
- 2 Rate for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNUAL-2			2019 to 30th	JUNE-2	019) DIST	RICT ATTO	CK	
Sr. No.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks
110.		Unit	Labour	Composite	Unit	Labour	Composite	110.	
1	Providing and laying R.C.C. pipe, moulded with cement concrete 1:1½:3, with spigot socket or collar joint, etc. including cost of reinforcement, conforming to B.S. 5911: Part I: 1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes where necessary, finishing and testing, etc., complete.  i) 100 mm (4") i/d  ii) 150 mm (6") i/d	Rft. Rft.	20.65 24.90	190.50	Metre	67.75 81.65	403.10 624.85	Chapter - 8	
2	iii) 225 mm (9:) i/d  Providing and laying non-reinforced concrete pipe, moulded with cement concrete 1:1½:3, conforming to ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipe where necessary, finishing and testing, etc. complete.  i) 100 mm (4") i/d  ii) 150 mm (6") i/d  iii) 200 mm (8") i/d  iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm)  v) 250 mm (10") i/d	Rft. Rft. Rft. Rft. Rft. Rft.	48.30 15.50 18.70 30.00 32.20 32.65	65.30 89.10 120.95 142.75	Metre Metre Metre Metre Metre	50.85 61.35 98.40 105.60 107.10	214.20 292.25 396.70 468.20 513.50	ditto	
3	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipes where necessary, testing, etc., complete.			0				ditto	
	i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	49.10 61.65 74.15 92.80 106.75 158.70 190.35 237.15 291.85 379.65 717.05 992.45 1260.1	500.15 632.15 779.50 968.05 1148.70 1400.85 1668.15 2210.80 2857.1 3809.3	Metre	161.05 202.20 243.20 304.40 350.15 520.55 624.35 777.85 957.25 1245.25 2351.9 3255.25 4133.15	1106.85 1640.50 2073.45 2556.75 3175.20 3767.75 4594.80 5471.55 7251.40 9371.3 12494.5 15639.2 17899.3		

	MRS, 1st BI-ANNUAL-2	019 (1st	JANUARY-2	2019 to 30th	JUNE-2	019) DIST	RICT ATTO	CK	
Sr.	Description	R	ate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
-	  xiv  1680 mm (66") i/d	Rft.	1981.05	6598.25	Metre	6497.85	21642.25		
	xv) 1830 mm (72") i/d	Rft.	2461.20	7496.15	Metre	8072.75	24587.35		
4	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class III, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipes where necessary, testing, etc. complete:-							Chapter-8	
5	i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	49.10 61.65 74.15 92.80 106.75 158.70 190.35 237.15 291.85 379.65 728.15 1008.05 1279.60 2012.20 2500.15	551.70 683.70 846.35 1027.35 1197.55 1502.45 1789.45 2064.75 2601.25 3283.05 4057.25 5314.85 6240.40 8338.15 10306.25	Metre Metre Metre Metre Metre Metre Metre Metre Metre Metre Metre Metre	161.10 202.20 243.30 304.30 350.15 520.50 624.30 777.90 957.20 1245.25 2388.40 3306.40 4197.05 6600.05 8200.55	1809.60 2242.55 2776.05 3369.70 3927.95 4928.05 5869.40 6772.40 8532.10 10768.40 13307.80 17432.70 20468.50 27349.15 33804.50	Chapter - 8	
	Specification C-76-79, Class IV, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipes where necessary, testing, etc. complete:-  i) 310 mm (12") i/d iii) 380 mm (15") i/d iii) 460 mm (18") i/d iii) 460 mm (24") i/d v) 610 mm (24") i/d v) 690 mm (27") i/d vi) 690 mm (30") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii) 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	49.10 61.65 74.15 92.80 106.75 158.70 190.35 237.15 291.85 379.65 728.15 1008.05 1279.60 2012.20 2500.15	625.10 751.05 968.75 1229.30 1368.90 1730.10 2090.50 2408.70 3201.00 3923.20 4913.35 6231.70 7954.00 10492.35 12460.50	Metre	161.10 202.20 243.30 304.30 350.15 520.50 624.30 777.90 957.20 1245.25 2388.15 3306.60 4197.05 6600.05 8200.55	2050.40 2463.40 3177.55 4032.10 4490.00 5674.70 6857.00 7900.45 10499.25 12868.10 16115.90 20439.85 26089.05 34414.90 40870.45		

	MRS, 1st BI-ANNUAL-	2019 (1st	JANUARY-2	2019 to 30th	JUNE-2	019) DIST	RICT ATTO	CK	1
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Lowering of sub-soil water table, by installation of tubewells along sewer line and pumping out water, for excavation in open cutting below sub-soil water level, concreting, curing, laying and jointing pipes, filling haunches, etc. till the completion of sewer line, including disposal of pumped out water:-  1) 0-1 ft. (0 to 310 mm) below SSWL 2) 0-2 ft. (0 to 610 mm) below SSWL 3) 0-3 ft. (0 to 910 mm) below SSWL 4) 0-4 ft. (0 to 1220 mm) below SSWL 5) 0-5 ft. (0 to 1520 mm) below SSWL 6) 0-6 ft. (0 to 1830 mm) below SSWL 7) 0-7 ft. (0 to 2170 mm) below SSWL 8) 0-8 ft. (0 to 2480 mm) below SSWL 9) 0-9 ft. (0 to 3100 mm) below SSWL 10) 0-10 ft. (0 to 3410 mm) below SSWL 11) 0-11 ft. (0 to 3410 mm) below SSWL 12) 0-12 ft. (0 to 3720 mm) below SSWL  Constructing gully grating chamber, 12"x12", ( 300x300 mm) complete in all respects:  a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) frame hinged safety type.  b) concrete Gully trap.	Rft of laid sewer ditto	878.80	305.55 567.60 983.15 1429.55 2011.05 2486.40 2973.80 3414.25 3675.30 4244.10 4728.35 5248.40	ditto ditto ditto ditto ditto ditto ditto ditto	- - - - - - - - - - 878.80	1002.15 1861.75 3224.65 4688.95 6596.20 8155.45 9754.15 11198.70 12055.05 13920.75 15508.95 17214.70 3169.85	16.2	1) This rate shall be payable, in addition to the item of excavation below SSWL for sewers and manholes under Chapter, EARTHWORK 2) The grant of these rates shall be subject to Superintending Engineer's approval.  3) The rate includes cost of providing pumps, POL and all operation charges at the site of work, etc.  Pipe connection to be paid separately.
8	Constructing standard gully grating chamber, 3'x2½' (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects.	Each	2628.45	9222.40	Each	2628.45	9222.40	ditto	Pipe connection to be paid separately.
9	Extra for making and finishing benching floor work in manhole chamber, with 1/8" (3 mm) thick cement finish.	100 <b>S</b> ft.	1078.70	1636.45	Sq.m	116.05	176.10	14.4	
10	Restoration of brick pavement on edge, over laid service line, with 2" (50 mm) sand cushion under soling.	100Sft.	1577.40	3309.85	Sq.m	169.75	356.15	13.1	
11	Restoration of flat brick pavement sand grouted, over 2" (50 mm) thick dry sand cushion, under soling on laid service line.	100Sft.	956.65	2188.00	Sq.m	102.95	235.45	13.1	
12	Restoration of metalled road, on laid service line, including compaction:-							13.1	
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base.	100Sft.	2901.20	9101.15	Sq.m	312.15	979.30		

	MRS, 1st BI-ANNUAL-2	019 (1st	JANUARY-2	019 to 30th	JUNE-2	019) DIST	RICT ATTO	CK	
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) Carpeted road, with 1½" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base.	100 <b>S</b> ft.	2063.00	6659.25	Sq.m	222.00	716.55		
	c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base.	100Sft.	1034.80	4588.90	Sq.m	111.35	493.75		
13	Providing and fixing 1¼"x1¼"x3/16" (31x31x5 mm) angle iron step, in manhole chambers, including carriage and setting the same in work to correct lines and levels.	Each	88.55	283.15	Each	88.55	283.15	14.7	
14	Fixing manhole frame and cover in R.C.C. slab including carriage to site.	Per set	239.15	-	Per set	239.15	-	ditto	
15	Providing and fixing 3" (75 mm) thick R.C.C. manhole cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20" (500 mm) clear i/d (frame weighing 37.324 Kg. or one maund) as per Standard Drawing STD/PD No. 5, of 1977, complete in all respects.	Per set	154.65	6006.25	Per set	154.65	6006.25	ditto	
15-A	Providing and fixing 6" thick R.C.C. manhole cover with tee shaped C.I. frame of 22" I/d (frame weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect.	Per set	339.55	7583.15	Per set	339.55	7583.15		
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects.	Per set	303.55	3090.15	Per set	303.55	3090.15	ditto	
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover with 3"x3"x½" (75x75x6mm) angle iron frame, 22" (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects.	Per set	251.35	4875.85	Per set	251.35	4875.85	ditto	
18	Desilting of disposal work collecting tank, including removal of sludge within 3 chains (90 metre).	100Cft.	870.45	924.75	cum	307.45	326.60	16.2	
19	Providing and installing, C.I. ventilating shaft painted with bituminous paint with foundation bolts, as per PHED Standard Drawing STD/PD No. 4 of 1977, complete in all respects (except concrete foundation block):-							14.6	
	a) 6" (150 mm) i/d shaft								
	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long	Per Cwt ditto ditto ditto	244.45 271.60 293.35 306.95	6363.55 6399.10 6416.70 6431.85	%kg ditto ditto ditto	481.20 534.65 577.45 604.20	12596.65 12631.35		

Sr.	Description	Rate (British System)			Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) 9" (225 mm) i/d shaft								
	<ul> <li>i) 18 ft. (5.5 metre) long</li> <li>ii) 24 ft. (7.30 metre) long</li> <li>iii) 30 ft. (9.15 metre) long</li> <li>iv) 36 ft. (11 metre) long</li> </ul>	Per Cwt ditto ditto ditto	217.40 234.25 250.80 301.90	6333.05 6349.30 6365.65 6416.60	ditto ditto	427.90 461.10 493.75 594.30			
	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long	Per Cwt ditto ditto	193.25 248.50 289.90	6309.70 6361.40 6402.30	%kg ditto ditto	380.45 489.15 570.70			
	Silt clearing 10' (3.00 m) dia wells, and removal of slush outside the compound:-  a) upto 10' (3.00 m) depth of slush  b) beyond 10' (3.00 m) depth of slush	Per well Per well	6782.80 13462.70		Per well Per well	6782.80 13462.70	- -		

Finance Department

# 22. SINKING OF WELLS

- Rates for all finished works include the removal of surplus debris, unused material and byproducts.
   Well curbs to be laid at spring level or as deep as possible.

MRS, 1st BI-ANNUAL-2019 (1s	t JANUARY-2019 to 30th JUNE-2019	9) DISTRICT ATTOCK
· · · · · · · · · · · · · · · · · · ·		•

Sr.	Description	F	Rate (British Sy	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Excavation of well in dry upto 20'(6 metre) below ground level, and disposal of soil within one chain (30 metre)								
	a) in ordinary soil or sand :-	1000 Cft.			cu.m				
	i) from 0' to 5' (o to 1.5 m) depth ii) from 5.1' to 10' (1.5 to 3.0 metre) depth iii) from 10.1' to 15' (3.0 to 4.5 metre) depth iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth	ditto ditto ditto ditto	4527.20 4728.25 5319.30 6105.30		ditto ditto ditto ditto	159.90 167.00 187.90 215.65			
	<ul> <li>i) from 0' to 5'(0 to 1.5 metre) depth</li> <li>ii) from 5.1' to 10'(1.5 to 3.0 metre) depth</li> <li>iii) from 10.1' to 15'(3.0 to 4.5 metre) depth</li> <li>iv) from 15.1' to 20'(4.5 to 6.0 metre) depth</li> <li>c) in hard strata, such as shingle, gravel, etc.</li> </ul>	1000 Cft. ditto ditto ditto	5514.25 5764.10 6300.30 7086.30		cu.m ditto ditto ditto	194.75 203.60 222.55 250.30	-		
	i) from 0' to 5'(0 to 1.5 metre) depth ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth	1000 Cft. ditto ditto ditto	11893.75 12320.30 12844.30 13788.75		cu.m ditto ditto ditto	420.10 435.15 453.65 487.00			
2	Dry sinking of well, including loading, and removing excavated material within one chain (30 m):-								
	a) in ordinary soil :-								
	i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth iv) from 25.1' to 30'(7.5 to 9.0 m) depth v) from 30.1' to 35'(9.0 to 10.5 m) depth vi) from 35.1' to 40'(10.5 to 12.0 m) depth vii) from 40.1'to 45'(12.0 to 13.5 m) depth viii) from 45'(13.5 Sm) to any depth	1000 Cft. ditto ditto ditto ditto ditto ditto	24372.50 30465.60 36558.70 42651.85 48744.95 54838.10 60931.20 67024.30		cu.m ditto ditto ditto ditto ditto ditto	860.85 1076.05 1291.25 1506.45 1721.65 1936.90 2152.10 2367.30			
	b) in hard soil :-								
	i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth iv) from 25.1' to 30'(7.5 to 9.0 m) depth	1000 Cft. ditto ditto ditto	33512.15 39605.30 45698.40 51791.50	-	cu.m ditto ditto ditto	1183.65 1398.85 1614.05 1829.30	-		

	MRS, 1st BI-ANNU	DISTRICT A	TTOCK						
Sr.	Description	F	ate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				•					
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	57884.65	-	ditto	2044.50	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	63977.75	-	ditto	2259.70	-		
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	70070.90	-	ditto	2474.90	-		
	viii) from 45'(13.5 m) to any depth	ditto	76164.00	-	ditto	2690.10	-		
	c) in hard strata, such as shingle, gravel, etc.								
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	45698.40	-	cu.m	1614.05	-		
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	51791.50	-	ditto	1829.30	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	57884.65	-	ditto	2044.50	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	58646.30	¥ 1	ditto	2071.40	-		
1	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	70070.90	-	ditto	2474.90	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	76164.00	-	ditto	2690.10	-		
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	82257.10		ditto	2905.30	-		
	viii) from 45'-1" (13.5 m) to any depth	ditto	88350.25		ditto	3120.55	-		
3	Wet sinking of well in ordinary soil (value of C upto 5), for	Service	1			W.		* 841-1	The outer dimensions of the curb
	depths below spring level, including charges of machinery,	#3	W. L	12 50	7 18	3		to	shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within	~						841-9	
	one chain (30 m):-				155				
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	37053.20	-	cu.m	1308.70	-		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto 🥤	78738.00	e Deni	ditto	2781.05	-		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	96908.30	n arabba	ditto	3422.80	-		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	125980.80	-	ditto	4449.65	-		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	139978.65	-	ditto	4944.05	-		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	157476.00	-	ditto	5562.05	-		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	161513.85	-	ditto	5704.65	-		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	165764.20	-	ditto	5854.80	-		
	ix) above 80'(24.0 m) to any depth	ditto	179972.55	-	ditto	6356.65	-		
4	Wet sinking of well in cohesive soil (value of Cmore than							*841-1	The outer dimensions of the curb
	5), for depths below spring level, including charges of							to	shall form basis of payment.
	machinery shoring, kentledge and removal of excavated							841-9	
	spoil within one chain (30 m):-								
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	-	51141.65	cu.m	-	1806.30		
1	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	-	63927.10	ditto	-	2257.90		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	76712.50	ditto	-	2709.50		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	102283.30	ditto	-	3612.65		
1	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	-	118019.20		-	4168.45		
1	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	-	127854.15		-	4515.80		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	-	139477.25		-	4926.35		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	-	144740.55	ditto	-	5112.25		
	ix) above 80'(24.0 m) to any depth	ditto	-	153425.00	ditto	-	5418.95		
<u></u>									

Sr.	Description	R	ate (British Sy	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	Wet sinking of well in shingle, or gravel, etc, for depths							*841-1	The outer dimensions of the curb
	below spring level, including charges of machinery,							to	shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within							841-9	
	one chain (30 m):-	1000 Cft.		69738.65	011.00		2463.15		
	i) from o' to 10'(0 to 3.0 m) depth	ditto	-	85236.10	cu.m ditto	-	3010.55		
	ii) above 10' to 20'(3.0 to 6.0 m) depth iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	102283.30	ditto	-	3612.65		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	139477.25	ditto		4926.35		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	_	153425.00	ditto		5418.95		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto		170472.20	ditto	_	6021.10		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	-	178401.15	ditto	_	6301.15		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	/-	182648.80	ditto	_	6451.15		
	ix) above 80'(24.0 m) to any depth	ditto	/ -	201875.00	ditto	_	7130.20		
	,,			the same of the sa					
6	Making and fixing in position, kiker wood well curb.	Per Cft.	1040.05	2843.35	cu.m	36734.90	100427.60		
7	Laying well curb in position only.	Each	345.85	1 - 60	Each	345.85	-		
8	Providing, making and laying R.C.C. well curb in position,	70		195 mm		19		* 841-1	1) If concrete mixer is supplied by
	using coarse sand, including all kinds of form, moulds,		<b>CONT.</b>		153			to	Government, all charges including
	curing, shuttering, rendering and finishing the exposed							841-9	depreciation will be recovered from
	surface, (including screening and washing of aggregate:-								the contractor.
		0	Gi 22/322/	e Demo		1227			2) The rate does not include cost of
	a) Ratio 1:11/2:3	Per Cft.	226.55	455.30	cu.m	8000.85	16081.85		steel reinforcement and its labour for
	b) ratio 1:2:4	ditto	226.55	424.65	ditto	8000.85	14999.35		bending, which is payable, separately.
9	Providing and fixing structural steel for cutting	100Kg	813.10	13344.25	100Kg	813.10	13344.25	841-1 to	
	edge.							841-9	
10	Making and removing false masonry on well.	100Cft.	7366.50	20492.35	cu.m	2601.85	7237.90		The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.

<sup>\*</sup> Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

## 23. TUBEWELL AND WATER SUPPLY

- Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)".
   Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUA	RY-2019 to 3	Oth JUNE	-2019) D	ISTRICT ATT	OCK	
Sr. No.	Description	R	ate (British S	System)	Ra	te (Metric	System)	Spec. No.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
1	Boring for tubewell in all types of soil except shingle and rock, from ground level to 100 ft. (30 m) depth, including sinking and withdrawing of casing pipe, complete:-							Chap. 2	
2	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d  Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 100.1 ft. to 200 ft. (30 to 60 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d	Per Rft. of bore ditto	nanci	64.45 87.75 159.50 242.15 315.70 399.55 433.10 654.75 694.45 268.15 377.25 428.20 489.85 531.05 768.55 808.30	ditto		211.40 287.75 523.20 794.25 1035.50 1310.60 1420.55 2147.55 2277.85 879.60 1237.40 1404.45 1606.65 1741.85 2520.85 2651.20	ditto	
3	Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 200.1 ft. to 300 ft. (60 to 90 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d	Per Rft. of bore ditto ditto ditto		374.80 483.25 540.05 609.30 644.10	of bore ditto ditto ditto		1229.30 1585.05 1771.35 1998.55 2112.60	ditto	
4	f) 15" (375 mm) i/d g) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 300.1 ft. to 400 ft. (90 to 120 m) below ground level, including sinking and withdrawing of casing pipe, complete:-	ditto ditto		844.50 885.45			2769.95 2904.30	Chap. 2	

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	Ra	ate (British S	ystem)	Ra	te (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
				•			•				
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	Rft of bore ditto ditto ditto ditto		652.50 729.40 766.05 1033.45 1037.15	ditto ditto		2140.25 2392.50 2512.60 3389.70 3401.90				
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells, in all types of soil except shingle, gravel and rock:-							ditto			
	a) from ground level to 250 ft. (75 m) below ground level:-										
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto		512.90 737.65			1682.35 2419.50				
	b) exceeding 250 ft. (75 m) depth below ground level:-		/		\						
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Rft of bore ditto		512.90 737.65			1682.35 2419.50				
6	Boring for tubewell in shingle, gravel and rock, including sinking and withdrawing of casing pipe:-	100		رهگورت پنجا مرحکورت پنجا	153			ditto	Location and depth of shingle, gravel or rock is to be determined from the bore log.		
	a) from ground level to 200 ft. (60 m) below ground level:-										
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto	nanci	1156.80 1564.50		ž.	3794.25 5131.55				
	b) exceeding 200 ft. (60 m) depth below ground level:-										
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	ditto ditto		1156.80 1564.50			3794.25 5131.55				
	Providing strong substantially built box of deodar wood 4'x2½x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	772.60	12387.40	Job for compl- ete bore	772.60	12387.40	ditto			
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	118.80	170.70	Per Set of 2 bottles	118.80	170.70	Chap. 2			
	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc. complete:-							ditto	Cost/labour of jointing both ends is included in the rate.		
	a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick	Per Rft. Per Rft.	31.10 31.10		Per Metre Per Metre	102.00 101.95	2802.05 4179.65				

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUA	RY-2019 to 3	0th JUNE	-2019) DI	STRICT ATT	OCK	
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				-					
	c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick	Per Rft. Per Rft.	41.45 47.05	1536.65 1962.25		135.95 154.35	5040.20 6436.20		
	d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick  e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick	Per Rft.	51.80	2204.30		169.95	7230.15		
	f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick	Per Rft.	60.95	2659.70		199.85	8723.75		
	g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick	Per Rft.	74.60	3140.60		244.75	10301.25		
	h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick	Per Rft.	74.60	3266.60		244.75	10714.50		
	i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick	Per Rft.	84.40	3601.90		276.85	11814.25		
	i) 10" i/d, 1/4" (250 mm i/d 6 mm) thick	Per Rft.	84.40	4590.20	Per Metre	276.85	15055.90		
	k  12" i/d, ½" (300 mm i/d 6 mm) thick	Per Rft.	85.65	5225.40		280.90	17139.25		
	I) 15" i/d, ¼" (375 mm i/d 6 mm) thick	Per Rft.	98.65	6438.05		323.65	21116.80		
	m) 18" i/d, ½" (450 mm i/d 6 mm) thick	Per Rft.	98.65	7317.40		323.65	24001.15		
	n) 20" i/d, ½" (500 mm i/d 6 mm) thick	Per Rft.	116.90	8082.50		383.50	26510.55		
	o) 22" i/d, ½" (550 mm i/d 6 mm) thick	Per Rft.	118.15	9282.05		387.55	30445.05		
	22 74, 74 (000 11111) thick	i or rate	110.10	0202.00	1 GI WIGHT	007.00	00110.00		
10	Providing and installing M.S. Bail plug in tubewell bore			*)					In the case of increase or decrease
	hole:		/	1	\				in the length of Bail plug, the rates will be increased or decreased as
	a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long.	Each	145.65	638.50	Each	145.65	638.50		per rates given in serial No. 14 of
	b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long.	Each	145.65	837.45	Each	145.65	837.45		this chapter for the respective
	c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long.	Each	243.10	1579.05	Each	243.10	1579.05		diameter.
	d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long.	Each	243.10	1974.90	Each	243.10	1974.90		
	e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long.	Each	328.10	2493.55	Each	328.10	2493.55		
	f) 7" i/d, 2 ft. (175 mm i/d 600 mm) long.	Each	328.10	2882.35	Each	328.10	2882.35		
	g) 8" i/d, 2 ft. (200 mm i/d 600 mm) long	Each	404.50	3204.75	Each	404.50	3204.75		
	h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long	Each	404.50	3548.65	Each	404.50	3548.65		
	i) 10" i/d, 2 ft. (250 mm i/d 600 mm) long	Each	404.50	4499.60	Each	404.50	4499.60		
	j) 12" i/d, 2 ft. (300 mm i/d 600 mm) long	Each	485.50	5407.90	Each	485.50	5407.90		
	k) 15" i/d, 2 ft. (375 mm i/d 600 mm) long	Each	485.50	6639.00	Each	485.50	6639.00		
	l) 18" i/d, 2 ft. (450 mm i/d 600 mm) long	Each	583.75	7583.10	Each	583.75	7583.10		
	m) 20" i/d, 2 ft. (500 mm i/d 600 mm) long	Each	635.00	8409.85	Each	635.00	8409.85		
	n) 22" i/d, 2 ft. (550 mm i/d 600 mm) long	Each	635.00	9240.45		635.00	9240.45		
11	Providing and installing, P.V.C. strainer B.S.S. Class 'B',							Chap. 2	
	in tubewell bore hole, including sockets and solvents, etc.								
	complete:-								
	a) 3" i/d (75 mm)	Per Rft.	22.80	123 60	Per Metre	74.70	405.35		
	b) 4" i/d (100 mm)	Per Rft.	25.95		Per Metre	85.15	592.90		
	c) 5" i/d (125 mm)	Per Rft.	27.50		Per Metre	90.15	798.60		
	d) 6" i/d (150 mm)	Per Rft.	32.20	320.20		105.55	1050.20		
	e) 8" i/d (200 mm)	Per Rft.	44.00		Per Metre	144.35	2505.95		
	f) 10" i/d (250 mm)	Per Rft.	45.00	1137.00		147.65	3729.40		
	g) 12" i/d (300 mm)	Per Rft.	45.00		Per Metre	147.65	4988.95		
12	Providing and installing P.V.C. strainer B.S.S. Class `D',								
	in tubewell bore hole, including sockets and solvent, etc.								
	complete:-								
	a) 1½" i/d (30 mm)	Per Rft.	15.90	55 50	Per Metre	52.15	182.05		
	199 174 174 (00 min)	. 51 1(1).	10.00	55.50	I GI IVIGUIG	UZ. 10	102.00		

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
				•			•				
	b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft.	16.25 16.40 22.80 25.90 27.45 49.20	188.40 294.70 429.45	Per Metre	53.35 53.85 74.75 84.95 90.10 161.35	202.9 305.75 617.95 966.6 1408.65 2030.95				
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:-										
	i) B.S.S. Class`B'										
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Each Each Each Each Each Each Each	11.05 12.40 13.55 17.60 20.95 22.15 25.75 25.75	63.85 84.40 125.15 182.00 354.55 490.15 661.75 685.75	Each Each Each	11.05 12.40 13.55 17.60 20.95 22.15 25.75 25.75	63.85 84.40 125.15 182.00 354.55 490.15 661.75 685.75				
	ii) B.S.S. Class`D'  a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each	7.50 7.95 8.20 11.05 12.45 13.55 17.65	35.10 48.75 68.20 91.45 119.25 167.15 218.05	Each Each Each	7.50 7.95 8.20 11.05 12.45 13.55 17.65	35.10 48.75 68.20 91.45 119.25 167.15 218.05				
14	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:-							Chap. 2			
	a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, ½" (250 mm i/d 6 mm) thick j) 12" i/d, ½" (300 mm i/d 6 mm) thick k) 15" i/d, ½" (375 mm i/d 6 mm) thick l) 18" i/d, ½" (450 mm i/d 6 mm) thick m) 20" i/d, ½" (550 mm i/d 6 mm) thick n) 22" i/d, ½" (550 mm i/d 6 mm) thick	Per Rft.	87.10 87.10 108.95 108.95 155.50 155.50 181.45 181.45 217.75 217.75 266.90 287.50	366.70 482.15 851.75 1074.70 1229.50 1358.85 1532.65 1953.85 2302.75 2824.00 3507.25 3887.90	Per Metre	285.70 285.70 357.35 357.35 510.05 595.15 595.15 595.15 714.20 714.20 875.45 943.00 943.00	927.25 1202.80 1581.45 2793.75 3525.00 4032.75 4457.10 5027.10 6408.65 7553.00 9262.70 11503.75 12752.25 13933.15				

	MRS, 1st BI-ANNUA	STRICT ATT	OCK						
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
15	Providing and installing P.V.C. blind pipe, B.S.S. Class							ditto	
	`B', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete.								
	a) 3" i/d (75 mm)	Per Rft.	30.25		Per Metre	99.15	442.00		
	b) 4" i/d (100 mm)	Per Rft. Per Rft.	34.20	191.00 255.70	Per Metre Per Metre	112.20 117.20	626.45 838.70		
	c) 5" i/d (125 mm) d) 6" i/d (150 mm)	Per Rit. Per Rft.	35.75 42.80	255.70 350.90	Per Metre	138.85	1149.40		
	e) 8" i/d (200 mm)	Per Rft.	57.15	522.00	Per Metre	187.40	1712.20		
	f) 10" i/d (250 mm)	Per Rft.	59.50	882.70	Per Metre	195.15	2895.25		
	g) 12" i/d (300 mm)	Per Rft.	71.20	1227.00	Per Metre	233.45	4024.60		
	h) 14" i/d (350 mm)	Per Rft.	68.10	1457.25	Per Metre	223.35	4779.85		
16	Providing and installing P.V.C. blind pipe, B.S.S. Class `D', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete.			C					
	a) 1¼" i/d (30 mm)	Per Rft.	18.95	56.40	Per Metre	62.10	184.90		
	b) 1½" i/d (40 mm)	Per Rft.	19.30	66.85	Per Metre	63.25	219.30		
	c) 2" i/d (50 mm)	Per Rft.	20.50	95.35		67.20	312.80		
	d) 3" i/d (75 mm)	Per Rft.	25.90	187.35	and the second of	85.00	614.55		
	e) 4" i/d (100 mm)	Per Rft.	34.20		Per Metre	112.20	1000.00		
	f) 5" i/d (125 mm)	Per Rft.	35.75	The second of th	Per Metre	117.20			
	g) 6" i/d (150 mm)	Per Rft.	43.55	628.55	Per Metre	142.90	2061.70		
17	Testing and developing of tubewell of size 6" (150 mm) i/d and above continuously.								Compressor, accessories along with working staff, to be supplied by
	i) wate 4.5 on all only one	D. 1-1	nance	1100.75	tmen	Ĺ	4400.75		Government.
	i) upto 1.5 cs. discharge	Per Hour		1122.75	Per Hour		1122.75		
	ii) above 1.5 cs. discharge	ditto		1357.25			1357.25		
18	Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3 mm), around tubewell in bore hole.	Per Cft.	36.20	87.85		1278.55	3102.85		The rate includes wastage, etc.
19	Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc. complete in all respects:-							Chap. 2	<ol> <li>Pipes to be supplied by Government.</li> <li>Providing and installing specials and valves is not included in the rate, which is payable separately.</li> </ol>
	a) 3" (75 mm) i/d	Per Rft.		58.45	Per Metre		191.70		
	b) 4" (100 mm) i/d	Per Rft.			Per Metre		237.35		
	c) 5" (125 mm) i/d	Per Rft.			Per Metre		298.65		
	d) 6" (150 mm) i/d	Per Rft.			Per Metre		351.55		
	e) 8" (200 mm) i/d	Per Rft.			Per Metre		420.25		
	f) 10" (250 mm) i/d	Per Rft.			Per Metre		638.55		
	g) 12" (300 mm) i/d b) 15" (375 mm) i/d	Per Rft.			Per Metre		750.05 966.45		
	h) 15" (375 mm) i/d	Per Rft.		294.00	Per Metre		900.45		

	MRS, 1st BI-ANNU	AL-2019 (1	st JANUA	RY-2019 to 3	0th JUNE	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	ate (British S	System)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 18" (450 mm) i/d	Per Rft.		387 20	Per Metre		1270.05		
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:-	re Nit.		307.20	ra Male		1270.03	ditto	Pipes to be supplied by Government.     Providing and installing specials
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft.		29.50 41.40 45.60 53.55 74.05 87.00 120.30	Per Metre		87.50 96.70 135.75 149.65 175.60 242.90 285.30 394.45 505.65		and valves is not included in the rate, which is payable separately.
21	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches with Tyton joints, complete in all respects:-				) w.			Chap. 2	Pipes to be supplied by Government.     Providing and installing specials
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft.	nanci	14.40 18.60 20.85 28.35 35.90 42.65 60.20	Per Metre	of the state of th	41.75 47.25 61.05 68.30 93.05 117.80 139.90 197.45 236.35		and valves is not included in the rate, which is payable separately.
22	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves.							Chap. 2	Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) Light Quality								
	a) ½" i/d (15 mm) 2mm thick b) ¾" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1¼" i/d (32 mm) 2.65mm thick e) 1½" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"½ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick	Per Rft.	10.35 11.30 12.80 12.90 13.00 14.55 15.15 17.40 18.75	98.10 136.20 174.25 213.70 268.10 373.10 432.35	Per Metre	34.00 37.15 42.00 42.30 42.65 47.70 49.60 57.10 61.45	234.15 321.80 446.70 571.60 700.95 879.40 1223.80 1418.05 2013.95		
	ii) Medium Quality  a) ½" i/d (15 mm) 2.65mm thick b) ¾" i/d (20 mm) 2.65mm thick	Per Rft. Per Rft.	10.35 11.30		Per Metre Per Metre	34.00 37.15	278.65 352.90		i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia,

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUA	RY-2019 to 3	0th JUNE	-2019) DI	STRICT ATT	OCK	
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) 1" i/d (25 mm) 3.25mm thick d) 11/4" i/d (32 mm) 3.25mm thick	Per Rft. Per Rft.	12.8 12.90	200.05	Per Metre Per Metre	42 42.30	517.9 656.10		3/4"dia & 1/2"dia) for Bath rooms/ Levorotary.
	e) 1½" i/d (40 mm) 3.25mm thick f) 2" i/d (50 mm) 3.65mm thick g) 2"½ i/d (65 mm) 3.65mm thick	Per Rft. Per Rft. Per Rft.	13.20 14.55 15.15	316.95	Per Metre Per Metre Per Metre	43.35 47.70 49.60	754.95 1039.50 1326.10		ii. For internal G.I piping (1"dia, 3/4"dia & Bath room(s)/ Levorotary of rate
	h) 3" i/d (75 mm) 4.05mm thick i) 4" i/d (100 mm) 4.5mm thick j) 5" i/d (150 mm) 4.85mm thick	Per Rft. Per Rft. Per Rft.	17.40 18.75 21.70	741.50	Per Metre Per Metre Per Metre	57.10 61.45 71.15	1702.70 2432.05 3277.90		(composite) shall be reduced by 8% and specials mentioned above may be paid at the rates placed on
	k) 6" i/d (200 mm) 4.85mm thick  iii) Heavy Quality	Per Rft.	22.00	1175.95	Per Metre	72.15	3857.15		Website as per actual quantity used.
	a) ½" i/d (15 mm) 3.25mm thick	Per Rft.	10.35	114.80	Per Metre	34.05	376.50		
	b) <sup>3</sup> / <sub>4</sub> " i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick d) 11/ <sub>4</sub> " i/d (32 mm) 4.05mm thick	Per Rft. Per Rft. Per Rft.	11.30 12.80 12.90	221.60	Per Metre Per Metre Per Metre	37.15 42.00 42.30	481.90 726.95 936.30		
	e) 1½" i/d (40 mm) 4.05mm thick f) 2" i/d (50 mm) 4.5mm thick	Per Rft. Per Rft. Per Rft.	13.20 14.55 15.15	323.75 452.55		43.35 47.70 49.60	1061.85 1484.30 1770.85		
	g) 2"½ i/d (65 mm) 4.5mm thick h) 3" i/d (75 mm) 4.85mm thick i) 4" i/d (100 mm) 5.4mm thick	PerRft. PerRft.	17.40 18.75	713.05 1037.10	Per Metre Per Metre	57.10 61.45	2338.75 3401.65		
	j) 5" i/d (125 mm) 5.4mm thick k) 6" i/d (150 mm) 5.4mm thick	Per Rft. Per Rft.	21.70 22.00	and the second s	Per Metre Per Metre	71.15 72.15	4096.30 4986.85		
23	Providing, laying, cutting, jointing, testing and disinfecting Asbestos Cement / Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:-	$_{\it Fi}$	nanci	: Depai	tmen	t		PS 428 & ISO 160	Providing and installing specials and valves is not included in the
	B Class Working Pressure			-					rate, which is payable separately.
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Per Rft. Per Rft.	14.85 15.70	299.80	Per Metre Per Metre	48.65 51.45	755.55 983.30		
	c) 6" i/d (150 mm) d) 8" i/d (200 mm)	Per Rft. Per Rft.	21.50 29.65	796.20	Per Metre Per Metre	70.50 97.20	1560.65 2611.50		
	e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm)	Per Rft. Per Rft. Per Rft.	38.60 49.15 56.80	1434.10	Per Metre Per Metre Per Metre	126.55 161.20 186.25	3556.60 4703.80 6772.95		
	h) 16" i/d (400 mm) i) 18" i/d (450 mm)	Per Rft. Per Rft.	64.10 75.60	2620.80 3265.35	Per Metre Per Metre	210.25 248.00	8596.15 10710.40		
	j) 20" i/d (500 mm) k) 24" i/d (600 mm) l) 28" i/d (700 mm)	Per Rft. Per Rft. Per Rft.	88.85 106.05 112.65	5542.10	Per Metre Per Metre Per Metre	291.45 347.85 369.45	13179.00 18178.00 29160.25		
24	m) 32" i/d (800 mm) n) 40" i/d 1000 mm) C Class Working Pressure	Per Rft. Per Rft.	122.15 134.20		Per Metre Per Metre	400.65 440.25	33367.20 51513.65	PS 428 &	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Per Rft. Per Rft.	14.85 15.70	10064.85		48.65 51.45	28834.50 33012.75	ISO 160	
	c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Per Rft. Per Rft. Per Rft.	21.50 29.65 38.60	352.40	Per Metre Per Metre	70.50 97.20 126.55	51138.40 804.90 1155.80		
	f) 12" i/d (300 mm) g) 14" i/d (350 mm)	Per Rft. Per Rft.	49.15 56.80	595.65 925.40	Per Metre Per Metre	161.20 186.25	1953.70 3035.25		

	MRS, 1st BI-ANNUA	STRICT ATT	OCK						
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	h) 16" i/d (400 mm)	Per Rft.	64.10	1278.05	Per Metre	210.25	4192.00		
	h) 16" i/d (400 mm)  i) 18" i/d (450 mm)	Per Rft.	75.60	1772.10		248.00	5812.45		
	i) 20" i/d (500 mm)	Per Rft.	88.85	3038.80		291.45	9967.25		
	k) 24" i/d (600 mm)	Per Rft.	107.45	3884.95		352.45	12742.65		
25	D Class Working Pressure							PS 428 &	
	a) 3" i/d (75 mm)	Per Rft.	14.85	4650.20		48.65	15252.70	ISO 160	
	b) 4" i/d (100 mm)	Per Rft.	15.70	5532.40		51.45	18146.25		
	c) 6" i/d (150 mm)	Per Rft.	21.50	7806.35		70.50	25604.80		
	d) 8" i/d (200 mm)	Per Rft.	29.65	245.40		97.20	804.90		
	e) 10" i/d (250 mm) f) 12" i/d (300 mm)	Per Rft. Per Rft.	38.60	397.65		126.55	1304.35		
	g) 14" i/d (350 mm)	Per Rit. Per Rft.	49.15 56.80	708.25 1230.15		161.20 186.25	2323.05 4034.95		
	h) 16" i/d (400 mm)	Per Rft.	64.10	1801.90		210.25	5910.30		
	i) 18" i/d (450 mm)	Per Rft.	75.60	2616.65		248.00	8582.60		
	j) 20" i/d (500 mm)	Per Rft.	88.85		Per Metre	291.45	14319.20		
	,,, == ,, = (=== ,,		/	· was	\				
26	Providing, laying, cutting, jointing, testing and disinfecting		/		1			PS 3051	Providing and installing specials
	P.V.C. pipe line with `B' Class working pressure	法	The second district of					BS 3505	and valves is not included in the
	pipe, in trenches, complete in all respects:-	188	Property and the second	And the second s	7 124				rate, which is payable separately.
		- 307	-	The Road of the Local District Control Distr					
	a) 3" i/d (75 mm)	Per Rft.	4.30	110.90	Per Metre	14.05	363.70		
	b) 4" i/d (100 mm)	Per Rft. Per Rft.	5.50	165.40		17.95	542.50		
	c) 5" i/d (125 mm) d) 6" i/d (150 mm)	Per Rit.	6.70 7.00	231.05 321.25	and the second s	21.90 23.00	757.80 1053.75		
	d) 6" i/d (150 mm)  e) 8" i/d (200 mm)	Per Rft.	9.95	484.10	The state of the s	32.60	1587.90		
	f) 10" i/d (250 mm)	Per Rft.	13.20	852.85		43.30	2797.40		
	h) 12" i/d (300 mm)	Per Rft.	16.35	1195.30		53.70	3920.65		
	g) 14" i/d (350 mm)	Per Rft.	21.15	1438.15	7 TOT - COLORADO - LANCE - COLORADO - COLORA	69.45	4717.05		
27	Providing, laying, cutting, jointing, testing and disinfecting							Chap	Providing and installing specials
	pipe line in trenches with P.V.C. pipes of B.S.S. with `D'							2	and valves is not included in the
	Class working pressure complete in all respects:-								rate, which is payable separately.
	a) 2" i/d (50 mm)	Per Rft.	3.45		Per Metre	11.40	261.90		
	b) 3" i/d (75 mm)	Per Rft.	4.25		Per Metre	13.85	554.05		
	c) 4" i/d (100 mm)	Per Rft.	5.40		Per Metre	17.75	923.30		
	d) 5" i/d (125 mm)	Per Rft.	6.60		Per Metre	21.65	1357.75		
	e) 6" i/d (150 mm)	Per Rft.	6.90	603.60	Per Metre	22.70	1979.85		
28	Providing and fixing cast iron special of B.S.S. Class `B'							9.1	i) Labour rates include the cost of
	(such as bend, tee cross collar, reducer, tail piece,								jointing material & labour.
	flanged spigot, cap, flanged socket, taper, angle branch,								
	plug etc.) for cast iron pipe line, complete:-								ii) The internal dia of the pipe, from
	a) C.I.S.S. Specials, with spigot. and								be considered the internal dia for
	socket joint:-								the purpose of payments of
	i) 3" to 6" (75 to 150 mm) i/d	Per Kg.	23.60	122.15	Per Kg	23.60	122.15		specials.
	ii) 8" to 12" (200 to 300 mm) i/d	Per Kg.	12.90	111.45	U	12.90	111.45		
	iii) 15" to 18" (375 to 450 mm) i/d	Per Kg.	9.85	108.40	Per Kg	9.85	108.40		

	MRS, 1st BI-ANNUA	STRICT ATT	OCK						
Sr.	Description	R	Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) C.I. flanged specials, with flanged and								
	flanged joints:-								
	i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d	PerKg PerKg	9.55 2.35	108.10 100.90		9.55 2.35	108.10 100.90		
	iii) 15" to 18" (375 to 450 mm) i/d	Per Kg	4.20	100.90		4.20	100.90		
	c) C.I. Specials, with tyton joints:-								
	i) 3" to 6" (75 to 150 mm) i/d	Per Kg	13.55	112.10 112.10		13.55	112.10 112.10		
	ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d	PerKg PerKg	13.55 13.55	112.10		13.55 13.55	112.10		
29	Providing and fixing cast iron specials of B.S.S. Class 'B' (such as bend, tee, cross collar, reducer, tail piece, flanged socket, flanged spigot, cap, taper, angle branch,			*)				9.1	Labour rates include the cost of jointing material and labour.
	plug, etc) for Asbestos cement pipe line, with comet joint		/		1				2) The internal dia of the pipe, from
	and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d	Per Kg	12.45	111.00	Per Kg	12.45	111.00		which the branch is taken out, will be considered the internal dia for
	ii) 8" to 18" (200 to 450 mm) i/d	Per Kg	6.40	104.95	Per Kg	6.40	104.95		the purpose of payment.
	iii) 20" to 24" (500 to 600 mm) i/d	Per Kg	5.10	103.65	Per Kg	5.10	103.65		
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class`B', for cast iron pipe line, and Asbestos cement pipe line (including cost of jointing material):-		to S		550			9.1	Labour rates include cost of jointing material and labour.
	a) 3" i/d (75 mm)	Each	881.90	6785.90	Each	881.90	6785.90		
	b) 4" i/d (100 mm) c) 5" i/d (125 mm)	Each Each	959.70 1727.45	7979.70 9887.45	Each Each	959.70 1727.45	7979.70 9887.45		
	d) 6" i/d (150 mm)	Each	1841.60	13241.60	Each	1841.60	13241.60		
	e) 8" i/d (200 mm) f) 10" i/d (250 mm)	Each Each	2150.25 3660.10	23030.25 29820.10		2150.25 3660.10	23030.25 29820.10		
	g) 12" i/d (300 mm)	Each	4112.95	38492.95		4112.95	38492.95		
	h) 16" i/d (400 mm)	Each	5455.15	59455.15	Each	5455.15	59455.15		
	i) 18" i/d (450 mm)	Each	6278.55	120278.55	Each	6278.55	120278.55		
31	Providing and fixing, sluice valve of B.S.S. quality and weight, for Asbestos cement pipe line, with comet joint and rubber ring, complete (including cost of jointing materials):-							9.1	Labour rates include cost of jointing material and labour.
	a) 3" i/d (75 mm)	Each	452.95	5492.95		452.95	5492.95		
	b) 4" i/d (100 mm)	Each	546.85	6306.85	Each	546.85	6306.85		
	c) 6" i/d (150 mm) d) 8" i/d (200 mm)	Each Each	678.05 1092.10	10638.05 19092.10		678.05 1092.10	10638.05 19092.10		
	e) 10" i/d (250 mm)	Each	1395.45	24075.45	Each	1395.45	24075.45		
	f) 12" i/d (300 mm)	Each	1665.30	29865.30		1665.30	29865.30		
	g) 16" i/d (400 mm) h) 18" i/d (450 mm)	Each Each	1962.45 2308.80	57162.45 101908.80		1962.45 2308.80	57162.45 101908.80		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2½" (65 mm) dia (including cost of jointing	Each	60.65	4740.65	Each	60.65	4740.65	9.1	Labour rates include cost of jointing material and labour.
	material).								2) Connecting pipes and specials,

	MRS, 1st BI-ANNUA	STRICT ATT	OCK						
Sr.	Description	R	ate (British S	System)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				-					
									if used, will be paid extra.
33	Providing and fixing, air valve 2½ (65mm) dia of B.S.S. quality and weight (complete with jointing material).							ditto	
	a) single	Each	128.55	3368.55	Each	128.55	3368.55		
	b) double	Each	128.55	7628.55	Each	128.55	7628.55		
34	Providing and fitting C.I. flanges on pipes, including turning, threading, facing and fitting, etc. complete in all respects:-							ditto	
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	37.90	114.90	Per Kg	37.90	114.90		
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	23.80	100.80	Per Kg	23.80	100.80		
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	20.25	97.25	Per Kg	20.25	97.25		
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:	Per Inch	F		Per cm i/d				
	a) 3" to 6" (75 to 150 mm) i/d b) 8" to 12" (200 to 300 mm) i/d c) 15" to 18" (375 to 450 mm) i/d	i/d of pipe ditto ditto		60.35 76.00 69.75			24.15 30.40 27.90		
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I. pipe of B.S.S. 1387-1967 complete in all respects, including specials and valves:-	Fi	nancı	: Depai	tmen	Ť			Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) G.I. flanged joints (Heavy Quality)								
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	18.95 18.95 20.10 20.20 23.60 26.95 26.95	329.45 456.95 544.85 715.80 1041.95 1254.10 1525.35	Per Metre Per Metre Per Metre Per Metre	62.10 62.10 65.90 66.20 77.35 88.35 88.50	1080.65 1498.70 1787.15 2347.85 3417.55 4113.50 5003.10		
	ii) C.I. flanged joints (Medium Quality)								
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	21.75 20.35 22.80 22.85 26.50 30.10 30.30	357.55 456.75 582.30 832.40 1120.25	Per Metre Per Metre	71.25 66.80 74.85 75.00 86.95 98.75 99.30	864.75 1172.75 1498.15 1909.95 2730.30 3674.45 4319.75		

	MRS, 1st BI-ANNUA	STRICT ATTO	OCK						
Sr.	Description	R	ate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
37	Providing and installing P.V.C. bends, of B.S.S.								
	i) Class `B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm)	Each Each Each Each	99.25 112.05 140.05 144.20	225.25 382.05 668.05 913.40		99.25 112.05 140.05 144.20	225.25 382.05 668.05 913.40		
	ii) Class `D' working pressure:- a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each	67.65 71.95 76.90 99.25 112.05 140.05 144.20	101.25 107.95 148.90 286.45 547.65 1136.05 1560.20	Each Each Each Each Each Each	67.65 71.95 76.90 99.25 112.05 140.05 144.20	101.25 107.95 148.90 286.45 547.65 1136.05 1560.20		
38	Providing and installing P.V.C. tees, of B.S.S.  i) Class `B' working pressure:-  a) 3" i/d (80 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm)	Each Each Each Each	148.85 170.00 207.30 216.30	628.85 1106.00 2079.30 2172.30	Each Each Each Each	148.85 170.00 207.30 216.30	628.85 1106.00 2079.30 2172.30		
	ii) Class`D' working pressure:- a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each	103.00 108.25 114.90 148.85 170.00 207.30 216.30	235.00 267.85 324.90 610.85 1106.00 2067.30 2136.30	Each Each Each Each Each Each Each	103.00 108.25 114.90 148.85 170.00 207.30 216.30	235.00 267.85 324.90 610.85 1106.00 2067.30 2136.30		
39	Providing and installing P.V.C. sockets, B.S.S.  i) Class `B' working pressure:-								
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Each Each Each Each Each Each Each	67.95 80.75 100.95 105.05 151.05 175.80 203.85 227.40	151.95 230.75 310.95 393.05 799.05 1915.80 4283.85 3467.40	Each Each Each Each Each	67.95 80.75 100.95 105.05 151.05 175.80 203.85 227.40	151.95 230.75 310.95 393.05 799.05 1915.80 4283.85 3467.40		

	MRS, 1st BI-ANNUA	L-2019 (1	st JANUA	RY-2019 to 3	0th JUNE	-2019) DI	STRICT ATTO	OCK	
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) Class`D' working pressure:- a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each	41.55 45.85 50.80 67.95 80.75 100.95 105.05	64.35 77.05 101.20 222.75 366.35 628.95 1029.05	Each Each Each Each Each	41.55 45.85 50.80 67.95 80.75 100.95 105.05	64.35 77.05 101.20 222.75 366.35 628.95 1029.05		
40	Providing and installing P.V.C. Tapered core, B.S.S.  i) Class `B' working pressure:-  a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	99.25 112.05	141.25 166.05		99.25 112.05	141.25 166.05		
	c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Each Each Each Each Each Each	140.05 144.20 203.25 227.95 266.50 290.05	208.45 225.80 338.85 401.95 480.10 557.65	Each Each Each Each	140.05 144.20 203.25 227.95 266.50 290.05	208.45 225.80 338.85 401.95 480.10 557.65		
	ii) Class`D' working pressure:- a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm)	Each Each Each	67.65 71.95 76.90	88.05 99.55 111.70	2	67.65 71.95 76.90	88.05 99.55 111.70		
41	Making connection for new watersupply lines with the running main, including excavation of trench and refilling, complete, but excluding cost of pipe and specials, etc.	97	nanci	: Depai	inen				The rate includes the component of bailing out water from the trench and cutting of existing pipe line.
	Diameter of running main:  i) upto 6" i/d (150 mm)  ii) upto 8" i/d (200 mm)  iii) upto 10" i/d (250 mm)  iv) upto 12" i/d (300 mm)  v) upto 16" i/d (400 mm)  vi) upto 20" i/d (500 mm)  vii) upto 24" i/d (600 mm)	Per Connection ditto ction ditto ditto ditto ditto ditto ditto	1739.45 2196.40 3098.05 4240.50 5199.25 6741.55 8100.20		Per Connection ditto ction ditto ditto ditto ditto ditto	1739.45 2196.40 3098.05 4240.50 5199.25 6741.55 8100.20			
42	Providing, laying, cutting, jointing, testing and disinfecting High Density Polyethylene Pipe ( <b>HDPE-100</b> ) working presure pipe in trenches. complete in all respects:-								
а)	PN-8 (SDR-21) i) 3" (90mm) ii) 4" (110mm) iii) 5" (125mm) iv) 6" (160mm) v) 8" (200mm)	P.Rft P.Rft P.Rft P.Rft P.Rft	5.35 9.05 9.95 10.85 13.10	139.10 190.65 241.90 393.30 609.40		17.50 29.60 32.60 35.55 43.05	456.30 625.50 793.65 1,290.45 1,999.45		

Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	vi) 10" (250mm)	P.Rft	33.90	941.30		111.25	3,088.35		
	vii) 12" (315mm)	P.Rft	39.95	1,528.40		131.10	5,014.70		
	viii) 14" (355mm)	P.Rft	44.25	1,934.50		145.15	6,347.05		
b)	PN-10 (SDR-17)								
,	i) 3" (90mm)	P.Rft	5.35	155.00		17.50	508.55		
	ii) 4" (110mm)	P.Rft	9.80	231.90		32.20	760.90		
	iii) 5" (125mm)	P.Rft	10.90	294.35		35.70	965.70		
	iv) 6" (160mm)	P.Rft	11.90	477.75		39.10	1,567.55		
	v) 8" (200mm)	P.Rft	14.65	744.55		48.00	2,442.80		
	vi) 10" (250mm)	P.Rft	36.45	1,171.90		119.65	3,845.00		
	vii) 12" (315mm)	P.Rft	43.70	1,872.90		143.45	6,145.00		
	viii) 14" (355mm)	P.Rft	48.95	2,376.75		160.60	7,798.05		
c)	PN-12.5 (SDR-13.6)			* )	\				
	3" (90mm)	P.Rft	5.35	185.60	1	17.50	608.95		
	ii) 4" (110mm)	P.Rft	9.80	269.85	1	32.20	885.40		
	iii) 5" (125mm)	P.Rft	10.90	356.75	-111:	35.70	1,170.50		
	iv) 6" (160mm)	P.Rft	11.90	580.60		39.10	1,904.90		
	v) 8" (200mm)	P.Rft	14.65	901.20		48.00	2,956.85		
	vi) 10" (250mm)	P.Rft	36.45	1,425.25	J 188	119.65	4,676.30		
	vii) 12" (315mm)	P.Rft	43.70	2,275.60		143.40	7,466.25		
	viii) 14" (355mm)	P.Rft	48.95	2,878.55		160.55	9,444.60		
		70	AND STATE		1500				
d)	PN-16 (SDR-11)	D D(:	All and a second	7		40.00	<b>-</b>		
	i) 3" (90mm)	P.Rft	5.75	225.20		18.90	738.90		
	ii) 4" (110mm)	P.Rft	10.15	335.05	tmen	33.25	1,099.25		
	iii) 5" (125mm)	P.Rft	11.30	431.85	S-224 E-22	37.05	1,416.85		
	iv) 6" (160mm)	P.Rft P.Rft	12.45	702.25		40.75	2,304.15		
	v) 8" (200mm)	P.Rft P.Rft	15.45 39.55	1,091.75 1,719.65		50.75 129.75	3,582.05		
	vi) 10" (250mm) vii) 12" (315mm)	P.RIT P.Rft	39.55 48.40	2,740.50		158.80	5,642.15 8,991.65		
	viii) 12" (315mm) viii) 14" (355mm)	P.RIT P.Rft	48.40 63.05	2,740.50 3,480.20		206.80	11,418.50		
	viii) 14 (333Hiiii)	r.nii	03.05	3,400.20		200.00	11,410.50		

## 24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

Description	F	Rate (British S	ystem)	Rat	e (Metric Sys	tem)	Spec.	Remarks
	Unit	Labour	Composite	Unit	Labour	Composite	No.	
Supply and erection of G.I. pipes for wiring purposes, including								
pull boxes, inspection boxes, bends, tees, etc. complete with								
all specials.								
a) on surface, including clamps, etc.							38.4	
i) 15 mm i/d	Per Rft.	21.10	83.05	Per Metre	69.15	272.35		
ii) 20 mm i/d	Per Rft.	21.10	103.60	Per Metre	69.15	339.85		
iii) 25 mm i/d	Per Rft.	21.10	136.20	Per Metre	69.15	446.70		
iv) 32 mm i/d	Per Rft.	26.35	175.35	Per Metre	86.45	575.20		
v) 40 mm i/d	Per Rft.	26.35	213.95	Per Metre	86.45	701.80		
vi) 50 mm i/d	Per Rft.	31.40	265.95	Per Metre	102.95	872.30		
vii) 80 mm i/d	Per Rft.	39.95	419.35	Per Metre	131.00	1,375.45		
	K. 1.52	THE PER	J-15/					
b) recessed in walls, including hooks, cutting jharries and	-Cal			53			20.0	
repairing surface:			2 72 -				38.3	
i) 15 mm i/d	Per Rft.	31.65	90.80	Per Metre	103.75	297.90		
ii) 20 mm i/d	Per Rft.	31.65	112.80	Per Metre	103.75	370.00		
iii) 25 mm i/d	Per Rft.	32.95	147.25	Per Metre	108.10	482.90		
iv) 32 mm i/d	Per Rft.	32.95	181.30		108.10	594.60		
v) 40 mm i/d	Per Rft.	35.95	222.20	Per Metre	117.90	728.80		
vi) 50 mm i/d	Per Rft.	49.45	283.30	Per Metre	162.10	929.15		
vii) 80 mm i/d	Per Rft.	79.10	458.65	Per Metre	259.40	1,504.35		
Supply and erection of M.S. conduit pipes for wiring, including pull boxes, inspection boxes, bends, tees, etc. complete with							38.4 & 38.6	
all specials.								
a) on surface, including clamps, etc.								
i) 16 mm i/d	Per Rft.	14.65	35.80	Per Metre	48.05	117.35		
ii) 20 mm i/d	Per Rft.	14.65	41.35	Per Metre	48.05	135.55		
iii) 25 mm i/d	Per Rft.	14.65	46.75	Per Metre	48.05	153.40		
iv) 32 mm i/d	Per Rft.	14.65	51.35	Per Metre	48.05	168.45		
v) 40 mm i/d	Per Rft.	16.50	64.50	Per Metre	54.05	211.60		
vi) 50 mm i/d	Per Rft.	20.30	78.80	Per Metre	66.50	258.50		
b) recessed in walls, including cutting jharries, cost of							38.3 &	
hooks and repairing surface etc.							38.7	
i) 16 mm i/d	Per Rft.	28.25	50.50	Per Metre	92.65	165.60		
ii) 20 mm i/d	Per Rft.	28.25	55.50	Per Metre	92.65	182.00		
iii) 25 mm i/d	Per Rft.	31.65	63.45		103.75	208.15		
iv) 32 mm i/d	Per Rft.	32.95	69.70	Per Metre	108.10	228.55		

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUARY	-2019 to 30t	h JUNE-20	019) DISTR	RICT ATTOC	K	
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) 40 mm i/d	Per Rft.	34.40	81.45	Per Metre	112.75	267.10		
	vi) 50 mm i/d	Per Rft.	35.95	95.15	Per Metre	117.90	312.10		
3	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries,							38.3 & 38.5	
	and repairing surface, etc., complete with all specials.							30.0	
	i) 12 mm i/d	Per Rft.	25.50	36.85	Per Metre	83.65	120.90		
	ii) 20 mm i/d iii) 25 mm i/d	Per Rft. Per Rft.	26.35 29.30	41.45 47.85	Per Metre Per Metre	86.45 96.05	135.90 156.85		
	iv) 32 mm i/d	Per Rft.	31.65	58.95	Per Metre	103.75	193.35		
	v) 40 mm i/d	Per Rft.	32.95	71.05	Per Metre	108.10	233.05		
	vi) 50 mm i/d	Per Rft.	34.40	84.25	Per Metre	112.75	276.25		
4	Supply and erection of PVC pipe for wiring on surface	11/	and the same of th		411				
	including clamps inspection boxes, pull boxes, bends, tees,	1 53	The second secon	The same of the sa	ラ器:				
	repairing surface, etc., complete with all specials:-	188	The second of th	And the second s	7 %				
	i) 12 mm i/d	Per Rft.	6.60	18.60	Per Metre	21.60	61.10		
	ii) 20 mm i/d	Per Rft.	6.60	22.25	Per Metre	21.60	72.95		
	iii) 25 mm i/d	Per Rft.	6.60	26.90	Per Metre	21.60	88.30		
	iv) 32 mm i/d	Per Rft.	7.55	37.75	Per Metre	24.70	123.85		
	v) 40 mm i/d vi) 50 mm i/d	Per Rft. Per Rft.	7.55 9.10	50.00 67.05	Per Metre Per Metre	24.70 29.80	164.05 219.85		
	VI) 30 Hilling	i Gitat.	ance (	Depuis	1 G Maic	29.00	219.00		
5	Supply and erection of G.I. flexible pipe for wiring, including welding of sockets, nipples and check nuts, etc. complete:-							38.4	
	i) 12 mm i/d	Per Rft.	17.25	62.35	Per Metre	56.60	204.60		
	ii) 20 mm i/d	Per Rft.	18.40	79.35	Per Metre	60.35	260.25		
	iii) 25 mm i/d	Per Rft.	19.05	104.50	Per Metre	62.45	342.70		
	iv) 32 mm i/d	Per Rft.	23.00	127.65	Per Metre	75.45	418.75		
	v) 40 mm i/d	Per Rft.	25.10	144.05	Per Metre	82.30	472.55		
	vi) 50 mm i/d vii) 80 mm i/d	Per Rft. Per Rft.	27.60 36.80	186.15 354.50	Per Metre Per Metre	90.55 120.70	610.55 1,162.80		
6	Supply and erection PVC pipe for recessed wiring (main and							38.2 &	
	sub-main) purpose, including bends, specials, etc. in floor,							38.3	
	wall or trenches:-								
	i) 50 mm i/d	Per Rft.	34.40	85.90	Per Metre	112.75	281.80		
	ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft.	39.55 39.55	106.90 136.45	Per Metre Per Metre	129.70 129.70	350.60 447.65		
	111) 100 Hill 11/4	rentii.	39.33	130.43	ra welle	129.70	CO. 1 <del>++</del>		
7	Supply and erection of PVC pipe for surface wiring (main and								
	sub-main) including clamps, inspection boxes, pull boxes								
	bends etc., complete with all specials:-								
	i) 50 mm i/d	Per Rft.	9.10	61.80	Per Metre	29.80	202.65		

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description		Rate (British System)			Rate (Metric System)			Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 80 mm i/d	Per Rft.	13.20	97.20	Per Metre	43.25	318.80		
	iii) 100 mm i/d	Per Rft.	15.05	125.25	Per Metre	49.40	410.75		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	2.65	4.95	Per Metre	8.65	16.20	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	2.65	14.20	Per Metre	8.65	46.55	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):-  a) 250/440 volts, PVC insulated:							38.1	
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052") viii) 19/1.63 mm (19/0.064")	Per Rft.	5.25 5.25 5.25 5.85 6.60 8.10 18.85 21.95	11.70 12.10 15.95 22.95 32.25 75.70 124.35 169.00	Per Metre	17.30 17.30 17.30 19.20 21.60 26.60 61.75 72.05	38.35 39.75 52.40 75.35 105.85 248.35 407.85 554.35		
	b) 250/440 volts, PVC insulated cotton braided and compounded cables:-								
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft.	5.85 5.85 5.85 6.20 6.95 8.00	12.30 12.70 16.55 23.30 32.60 75.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	19.20 19.20 19.20 20.35 22.75 26.20	40.25 41.65 54.30 76.50 106.95 247.95		
11	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):-								
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft.	5.25 5.25 5.25 5.85 6.60 8.10	11.25 14.25 18.55 25.95 36.10 69.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	17.30 17.30 17.30 19.20 21.60 26.60	36.95 46.75 60.80 85.20 118.45 227.30		

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUARY	-2019 to 30t	h JUNE-20	019) DISTF	RICT ATTOC	K	
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		1	Luboui	Composito	Offic	Labour	Odripodic		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-							38.1 to 38.7	
	i) 7/1.63 mm (7/0.064") ii) 19/1.32 mm (19/0.052") iii) 19/1.63 mm (19/0.064") iv) 19/2.11 mm (19/0.083") v) 37//1.83 mm (37/0.072") vi) 37/2.11 mm (37/0.083") vii) 37/2.62 mm (37/0.103")	Per Rft.	8.00 8.80 9.60 10.55 18.20 21.95 31.00	77.90 129.55 174.45 330.50 460.15 577.10 884.45	Per Metre Per Metre Per Metre	26.20 28.80 31.45 34.60 59.65 72.05 101.70	255.55 424.95 572.15 1,084.00 1,509.35 1,892.90 2,901.05		
13	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):-	8						ditto	
	a) PVC insulated, PVC sheathed twin core, 250/440 volts.  i) 3/0.74 mm (3/0.029")  ii) 3/0.91 mm (3/0.036")  iii) 7/0.74 mm (7/0.029")  iv) 7/0.91 mm (7/0.036")  v) 7/1.12 mm (7/0.044")  vi) 7/1.63 mm (7/0.064")	Per Rft.	5.85 5.85 5.85 6.20 6.95 8.00	19.10 25.95 34.55 49.40 69.40 135.95	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	19.20 19.20 19.20 20.35 22.75 26.20	62.70 85.20 113.25 162.10 227.65 445.95		
	b) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:-			8					
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft.	6.20 6.20 6.20 6.95 7.30 8.35	27.60 38.30 51.15 73.90 104.35 208.80	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	20.35 20.35 20.35 22.75 24.00 27.45	90.50 125.60 167.70 242.35 342.30 684.90		
	c) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:-								
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052")	Per Rft.	6.60 6.60 6.95 6.95 7.30 8.35 11.70	34.85 47.65 64.55 94.25 134.45 271.10 504.55	Per Metre	21.60 21.60 22.75 22.75 24.00 27.45 38.45	114.25 156.35 211.80 309.10 441.00 889.20 1,654.95		
	d) PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG.								Cost of trenches where necessary is included in the rates.

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK								
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 19/1.32 mm (19/0.052")	Per Rft.	11.70	562.20	Per Metre	38.45	1,843.95		
	ii) 19/1.63 mm (19/0.064")	Per Rft.	12.55	750.30	Per Metre	41.15	2,461.05		
	iii) 19/1.83 mm (19/0.072")	Per Rft.	13.20	1,014.95	Per Metre	43.25	3,329.05		
	iv) 19/2.11 mm (19/0.083")	Per Rft.	14.25	1,419.00	Per Metre	46.75	4,654.40		
	v) 37//1.83 mm (37/0.072")	Per Rft.	14.65	1,931.35	Per Metre	48.05	6,334.75		
	vi) 37/2.11 mm (37/0.083")	Per Rft.	17.55	2,441.10	Per Metre	57.65	8,006.75		
	vii) 37/2.36 mm (37/0.093")	Per Rft.	21.10	2,975.15	Per Metre	69.15	9,758.45		
	viii) 37/2.62 mm (37/0.103")	Per Rft.	26.35	3,702.95	Per Metre	86.45	12,145.60		
14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")			and the company of th				38.1	
	deep, with 4.75 mm thick (3/16") bakelite sheet top, for							to	
	recessed wiring, including making holes for regulators, switches, plugs, etc.		/ "					38.7	
	i) 10 x 10 cm (4"x4")	Each	86.45	157.25	Each	86.45	157.25		
	ii) 17.5 x 10 cm (7"x4")	Each	108.10	221.80	Each	108.10	221.80		
	iii) 22.5 x 10 cm (9"x4")	Each	144.10	283.90	Each	144.10	283.90		
	iv) 20 x 25 cm (8"x10")	Each	172.90	419.45	Each	172.90	419.45		
	v) 25 x 30 cm (10"x12")	Each	216.15	558.70	Each	216.15	558.70		
	vi) 30 x 35 cm (12"x14")	Each	288.20	732.90	Each	288.20	732.90		
15	Supply and erection of round block of Sahl wood, 10x4 cm (4"x1½") thick.	Each	24.70	38.00	Each	24.70	38.00	38.1	
16	Supply and erection of teak wood board, 4.5 cm (1¾") thick.	Fin	ance :	Depart	ment			38.1	
	i) 17.5 x 10 cm (7"x4")	Each	34.60	91.65	Each	34.60	91.65		
	ii) 22.5 x 10 cm (9"x4")	Each	34.60	104.00	Each	34.60	104.00		
	iii) 20 x 25 cm (8"x10")	Each	38.45	121.45	Each	38.45	121.45		
	iv) 25 x 30 cm (10"x12")	Each	43.25	163.55	Each	43.25	163.55		
	v) 30 x 35 cm (12"x14")	Each	49.40	220.40	Each	49.40	220.40		
17	Supply and erection of Sahl wood board, 4.5 cm (1¾") thick.								
	i) 17.5 x 10 cm (7"x4")	Each	34.60	71.25	Each	34.60	71.25		
	ii) 22.5 x 10 cm (9"x4")	Each	34.60	89.80	Each	34.60	89.80		
	iii) 20 x 25 cm (8"x10")	Each	38.45	105.40	Each	38.45	105.40		
	iv) 25 x 30 cm (10"x12")	Each	43.25	126.25	Each	43.25	126.25		
	v) 30 x 35 cm (12"x14")	Each	49.40	149.10	Each	49.40	149.10		
18	Supply and erection of iron/aluminum clad, 500 volts main							38.1	When the base frame is already
	switches with kitkat fuses, on angle iron board with 3 mm								installed, the labour and composite
	(1/8") thick M.S. sheet covering, including bonding to earth								rates will be reduced as follows:- For
	with necessary flexible pipe and thimbles, etc.								15 to 35 Amps. by Rs. 21.20 and Rs.
	a) double pole:								145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.
	i) 15/20 Amp.	Each	576.40	1,631.00	Each	576.40	1,631.00		by No. 30.00 and No. 330.00.
1	ii) 30/35 Amp.	Each	576.40	1,921.50	Each	576.40	1,921.50		
	iii) 60/65 Amp.	Each	864.60	2,529.20	Each	864.60	2,529.20		

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	iv) 100 Amp.	Each	864.60	3,085.40	Each	864.60	3,085.40				
	la distant										
	b) triple pole:	Fash	004.00	0.040.75	□ a a la	004.00	0.040.75				
	i) 15/20 Amp. ii) 30/35 Amp.	Each Each	864.60 576.40	2,246.75 2,391.15	Each Each	864.60 576.40	2,246.75 2,391.15				
	11) 30/35 /AIIIp.	Laci	370.40	2,001.10	Lacii	370.40	2,001.10				
	c) triple pole with neutral link:										
	i) 30/35 Amp.	Each	576.40	2,564.20	Each	576.40	2,564.20				
	ii) 60/65 Amp.	Each	864.60	3,274.45	Each	864.60	3,274.45				
	iii) 100 Amp.	Each	1,132.65	4,055.40	Each	1,132.65	4,055.40				
19	Supply and erection of iron/aluminum clad, 500 volts main		/ "						When the base frame is already		
	switches with triple pole and neutral link and HRC fuses, on	/	****		\			38.1	installed, the labour & composite		
	angle iron board with 3 mm (1/8") thick M.S. sheet covering,	1.1.6	The state of the s	-					rates will be reduced as follows:-		
	including bonding to earth with necessary flexible pipe and	188	And the Party of t	The same of the sa	그 %.						
	thimbles.	188 /	The second secon		7 83				i) For 60/65 Amp. by Rs. 21.20 and		
	60/65 Amp	Each	864.60	3,317.45	Each	864.60	3,317.45		Rs. 145.50. ii) For 100 to 300 Amp. by Rs. 21.20		
	100 Amp	Each	1,132.65	4,623.70	Each	1,132.65	3,317.43 4,623.70		and Rs. 350.80		
	150 Amp	Each	1,132.65	6,188.50	Each	1,132.65	6,188.50		iii) For 400 to 500 Amp. by Rs. 42.20		
	200 Amp	Each	2,593.80	10,208.20	Each	2,593.80	10,208.20		and Rs. 526.20		
	300 Amp	Each	2,593.80	11,617.20	Each	2,593.80	11,617.20				
	400 Amp	Each	3,674.55	15,702.05	Each	3,674.55	15,702.05				
	500 Amp	Each	3,890.70	19,731.20	Each	3,890.70	19,731.20				
20	Supply and erection of iron/aluminum clad, branch							ditto	When the base frame is already		
	distribution board, 250 volt, on angle iron frame of suitable								installed the labour and composite		
	size with 3 mm (1/8") M.S. sheet covering:								rates will be reduced by Rs. 19.50 &		
									Rs. 152.20 respectively.		
	i) 2 way, 15 Amp per way	Each	288.20	695.80	Each	288.20	695.80				
	ii) 3 way, 15 Amp per way	Each	288.20	695.80	Each	288.20	695.80				
	iii) 4 way, 15 Amp per way iv) 5 way, 15 Amp per way	Each Each	288.20 288.20	769.95 831.75	Each Each	288.20 288.20	769.95 831.75				
	v) 6 way, 15 Amp per way	Each	288.20	875.00	Each	288.20	875.00				
	vi) 7 way, 15 Amp per way	Each	288.20	930.65	Each	288.20	930.65				
	vii) 8 way, 15 Amp per way	Each	288.20	980.05	Each	288.20	980.05				
	viii) 9 way, 15 Amp per way	Each	288.20	1,035.70	Each	288.20	1,035.70				
	ix) 10 way, 15 Amp per way	Each	288.20	1,116.05	Each	288.20	1,116.05				
	x) 11 way, 15 Amp per way	Each	288.20	1,177.85	Each	288.20	1,177.85				
	xi) 12 way, 15 Amp per way	Each	288.20	1,233.45	Each	288.20	1,233.45				
	xii) 2 way, 30 Amp per way xiii) 3 way, 30 Amp per way	Each Each	432.30 432.30	839.90 846.05	Each Each	432.30 432.30	839.90 846.05				
	xiii) 3 way, 30 Amp per way   xiv) 4 way, 30 Amp per way	Each	432.30	907.85	Each	432.30	907.85				
	(xv) 5 way, 30 Amp per way	Each	432.30	975.85	Each	432.30	975.85				
	xvi) 6 way, 30 Amp per way	Each	432.30	1,019.10	Each	432.30	1,019.10				
	xvii) 7 way, 30 Amp per way	Each	432.30	1,087.10	Each	432.30	1,087.10				
	xviii 8 way, 30 Amp per way	Each	432.30	1,142.70	Each	432.30	1,142.70				
	xix) 9 way, 30 Amp per way	Each	432.30	1,192.15	Each	432.30	1,192.15				

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK											
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		400.00	4.070.07		100.00	4.070.07					
	xx) 10 way, 30 Amp per way	Each	432.30	1,278.65	Each	432.30	1,278.65					
21	Supply and erection of bus bars, for 500 volts 3 phase A.C. supply with four copper bars, including glazed porcelain bridges, on angle iron board, fixed with rag bolts and M.S. sheet box 1.5 mm thick, etc. complete:-							38.1	When the base frame is already installed the labour and composite rates will be reduced by Rs. 21.20 and Rs. 145.50 respectively.			
	i) 60 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm)	Each	1,029.25	3,138.10	Each	1,029.25	3,138.10					
	ii) 100 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm)	Each	1,029.25	3,138.10	Each	1,029.25	3,138.10					
	iii) 200 Amp with 4 copper bars size 2"x1/8" (50x 3 mm)	Each	1,626.25	3,833.95	Each	1,626.25	3,833.95					
	iv) 300 Amp with 4 copper bars size 2"x3/16" (50x 5 mm)	Each	1,945.35	4,153.05	Each	1,945.35	4,153.05					
	v) 500 Amp with 4 copper size 2"x1/4" (50x 6 mm)	Each	1,245.40	4,061.30	Each	1,245.40	4,061.30					
22	<ul> <li>Supply and erection of plain pendent lamp holder, complete with bakelite lamp holder and flexible twin wire 23/0.0076" upto 2 metre length (without bulb and shade).</li> </ul>	Each	18.00	110.15	Each	18.00	110.15	38.1				
	ii) Extra for additional length of flexible wire, beyond 2 metres.	Per Rft.	iance (	1.65	Per Metre		5.45					
23	Supply and erection of counter weight pedent with porcelain counter weight, and fitting on bakelite lamp holder, with flexible twin wire 23/0.0076" complete (without bulb and shade).	Each	36.05	245.30	Each	36.05	245.30	38.1				
24	Supply and erection of stiff pedent with brass/metal pipe 6.3 cm (2.5") long, and 15 mm ( $\frac{1}{2}$ ") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm (3/0.029").	Each	54.20	496.40	Each	54.20	496.40	ditto				
25	Supply and erection of 22.5 cm (9") long swan neck plain brass/steel brass oxidised bracket lamp holder, complete.	Each	56.10	119.75	Each	56.10	119.75	ditto				
26	Supply and erection of wall type/pole type bracket, with double cover water tight reflector, flexible wire and brass bolder.	Each	77.45	508.75	Each	77.45	508.75	ditto				
27	Supply and erection of bakelite button holder shade, large size.	Each	12.45	51.85	Each	12.45	51.85	ditto				
28	Supply and erection of call bell 220/250 volts, fixed on teak wood board 17.5x10 cm (7"x4").	Each	54.20	239.55	Each	54.20	239.55	38.1				
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	10.80	213.30	Each	10.80	213.30	38.1				

MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
30	Supply and erection of ceiling rose, bakelite.	Each	18.00	38.05	Each	18.00	38.05	ditto	
30	Supply and electron of centring rose, bakente.	Each	16.00	36.05	Each	16.00	36.05	artto	
31	Supply and erection of switches 5 Amp.								
	i) open type	Each	17.30	34.85	Each	17.30	34.85	ditto	
	ii) piano type	Each	17.30	34.85	Each	17.30	34.85		
	iii) ring type, recessed	Each	17.30	29.65	Each	17.30	29.65		
	iv) plate type, recessed	Each	17.30	52.15	Each	17.30	52.15		
	v) double control, open type	Each	24.00	53.15	Each	24.00	53.15		
	vi) double control, ring type recessed	Each	24.00	47.00	Each	24.00	47.00		
	vii) double control, piano type	Each	24.00	48.25	Each	24.00	48.25		
32	Supply and erection of switches 10/15 Amp.	,	/ "	)	\			ditto	
		/	-		1				
	i) open type	Each	17.30	44.00	Each	17.30	44.00		
	ii) recessed type	Each	17.30	53.90	Each	17.30	53.90		
		188 1	Secretaria de la companya del la companya de la com		-/ 88/				
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	17.30	81.10	Each	17.30	81.10	ditto	
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	17.30	56.35	Each	17.30	56.35	ditto	
		455			<b>9</b> 3				
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.			2/2				ditto	
			4=00	<b>-</b> 0.00		4= 00	<b>70.00</b>		
	i) open type	Each	17.30	50.20	Each	17.30	50.20		
	ii) recessed type	Each	17.30	87.25	Each	17.30	87.25		
36	Supply and erection of 3 pin switch and plug combined,							ditto	
	recessed type.								
	i) 5 Amp	Each	17.30	70.75	Each	17.30	70.75		
	ii) 10/15 Amp	Each	17.30	96.45	Each	17.30	96.45		
	III) 10/15 ATIP	Each	17.30	90.43	Each	17.30	90.43		
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe,	Each	17.30	149.05	Each	17.30	149.05	ditto	
3,	open type.	Lacii	17.50	143.03	Laui	17.50	1-3.03	uitto	
	Гораттурс.								
38	Supply and erection of cut out, bakelite.							ditto	
	i) open type	Each	9.60	36.35	Each	9.60	36.35		
	ii) recessed type	Each	9.60	42.50	Each	9.60	42.50		
	, 71	]		3		5.55			
39	Supply and erection of button holder.							38.1	
	i) bakelite large size	Each	10.80	30.10	Each	10.80	30.10		
	1,	Each	10.80	42.45	Each	10.80	42.45		
1	ii) brass	⊏aUII	10.60	42.40	⊏dU∏	10.60	42.40		
40	Supply and erection of brass bracket with holder.	Each	14.40	46.05	Each	14.40	46.05	ditto	
11	Supply and greation of hall push an an //secessed to an		0.00	20.45	Faal-	0.00	20.45	جا: 44 <i>ح</i>	
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	9.60	30.15	Each	9.60	30.15	ditto	
	(without healpie wife).								
	<u>I</u>	<u> </u>	<u> </u>						

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK									
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
42	Supply and erection of kitkat, 500 volt:							ditto		
	i) 15/20 Amp	Each	17.60	50.05	Each	17.60	50.05			
	ii) 30/35 Amp	Each	19.20	51.65	Each	19.20	51.65			
	iii) 60/65 Amp	Each	29.30	75.65	Each	29.30	75.65			
	iv) 100 Amp	Each	32.95	122.60	Each	32.95	122.60			
	v) 200 Amp	Each	37.70	164.35	Each	37.70	164.35			
	vi) 300 Amp	Each	37.70	325.05	Each	37.70	325.05			
	vii) 400 Amp	Each	49.80	405.15	Each	49.80	405.15			
	viii) 500 Amp	Each	49.80	581.30	Each	49.80	581.30			
43	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling	/	×		\			38.1		
	rose, etc., complete.	16	and the second second		1					
	i) double rod (80 watts) with two chokes and 2 starters.	Per set	311.35	1,269.55	Per set	311.35	1,269.55			
	ii) single rod (40 watts) with one choke and one starter.	ditto	249.10	688.15	ditto	249.10	688.15			
	iii) round tube, 32 watt, with one choke and one starter, without cover.	Each	249.10	746.25	Each	249.10	746.25			
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	207.55	828.35	ditto	207.55	828.35			
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking arrangement, including painting:-	2.02	sers-Us 1	2710 37102 1	234.0026.00			ditto		
	i) 60x35x15 cm (24"x14"x6")	Each	649.75	2,624.05	Each	649.75	2,624.05			
	ii) 95x40x20 cm (38"x16"x8")	Each	938.35	3,318.95	Each	938.35	3,318.95			
	iii) 105x52.5x22.5 cm (42"x21"x9")	Each	1,427.00	4,608.35	Each	1,427.00	4,608.35			
	iv) 135x70x27.5 cm (54"x28"x11")	Each	1,569.65	6,566.45	Each	1,569.65	6,566.45			
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate 25x6 mm (1" $x\frac{1}{4}$ "), with bolts and nuts for hanging ceiling fans.	Each	41.50	156.45	Each	41.50	156.45	38.1 & 38.10		
46	Supply and erection of girder strut, of M.S. tee section $40x40x6$ mm $(1\frac{1}{2}"1\frac{1}{2}"x\frac{1}{4}")$ , complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	54.20	1,110.20	Each	54.20	1,110.20	ditto		
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with 75x40x3 mm (3"x1½"x1/8") M.S. steel channel, with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	58.10	1,239.90	Each	58.10	1,239.90	38.1		
48	Supply and erection of roof suspension hook of M.S plate 75x40x12.7mm (3"x1½"x½") with 16 mm (5/8") hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Each	77.45	525.20	Each	77.45	525.20			

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK								
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		O.I.I.C	Luboui	Composito	O I II C	Laboai	Composito		
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	22.15	39.45	Each	22.15	39.45	ditto	
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	696.40	2,775.40	Each	696.40	2,775.40	38.12	
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x¼") section:-								
	i) 0.60 metre (2') long for 2 lines. ii) 1.200 metre (4') long for 4 lines.	Each Each	154.40 180.15	601.05 1,341.90	Each Each	154.40 180.15	601.05 1,341.90		
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.	Per Rft.	10.40	24.30	Per Metre	34.10	79.80	38.14	
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	15.05	37.85	Per Metre	49.40	124.15	ditto	
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line, include shackle insulator for holding insulated wire and straining devices for bearer wire and other accessories etc., complete.	Per Rft.	65.90	334.80	Per Metre	216.15	1,098.15		
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	60.65	327.35	Per Metre	199.00	1,073.80		
56	Supply and erection of lightning arrestor horn type, complete.	Each	325.25	2,550.05	Each	325.25	2,550.05		
57	Supply and erection of shackle insulator, medium size.	Each	40.75	207.60	Each	40.75	207.60	38.12	
58	Supply and erection of pin insulator, green medium size.	Each	40.75	90.20	Each	40.75	90.20	ditto	
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	21.20	1,104.90	Per Kg	21.20	1,104.90	38.1	
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire, pole to pole etc.	Per Kg	21.20	144.90	Per Kg	21.20	144.90	ditto	
61	Wiring overhead line in 2 single core, PVC/weather proof cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.							38.12	

	MRS, 1st BI-ANNUAL-2	019 (1st	JANUARY	-2019 to 30t	h JUNE-20	019) DISTR	RICT ATTO	K	
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric Sys	item)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 3/0.74 mm (3/0.029") ii) 7/0.74 mm (7/0.029") iii) 7/0.91 mm (7/0.036") iv) 7/1.12 mm (7/0.044")	Per Rft. ditto ditto ditto	5.50 5.50 5.50 5.50	13.60 22.00 28.65 37.75	Per Metre ditto ditto ditto	18.05 18.05 18.05 18.05	44.65 72.10 93.90 123.85		
62	Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft.	10.15	23.45	Per Metre	33.25	76.85	38.1	
63	Supply and erection of street light pole bracket 30 mm (11/4") G.I. pipe 2 metre long, complete with 2 No. pole clamp.	Each	271.05	1,311.90	Each	271.05	1,311.90		
64	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):	/	/ ×		\				
	i) G.E.C. design ii) Philips design	Each ditto	542.10 542.10	2,964.65 3,347.80	Each ditto	542.10 542.10	2,964.65 3,347.80		
65	Supply and fitting of mercury vapour lamp, complete with choke set. i) 125 watt lamp ii) 250 watt lamp	Each ditto	207.55 249.10	1,134.55 2,041.30	Each ditto	207.55 249.10	1,134.55 2,041.30		
66	Manufacture and erection of angle iron lattice steel structure pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1½"x1½"x3/16" (30x30x5 mm) angle iron legs and ½"x¾"1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1¾"x1¾"x3/16" (45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x½" (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.	Each	9,114.75	28,647.80	Each	9,114.75	28,647.80	38.13	The composite rate will be reduced or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3½'x3½' (2400x1050x1050 mm), etc. complete in all respects.	Each	8,825.15	43,221.70	Each	8,825.15	43,221.70	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.

	MRS, 1st BI-ANNUAL-2	019 (1st	JANUARY	-2019 to 30t	h JUNE-20	019) DISTF	RICT ATTOC	K	
Sr.	Description	R	Rate (British S	ystem)	Ra	te (Metric Sys	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (½") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	1,193.95	5,172.85	Job	1,193.95	5,172.85		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in 15 mm (½") dia G.I. pipe, best quality:- i) on surface, including clamps, etc. ii) recessed in wall, including hooks, jharries and making good surface.	Per Rft. ditto	12.40 29.10	73.20 91.10	Per Metre ditto	40.65 95.50	240.05 298.80	38.11	
70	Bonding to earth with wire on surface, including cost of wire, clamps, thimbles, etc.	. /						ditto	
	a) G.I. wire: i) 8 SWG ii) 16 SWG	Per Rft. ditto	5.25 5.25	12.20 7.10	Per Metre ditto	17.30 17.30	40.10 23.30		
	b) Copper wire:  i) 16 SWG  ii) 20 SWG	Per Rft. ditto	5.25 5.25	12.60 8.10	Per Metre ditto	17.30 17.30	41.30 26.60		
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	19.85	24.50	Per Metre	65.05	80.35	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	795.95	4,659.15	Each	795.95	4,659.15	ditto	
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.								
	i) tape 40x3 mm (1½"x1/8") ii) tape 50x3 mm (2"x1/8")	Per Rft. ditto	29.10 29.10	270.60 320.95	Per Metre ditto	95.50 95.50	887.60 1,052.70		
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	542.10	2,878.10	Job	542.10	2,878.10		
75	Supply and erection of electric energy meter, including meter testing fee, etc.							38.1	
	a) single phase:								
	i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts	Each ditto	216.15 216.15	2,352.15 2,352.15	Each ditto	216.15 216.15	2,352.15 2,352.15		

	MRS, 1st BI-ANNUAL-2019 (1st JANUARY-2019 to 30th JUNE-2019) DISTRICT ATTOCK										
Sr.	Description	F	Rate (British S	ystem)	Ra	ate (Metric Sys	stem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	b) three phase, 4 wires:										
	i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts	Each ditto ditto	432.30 622.70 622.70	6,187.50 6,377.90 6,377.90	Each ditto ditto	432.30 622.70 622.70	6,187.50 6,377.90 6,377.90				
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.	Fach	410.45	200 50	Fash	440.45	000 50		The credit of out turn of dismantled material has been accounted for in the rate.		
	i) 1200 mm (48") sweep, 275-300 RPM. ii) 1400 mm (56") sweep, 250-275 RPM.	Each ditto	419.45 467.05	990.50 1,138.80	Each ditto	419.45 467.05	990.50 1,138.80				
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.	1							The credit of out turn of dismantled material has been accounted for in the rate.		
	i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM	Each ditto	288.20 288.20	685.70 761.65	Each ditto	288.20 288.20	685.70 761.65				
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	345.85	886.10	Each	345.85	886.10		The credit of out turn of dismantled material has been accounted for in the rate.		
79	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	54.05	115.85	Each	54.05	115.85	38.1			
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	43.25	67.95	Each	43.25	67.95	ditto			
81	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	54.05	177.65	Each	54.05	177.65	ditto			
82	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	108.10	213.20	Each	108.10	213.20		The credit out turn of dismantled material has been accounted for in the rate.		
83	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	207.35	245.50	Each	207.35	245.50				

## 25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUAR	OCK					
Sr.	Description	Ra	ate (British S	System)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Railway Track, etc.								
1	Laying, linking and packing tramway line.	100Lft.	1999.60		Metre	65.60			
2	Dismantling tramway track.	100Lft.	663.10		Metre	21.75			
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	5197.50		Metre	170.50			
4	Linking points and crossings, complete with fastenings.	Each	5022.60		Each	5022.60			
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	553.75		Each Point	553.75			
6	Fixing street lamp posts.	Each	647.40		Each	647.40			
7	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	6077.60	Depart	100 Nos	6077.60			
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	764.35		100 Nos	764.35			
	IRON WORK								
9	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	3201.00	9846.50	100 Kg	6301.20	19382.90		
10	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	Per Cwt	1145.10	7468.45	100 Kg	2254.15	14701.65		
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	361.40		100 Kg	711.40			
12	Fixing corrugated iron sheet, including revitting, etc.	100 Sft.	1301.00		sq.m	140.00			
13	Erecting corrugated iron sheet tanks, upto 20' (6 m) height.	Per Cwt	629.10		100 Kg	1238.40			

	MRS, 1st BI-ANNUAL-	2019 (1st	JANUAR'	Y-2019 to 30t	h JUNE-	2019) DIS	TRICT ATT	OCK	
Sr.	Description	Ra	ate (British S	System)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Erecting rolled steel beams or old rails, in roofs, etc., erection and fixing in position.	Per Cwt	382.55		100 Kg	753.00			
	Erecting rolled steel beams or rails, erection for posts etc. (other than in roofs).	Per Cwt	185.80		100 Kg	365.70			
16	Making bolts and nuts of iron rods.	Per Cwt	2462.15	9611.90	100 Kg	4846.70	18921.10		
17	Cutting rails, rolled steel joists and beams, with hacksaw:-		/ >	()					
	a) upto 6" size (150 mm) b) above 6" size (150 mm)	Per Cut Per Cut	243.95 359.85		Per Cut Per Cut	243.95 359.85			
	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	116.15		Per Cwt Cut	116.15			
19	Bending rolled steel beams or rails.	Per Bend	124.25	376.15	Per Bend	124.25	376.15		
	Drilling holes, in plates upto $\frac{1}{2}$ " (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	48.90	O ana and	Per Hole	48.90			
	Extra for drilling holes in plates over ½" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	27.20	wepui i	Per Hole	27.20			
22	Rivetting 1/8" dia (3 mm).	100 Nos	647.35		100 Nos	647.35			
23	Cutting out Rivets, all sizes.	100 Nos	2070.75		100 Nos	2070.75			
24	Fitting and erection of gutters of sheet iron.	Per Lft.	81.25		Metre	266.55			
25	Cutting and fixing iron bars, for barred windows.	Per bar	46.45		Per bar	46.45			
26	Cutting G.I. sheets.	Each Cut	25.50		Each Cut	25.50			
27	Notching web or foot of rail posts, for housing rail beams.	Per Notch	552.20	720.20	Per Notch	552.20	720.20		
28	Hoop iron netted trellis work fixed with nails.	Per Sft.	32.55		sq.m	349.95			
29	Fixing zinc iron or G.I. sheet on table tops.	Per Sft.	19.15		sq.m	205.85			
	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	201.00	886.20	sq.m	2162.95	9535.30		
	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and ¾" (20 mm) square bars 4" (100 mm) centre to centre, with locking arrangement.	Per Sft.	208.75	1029.70	sq.m	2246.00	11079.40		

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUAR'	Y-2019 to 30t	h JUNE-	2019) DIS	TRICT ATT	OCK	
Sr.	Description	Ra	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
32	Making and fixing grating in opening, including fixing at site with flat iron 2"x3/8" (50x10 mm) and 3/4" (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	80.35	433.70	sq.m	864.35	4666.75		
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed to 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete.	Per Rft.	390.85	970.95	Metre	1282.25	3185.50		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8" punched in M.S. flat 2 ¾ high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	201.40	670.40	Metre	660.75	2199.55		
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	145.45	696.95	Metre	477.20	2286.58		-do-
36	Providing and fixing collapsible gate made of 2"x2"x"½" (50x50x6 mm) tee iron at top and bottom, channel iron verticals ¾"x½"x½"x1/8" (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of ¾"x½"x½"x1/8" (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	293.25	794.50	sq.m	3155.20	8548.75		
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1½"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	64.60	263.40	sq.m	695.25	2834.15		
38	Providing and fixing M.S. angle iron 1½"x1½"x½" (40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.	Per Rft.	30.50	172.40	Metre	100.10	565.70		
39	Providing and fixing stair railing of 2½" (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars	Per Rft.	172.05	832.50	Metre	564.50	2731.30		The composite rate shall be reduced or increased by Rs. 31.90

	MRS, 1st BI-ANNUAL-	2019 (1st	JANUAR'	Y-2019 to 30t	h JUNE-	2019) DIS	STRICT ATTO	оск	
Sr.	Description	Ra	ate (British S	System)	Ra	ate (Metric S	System)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite		
	2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.								for each foot of reduction or addition in the height of the square bars.
	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	28.80	70.75	sq.m	310.10	761.30		
	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1½"x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ¾"x1"x¾"x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the Engineer-in-charge:-	AND							For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	<ul> <li>i) glass pane 2 mm thick</li> <li>ii) glass pane 2.5 mm thick</li> <li>iii) glass pane 3 mm thick</li> <li>iv) glass pane 4 mm thick</li> <li>v) glass pane 5 mm thick</li> <li>b) fixed with wire gauze, 22 SWG</li> </ul>	Per Sft. ditto ditto ditto ditto	73.70 73.70 73.70 73.70 73.70	387.85	ditto ditto ditto	793.20 793.20 793.20 793.20 793.20	4040.40 4067.00 4106.90 4173.40 4306.40		
	<ul> <li>i) glass pane 2 mm thick</li> <li>ii) glass pane 2.5 mm thick</li> <li>iii) glass pane 3 mm thick</li> <li>iv) glass pane 4 mm thick</li> <li>v) glass pane 5 mm thick</li> </ul>	Per Sft. ditto ditto ditto ditto	103.95 103.95 103.95 103.95 103.95	444.20 446.65 450.40 456.55 468.90	ditto ditto ditto	1118.30 1118.30 1118.30 1118.30 1118.30	4779.60 4806.20 4846.10 4912.60 5045.60		
	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1½"x1½" (30x30mm) for leaves including M.S. square bars ½"x½" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG) beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects.  a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass	Per Sft.	65.15	336.20	Sq.m	701.15	3617.65		
	panes ¼" (6 mm) thick. b) For fixed panels without wire gauze.	ditto	63.00	209.95	ditto	677.90	2258.95		
	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8"	Per Sft.	76.05	425.50	Sq.m	818.20	4578.15		

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUAR'	Y-2019 to 30t	h JUNE-	2019) DIS	STRICT ATT	OCK	
Sr.	Description	Ra	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.								
	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ½"x½" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	95.70	494.30	Per Sft.	1029.85	5318.85		
45	Flapping G.I. pipes for bath room drains.	Each	648.45	688.00	Each	648.45	688.00		
46	Supply and fixing iron grating for fire place.	Per Sft.	124.55	229.60	sq.m	1340.05	2470.50		
	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	54.20		Metre	177.80			
	Providing and fixing angle iron railing, using 2½"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x½" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long ¾" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	91.00	977.60	Metre	298.55	3207.35		
	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5 mm), angle iron post 3½ ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" (225x225x300 mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	1962.90	11728.40	Metre	64.40	384.80		
	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects.	100Rft.	3234.70	15018.15	Metre	106.15	492.70		

	MRS, 1st BI-ANNUAL-2	2019 (1st	JANUAR'	Y-2019 to 30t	h JUNE-	·2019) DIS	STRICT ATT	OCK	
Sr.	Description	Ra	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
51	Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s AI-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	105.65	543.30	sq. m	1136.80	5845.90		(1) Increase rate by Rs. 40.00 per Sft or Rs.430.50 per Sq-metre if sections thickness is 2 mm. (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade. (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used.
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of approved manufacturer having frame size of 100 x 20 mm (4"x¾") and leaf frame sections of 50 x 20 mm (2"x¾"), all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Srt	152.65	447.95	sq. m	1642.50	4819.95		<ul> <li>(1) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if section thickness is 1.2 mm.</li> <li>(2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminium shade.</li> <li>(3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per sq-metre if local</li> </ul>
53	Providing and fixing all types of glazed aluminium windows of anodized champagne colour partly fixed and party sliding using deluxe section of approved manufacturer having Frame of size 100mm x 30mm using frame at bottom, at top and side leaf leaf frame sections of 60mm x 23mm at top & bottom and size 45mm x 25mm at center and size 45mm x 25mm at sides, Jali leaf frame size 43mm x 13mm i/c fine quality aluminum jali, 5mm thick imported tinted glass with rubber gasket using approved standard latches, wheel, stopper, brush chennel angle joint and hardware etc. complete in all respect.								glass is used.
	a) 1.6 mm thick b) 2 mm thick	Per Sft Per Sft	103.60 103.60			1114.75 1114.75	7235.55 8165.25		
54	P/F MS box section of 16 SWG, having frames of 2" x 1-1/2", leave frame of T-type box section of 2"x1"x1", with ½"x1/2" box section using, U shaped rubber for fixing 5 mm thick glass panes i/c the cost of fixing of 24 SWG wire guaze on inner side by means of ½"x1/8" MS flat patti, MS grill fitted within the window frame and screws including hinges, brass handles and painting 3 coats. Complete in all respect	Per Sft	66.60	494.00	Sqm	716.35	5315.25		i. If Brass stays will be provided, rate of Rs.20/- P.Sft will be paid. ii. For fixed pannels without guaze, reduce rate of Rs.150/- P.Sft. lii. If box sections of 18SWG used, reduce rate of Rs. 25/- P.Sft.

## 26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, 1st BI-ANNU	JAL-2019	(1st JANUA	ARY-2019 to	30th JUNE	-2019) DIS	STRICT ATTO	OCK	
Sr.	Description		Rate (British S)			ate (Metric Sy		Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	70.50	81.40	Per sq.m	758.65	875.60		The board is to be of cement plaster ½" (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.
2	Fixing handles to iron hammers.	Each	90.05		Each	90.05	-		
3	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete.  Surveying	100Lft.	7,403.90	27,532.10	L.m.	242.90	903.30		Vertical bars in straining and stiffening posts to be 4 No. each by ½" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be ½" (6 mm) dia. at 12" (300 mm) centre to centre.
4	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	43.80	173.60	Each	43.80	173.60		
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	144.10	161.80	100Nos.	144.10	161.80		
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	345.85	549.80	100Nos.	345.85	549.80		
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	81.30	90.20	Per L.M.	266.75	295.95		
8	Placing boundary pillars in position, including digging pits.	Each	54.20	-	Each	54.20	-		
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	238.80	425.35	Each	238.80	425.35		Composite rate does not include cost of iron distance marks.
	Hand Pumps & Pressure Pipes								
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	54.20	-	Per cut	54.20	-		

chapter-26( Misc) Page 161

	MRS, 1st BI-ANNU	JAL-2019	(1st JANUA	ARY-2019 to	30th JUNE	-2019) DIS	STRICT ATTO	OCK	
Sr.	Description	I	Rate (British S)	/stem)	Ra	ate (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	98.6	0	Per cut	98.6	0		
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	68.60	-	Each End	68.60	-		
13	Assembling 1½" (40 mm) dia pressure pipe.	100Lft.	250.90	-	Per Metre	8.25	-		
14	Boring and fixing 1½" (40 mm) dia pressure pipe:								
	a) in ordinary soil b) in clay c) in shingle	Per Lft. Per Lft. Per Lft.	88.25 173.95 259.63	(*)	Per Metre Per Metre Per Metre	289.55 570.70 851.80	- - -		
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	39.10	_	Per Metre	128.30	-		
16	Fixing hand pump (Machine only)	Each	172.90	_	Each	172.90	-		
	Rest House Furniture & Fuel, etc.			16 . 6	ヲ源	Ç			
17	Washing Niwar of bed.	Per bed	571.25	606.50	Per bed	571.25	606.50		
18	Washing Durries.	100Sft.	761.65	845.65	sq.m	82.00	91.05		
19	Recaning chairs:	- 5	Financ	е Дера	rtmen	Ĺ			
	<ul> <li>i) office chairs, single caning seat only.</li> <li>ii) office chairs, double canning seat only.</li> <li>iii) office chairs, single caning back only.</li> <li>iv) office chairs, double caning back only.</li> <li>v) easy chairs, single caning seat only.</li> <li>vi) easy chairs, double caning seat only.</li> <li>vii) easy chairs, single caning only, back and seat in one piece.</li> <li>viii) easy chairs, double caning back &amp; seat in one piece or couches with caned area about 16 Sft (1.5 Sqm).</li> </ul>	Each Each Each Each Each Each Each	302.60 389.05 216.15 345.85 216.15 605.20 864.60 1,296.90	338.35 439.50 218.40 365.15 264.05 676.65 1,158.75 2,011.30	Each Each Each Each Each Each Each	302.60 389.05 216.15 345.85 216.15 605.20 864.60 1,296.90	338.35 439.50 218.40 365.15 264.05 676.65 1,158.75 2,011.30		
20	Making and fixing Hat pegs ordinary.	Each	155.65	519.00	Each	155.65	519.00		
21	Weaving charpoy.	Each	562.00	-	Each	562.00	-		
22	Sweeping chimney.	Each	126.95	128.25	Each	126.95	128.25		
23	Picture railing, including making, fixing and painting.	Per Lft.	44.55	121.45	Per LM	146.10	398.55		
24	Cutting fuel wood, from plantation.	100Kg	170.00	-	100Kg	170.00	-		
25	Splitting fuel wood.	100Kg	356.10	-	100Kg	356.10	-		

	MRS, 1st BI-ANNU	JAL-2019	(1st JANU)	ARY-2019 to	30th JUNE	-2019) DIS	STRICT ATTO	OCK	
Sr.	Description		Rate (British S)	/stem)	Ra	ate (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	575.85		100Kg of Char- coal	575.85	-		
27	Filling cement bags with coal and sewing (including cost of strings).	100Cft.	1,561.35	1,564.50	cu.m	551.45	552.60		
28	Supplying manure.	Cart Load	190.40	326.35	Cart Load	190.40	326.35		Capacity of cart, 20 Cft. (0.57 cu.m).
29	Washing punkha frills.	Each	172.90	-	Each	172.90	-		
30	Washing:-			* )					
	a) table cloth b) napkins, dusters, etc.	Each Each	43.25 28.80		Each Each	43.25 28.80	- -		
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	67.95		Each No.	67.95	-		
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	77.45	16 m 16 m	Each No.	77.45	-		
33	Dredging Sumps.	Per Shift	2,856.15	98 G	Per Shift	2,856.15	-		Not less than five gangmen to be employed for each shift to ensure effective dredging.
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each	207.55	e Depa	Each	207.55	-		
35	Bailing out water:-								
	a) by hand b) by pump	1000 Cft. 1000 Cft.	2,284.92 254.10	- 459.30	cu.m ditto	80.70 9.00	- 16.20		Rate includes cost of providing pump, POL and operation charges, etc.
36	Drilling holes in R.C. Trough.	Per Nos.	135.50	-	Per Nos.	135.50	-		
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.								The rate includes overlaps.
	i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick)	Per Sft. Per Sft.	1.30 2.60	2.90 3.95	sq.m sq.m	13.95 27.90	31.10 42.25		
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100 <b>S</b> ft.	1,502.95	6,559.30	sq.m	161.70	705.80		
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	232.30	-	Per Hole	232.30	-		Same rate to be paid for other type of masonry and R.C.C. work.

chapter-26( Misc) Page 163

	MRS, 1st BI-ANNU	JAL-2019	(1st JANU)	ARY-2019 to	30th JUNE	-2019) DIS	STRICT ATTO	OCK	
Sr.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Making 1½"x1½" (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	203.30	-	Per Plank	203.30	-		
	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	76.15		Per hole per c.m depth	30.45			
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	86.45	224.80	sq.m of each spray	9.30	24.20		
	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.								
	i) without cement concrete base. ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm).	100Rft. 100Rft.	8,788.30 9,667.75	27,431.40 30,018.40	Per Metre Per Metre	288.25 317.10	899.75 984.60		

Finance Department

chapter-26( Misc) Page 164